

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1216 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			VEHICLE TYPE PC≖passenger car; LDT=light-duty MDV≖medium-duty vehicle; LVW=l vehicle weight; ALVW=adjusted l	loaded	STAND (LEV≃lo UL	UST EMISSION ARD CATEGORY We emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200		5FMXV02.01GB			PC		EV II SULEV	150K / 150K						
No.	FAMI	LY (E	TIVE VAF)	No.	SPECIAL FEATI EMISSION CONTROL S	URES &	S (ECS)	* = not applicable	OC/TWC=oxidizing/3-way	at. ADSTWC≃adsorbing TWC				
1	5FMXR0120GCX			1	TWC(2), HO2S			MAF5/MAF5#air-fuel ratio se	D2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust					
2		*				*			gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SCaturbo (super charge)					
3	•			3		*		⊠ I BI≖ t⊓rottie Dody Injection						
4		• •				*	***************************************	CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parailel (2) suffix=series						
EVAF No.		CS lo.	ENGINI SIZE (L		VEHICLE MAKES & MODELS	VEHIC		ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1		1 2.0						Ford Focus, Ford Focus Wagon						
*		*	*		* * * * * * * * * * * * * * * * * * *									
*	• •			*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF = * CH4 RAF = *		NMOG or								carbons CC vity adjustm				
CER	T	STD	NMOG	NMHC	NMHC STD	diurnai+h mg=millig	0. 20EV 1/	r [8,mm]-mu	inning los: 1000 miles	D OKAL	₹ [g/gailo	n dispensed Fahrenheit	=on-board re SFTP=supp	fueling var	Or recovery	gegram	
0.04	8	0.049	CERT [g/mi]			CO [g/mi]		CER	Ox [g/mi]	x [g/mi]		HCHO [mg/mi]		/mi]	Hwy NOx [g/mi]		
		@ 50K	•	+	-	*	*	J CER	31	-	CERT	STD	CERT	STD	CERT	STD	
No.		@ UL	0.010		0.010	0.2	1.0	0.00	5 0.0)2	*	4	*	-	0.003	0.03	
	@ 50	°F & 4K	•	•	•	*	•	•					•	•	*	*	
@ 20	CO [g/mi] @ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/mi] (composite) (composite					CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
50		SFIF Z	≖@UL(IIei		CERT	STD	CERT	STD	CERT	ST	O CI	RT ST	D CERT	STD	CERT	STD	
CERT	4.1			SFTP 1	*	*	*	*	0.006	0.14	4 3	3.1 8.0	0.002	0.20	0.4	2.7	
STD	10.0			SFTP 2	*	*	*	٠	*	•		* *	*	*	*		
@ UL -		EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D		ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L ORV		2-D	RL	ORVR	
CERT	0.17	0.17		0.01	*	*	*	*	*	. *	-		-	*	*	*	
STD	0.35	0.35	0:05	0.20	*	•	*	•	•	*	-			+	 		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are granted a baseline partial zero emission vehicle (PZEV) allowance of 0.2 under 13 CCR Section 1962(c).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this __/S/n day of March 2004.

Allen Jons, Chief

Mobile Source Operations Division