TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0521 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STA (LEV=lo transitio	HAUST EMISSION NDARD CATEGORY w emission vehicle; TLE onal LEV; ULEV=ultra LE ULEV=super ULEV)	V= V;	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		KT04.7V	۸W		MDV: 5,751 - 8,500 pounds ALVW		PA Bin 10 ted ad ARB LEV i ULI	EV	120K / 120K	Gasoline				
No.		/APORATIVE No. SPECIAL FEATURES & *= not applic							OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	5TYXE0190AF0				1	2WU-TWC, 2TWC, 2H	O2S(2), SFI,	MAF	MAFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust					
2	•				2	*	· · · · · · · · · · · · · · · · · · ·	ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI					
3	*				3	•		-ШТВ	ITBI= throttle body injection TC/SC=turbo /super charger					
4		•			4	*		dla	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.	VEHICLES S					ES SUBJECT TO SFTP ABBREVIATIONS:								
1		1	4.7						Lexi	us LX 470 (2WD a	nd 4WD)			
*		*	*		Toyota Land Cruiser Wagon (2WD and 4WD), Lexus LX 470 (2WD and 4WD)									
*								*			· · · · · · · · · · · · · · · · · · ·			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FLE RAGE [g		NMOG @ CH4 R	RAF = *	NMOG or	or mirroger	1 パしパしゃ1	rormaidenv	/de PM≖o	articulate	matter	RAFEROS	carbons C	mant factor	2/2 D. (-/4-	-61-012 day.
CER	CERT STD		NMOG NMHC		NMHC	diurnai+ho mg=milligi	icanak ur	. [g/mi]=rui	nning loss 1000 miles	OKVK [g	/gallon d	lispensed] hrenheit	=on-board r	efueling var	or recovery ederal test p	α=gram
*	* *		CERT CERT [g/mi] [g/mi]		[g/mi]		g/mi]	NC	x [g/mi]	H	CHO [n		PM [/mi]		x [g/mi]
ega Andreg (gegenning	page action with the		favrrri	[A, m,]		CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	0.081	*	0.160	1.1	4.4	0.2	0.4		1	18	*	*	0.14	0.53
		@ UL	0.102	*	0.230	1.7	6.4	0.4	0.6	-	1	27	*	*	0.25	0.80
	@ 50°F	& 4K	*	*	*	*		*	*		*	*	*	*	*	*
@ 20	°F& 📓	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			(composite) (co			O [g/mi] NMHC+No					NMHC+NOx [g/mi] [SC03]		CO [g/mi] (SC03)	
50	K	SFTP 2 = @ UL (Tier 1,		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T STI	CER	STD	CERT	STD
CERT	5.3		SI	FTP @ 4K	*	+	*	*	0.1	0.6	7.9	11.	8 0.15	0.44	0.2	4.0
STD	12.5		SFT	P @ 120K	0.40	1.65	3.4	7.0	*	*		•	•	*	•	*
@ UL		/APORA	TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
_	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI		2-D	RL	ORVR
CERT	0.7	0.9	0.02	*	*	*	*	*	*	*	*	*	*	+	•	*
STD	2.0	2.5	0.05	*	*	*	•	•	*	*	*	•	+	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of July 2004

Allen Lyons, Chief

Mobile Source Operations Division