

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=ilght-dut truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STANDA ; (LEV=low em transitional t	IST EMISSION RD CATEGORY ission vehicle; TLEV= LEV; ULEV=ultra LEV; V=super ULEV)	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)		
200		5KMXV02.0LPC			PC	LE	V II SULEV	150K: EXH/ORVR 150K: EVAF	Gasoline (Tier 2 Unleaded)		
No.		APORATIVE NILY (EVAF)			SPECIAL FEATU EMISSION CONTROL S		OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	5KM	MXR0110PPL			WUTWC, TWO	C, HO2S(2), SFI, OB	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas rectrculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super_charper				
2		•				*					
3		•				*					
4		*		4		*	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVA		cs	ENGINE		VEHICLE	VEHICLES SUBJ		ABBREVIATIONS:			
No.		No.	SIZE (L		MAKES & MODELS	STANDARDS AR	E <u>UNDERLINED</u>	ABBREVIATIONS:			
		1 2.0					Kia Spectra				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
CER			NMOG NMHC		NMHC	mg=millig	ot-soak K ram mi=	∟ įg/mij≕ru ≕mile K≃ʻ	nning loss 1000 miles	ORVI	R [g/gailo: degrees F	n dispensed] ahrenheit	on-board r⇒ SFTP=sup	efueling vap plemental fe	or recovery derail test pr	g=gram rocedure
0.05			CERT	CERT [g/mi]	[g/mi]		CO [g/mi]		NOx [g/mi]		нсно	[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]	
			[g/mi]			CERT	STD	CER	r st	D	CERT	STD	CERT	STD	CERT	STD
1.0		@ 50K	*	*	<u> </u>	*	•	. *	•		*	*	•	*	*	*
	27	@ UL	0.007	*	0.010	0.2	1.0	0.00	0.0	2	0.1	4	*	*	0.001	0.03
F.4	@ 50°	F & 4K	0.015	*	0.020	0.2	1.0	0.004	0.0	2	0.4	8	*	*	*	*
CO [@ 20	g/mi] °F &	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/m (composite) (composi			NMHC+NOx [g/mi] [US06]				HC+NOx		CO [g/mi] [SC03]			
50K		SFTP 2 = @ UL (T		r 1, TLEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD
CERT	1.4	. Indian		SFTP 1	•	*	+	*	0.01	0.1	4 5	.3 8.0	0.00	0.20	0.6	2.7
STD	10.0			SFTP 2	*	*	*	•	*	•		* *	•	*		*
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	- ORVI	R 3-D	2-D	RL	ORVR
CERT	0.24	0.27	7 0.02	0.02	*	*	*	*	*	*	*		•	•	· ·	*
STD	0.35	0.35	5 0.05	0.20	*	*	*	. *	*	*	*	-	 •	•		*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

BE IT FURTHER RESOLVED: That the listed vehicle models are granted a baseline partial zero emission vehicle (PZEV) allowance of 0.2 under 13 CCR Section 1962(c).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of June 2004.

111 2

Allen Lyons, Chief Mobile Source Operations Division