Californi	a Environme	ntal Protectio	stection Agency				
AIR	RESO	URCES	S BO	ARD			

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROUP			(PC	VEHICLE TYPE =passenger car; LDT=light-duty truck;	EXHAUST EMISSION STANDARD CATEGORY				SEFUL LIF	FUEL TYPE			
YEAR IEST GROUP			MC	V=medium-duty vehicle: LVW=loaded	(LEV=low emission vehicle; TLEV= transitional LEV;			EVAF 1		EVAF 2		(CNG/LNG=compress ed/ liquefied natural		
				_		ehicle weight; ALVW=adjusted LVW)	SULEV=super ULEV)			H	EVAP/	EXH/	EVAP	gas; LPG=liquefied petroleum gas)
200	6	6BMXB03.0UL2		P((P)	C and LDT ≤ 6,000 pounds GVW C; LDT 3,751-5,750 pounds LVW)	LEV II ULEV				ORVR	ORVR	EVAP	Gasoline	
<u> </u>	EV	POR/			<u> </u>				120	Ж	100K	120K	150K	Gasoline
No.		AILY (E		N) .	SPECIAL FEATURES EMISSION CONTROL SYSTEM	& AS (ECS)	* = not applica	able		TWC=oxidiz	ing/3-way	at. ADSTW	/C≖adsorbing TWC sensor/heated O2S
1	6BN	IXR01	36E46	(PC; L No. 1 2 3 NE (L) M		2TWC, 2HAFS, 2HO2	2TWC, 2HAFS, 2HO2S, SFI, AIR, OBD (F)						hoteon/heated	AFS EGD avhaurat and
2	6BN	XR01	28E85	2		*			MFI/SFI= multiport fuel injection/sequential MFI					
3		*		3		*		<pre>cooler OBD (F) / (P)=full /partial on-board diagnostic prefix</pre>						
EVA		ECS	ENGIN			VEHICLE	ICLES SUB I	ECT TO SFTP		₩2=p	arallel (2)	suffix=serie	5	
No.	_	No.	SIZE (L)		MAKES & MODELS STAL	NDARDS AR	E UNDERLINED						
1		1	2.5				BMW:	(PC) 325Ci, 32	25010	Conv	/ertible			
1		1	3.0		BMW: (PC) 330Cl, 330Cl Convertible, 330Cl Convertible (Sport Package)									
2	_	1	3.0				BMW: (LDT	3,751 - 5,750 p	ound	e 1 \	AN) Y2 2 (Sport Pa	ckage)	
*		•	*					*	June	3 61	11 13 3.0	<u> </u>		
*		*	*					*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *				NMOG of	CH4=met	hane NMC an HCHO	G=non-CH4 =formaidehy	organic g	ases N	MHC≃no	n-CH4 hydro	carbons C	O=carbon n tment factor	nonoxide M	Ox=oxides	
PC/LD	T1	LDT2	NMOG	NMHC	NMHC STD [g/mi]	diurnal+1 mg=millig	ot-soak F gram mi		nning loss 1000 miles	ONTR	[B, Ballot	dispensed ahrenheit	f≂on-board r	refueling var	DOT FRCOVAN	/ 0=0ram
0.046	8	0.062	CERT [g/mi]	CERT [g/mi]			[g/mi]	NC	Dx [g/mi]		нсно [mg/mi]	PM [plemental fo g/mi])x [g/mi]
	STOCK STOCK					CERT	STD	CERI	r st	DC	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.008	•	0.040	0.5	1.7	0.003	3 0.0	5	0.3	8	*	*	0.003	0.07
		@ UL	0.009	*	0.055	0.6	2.1	0.003	0.0	7	1.0	11	•	*	0.004	0.09
	@ 50	°F & 4K	0.019	*	0.080	0.7	1.7	0.02	0.0	5	0.5	16	*	*	*	0.09
CO [(@ 20°F	CO [g/mi] SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			<u>(composite)</u> (comp		g/mi] NMHC+NC posite) [g/mi] [USC		[US06]	06] [U\$06]		NMHC+NOx [g/mi] [SC03]		CO [S	[g/mi] C03]		
CERT					CERI	STD	CERT	STD	CERT	STD	CE	RT STI	CER	T STD	CERT	STD
UERI	2.9			SFTP 1	•	*	•	•	0.01	0.14	2.	6 8.0	0.003	3 0.20	0.6	2.7
STD	10.0			SFTP 2	*	•	*	•	•	*	•		+	*		2.1
@ UL -	E	VAPORA	TIVE FAM	LY 1	EVA	PORATIV	E FAMIL	Y2	EVA	PORAT		MII V 2		VADODAT		-
3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR			_			VAPORAT	VE FAMI	LY 4	
CERT	1.0	1.9	0.02	0.07	0.45	0.27	0.01		3-D	2-D	RL	ORV	२ 3-D	2-D	RL	ORVR
STD	2.0	2.5		0.20	0.45			0.06	-	*	+ *	*	*		*	
		2.5	0.05	0.20	0.00	0.85	0.05	0.20	*	*	*	*	*		•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That certification to the evaporative emission standards in 13 CCR 1976(b)(1)(B)-(C) listed above has been permitted pursuant to 13 CCR 1976(b)(1)(F)-Endnote 3(b).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of September 2005.

Allen Lyons, Chief

Mobile Source Operations Division