		EXECUTIVE ORDER A-014-0546
California Environmental Protection Agency	TOYOTA MOTOR CORPORATION	New Passenger Cars, Light-Duty Trucks
California Environmental Protection Ageney		and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		IESI GROUP M				VEHICLE TYPE C=passengercar; LDT=light-du DV=medium-duty vehicle; LVW- vehicle weight; ALVW=adjusted	=loaded I LVW)	EXHAUST EMISSION STANDARD CATEGORY {LEV=low emission vehicle; TLEV= transitiona! LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles) 120K / 150K	FUEL TYPE (CNG/LNG=compressed/ figuefied natural gas; LPG=liguefied petroleum gas) Gasoline		
2006 6TYXT04.7PKV					0	LDT: 6001-8500# GVW ver 3750# LVW, 3751-5750#	ALVW							
No. 1 2 3	FAMI	EVAPORATIVE FAMILY (EVAF) 6TYXR0190P32 1 - 2 - 3				SPECIAL FEAT EMISSION CONTROL 2WU-TWC, 2TWC, 2	URES & SYSTEM	S (ECS)	* = not applicable AIR, OBD (F)	AF Gat AIF	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing T WU= warm-up cat. O25/HO2S=oxygen sensor/heated AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exh gas recirculation AIR/PAIR=secondary air injection/pu AIR MFI/SFI= multiport fuel injection/sequential MF TBI= throttle body injection TC/SC=turbo /super charf CAC=charge air cooler OBD (F) / (P)=full /partial on-br diagnostic prefix 2=parallel (2) suffix=series			
4		*			4	VEHICLE	VEH	CLES SUB.	ECT TO SETP					
EVA No.		CS No.	ENGI SIZE			MAKES & MODELS	STAN	DARDS AR	E UNDERLINED					
1		1	4.7					<u>TOY</u>	OTA TUNDRA 2WD	<u>/477</u>	<u></u>			
*		*	*											
*		*	•								· · · · · · · · · · · · · · · · · · ·			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	G FLEET AGE [g/mi]	N	MOG @ I CH4 RA	RAF = * .F = *	NMOG or NMHC	CH4=meth of nitroger dlurnal+ho	t-soak RL	ormaldehy [g/mi]=run	de PM≕pa ning loss ∣	ORVR fo/	nation di	spensed]=	carbons CC tivity adjustr on-board re SFTP=supp	fuelling vag	or recovery	g=gram
CERT	STD		NOG	NMHC	STD	mg=milligr			000 miles x [g/mi]		F=degrees Fahrenheit HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.047	0.062		ERT	CERT [g/ml]	[g/ml]		g/mi] STD	CERT	STD			STD	CERT	STD	CERT	STD
			.028		0.040	0.3	1.7	0.04	0.05	•	,	8	*	•	0.01	0.07
Alex in the	@ 501				0.055	0.4	2.1	0.04	0.07		· · · ·	11	*	*	0.01	0.09
	@U		.033		0.000			*	+			*	*	*	*	*
	@ 50°F & 4K * *					Ov Internil		o/mil	NMHC	+NOx		[g/mi]	NM	HC+NOx		[g/mi]
	CO [g/mi] SFTP 1 = 6		4K (SULE	EV, ULEV, ar 1, TLEV)	NMHC+N (comp				[g/mi] [U\$06]		ml] [SC03]		5C03]
@ 20° 50K	- 13 A	2=@	UL (Tier 1	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER				CERT	+
	2.1	Lizik		SFTP 1		*	•	*	0.01	0.40	0.2	10.5	5 0.04	0.31	0.4	3.5
└		i i i	- in 11	SFTP 2	*	*	*	+	*	+	•	•	*	*	*	<u> </u>
STD	12.5					PORATIVI	EAMILY	(2)	EVA	ORATIV	E FAN	ILY 3	E	VAPORAT	IVE FAM	
@ UL		_	VE FAM					ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
	3-D 2	2-D	RL	ORVR		2-D					*	*	*	*	*	
CERT	0.36 (.36	0.004	0.03		*					*	+	*		*	+
STD	0.90	.15	0.05	0,20	*	*	*	. اــــــــــــــــــــــــــــــــــــ			L	1		_1		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____2922 ___ day of July 2005.

Haphael Susnair

Mobile Source Operations Division