California Environmental Protection Agency AIR RESOURCES BOARD	EXECUTIVE ORDER A-014-0547				
	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles				

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD. YEA					N	VEHICLE TYPE C=passenger car; LDT=light-duty IDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted l	loaded LVW)	STAN (LEV=low transitior	IAUST EMISSION DARD CATEGORY emission vehicle; TLE nal LEV; ULEV-ulfra LE ILEV=super ULEV)	V≠ V;	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE {CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	_		T04.7PK	W	0	LDT: 6001-8500# GVW, ver 3750# LVW, 5751-8500#	ALVW			120K / 150K	Gasoline				
No. 1	FAM	IILY (E	ATIVE EVAF) D0P32		No.	SPECIAL FEAT EMISSION CONTROL S	SYSTEM	S (ECS)	* = not applicable	1100	= warm-up cat. O2S/H	cat. ADSTWC=adsorbing TWC 02S=oxygen sensor/heated 02S			
2					2	2WU-TWC, 2TWC, 2	1AF3, 2	1023, SFI, J	AIR, OBD (F)	- gas	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*	* *			······	*		TBI	TBI= throttle body injection TC/SC=turbo Sequencial mir CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4		· · ·					•		diag	gnostic prefix 2=paral	iel (2) suffix=series				
EVAP	-	CS No.	ENGIN SIZE (VEHICLE MAKES & MODELS	VEHIC	CLES SUBJ	ECT TO SFTP	1.1					
1		1	4.7				· · · · · · · · · · · · · · · · · · ·								
*		•	*						RA 2WD/4WD, SE						
*		•	*					·· · · ·	*		······································				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE [g/mi]			NMOG @ RAF = * CH4 RAF = *		NMOG or		CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/m]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	т	STD	CERT CERT		NMHC STD	diurnal+i mg≈milii	or oddie i	C [[] / [] -]	unning lo =1000 mi	33 UKV	rt (y/yai	lon dispe Is Fahren	πseαj=	on-board re	fueling vac	OF TECOVERV	o=oram	
0.04	7 (0.062			CERT [g/mi]	[g/mi]	CERT	[g/mi]		Óx [g/m	(g/mi]		0 [mg/m	i]	PM [g/mi]		federal test procedure Hwy NOx [g/mi]	
							UERI	STD		() S	TD	CERT	ST	D	CERT	STD	CERT	STD
		@ 50K	0.0	30	*	0.040	0.3	1.7	0.0	2 0	.05	*	8		*	*	0.01	0.07
	Frank S	@ UL	0.0	35	•	0.055	0.3	2.1	0.0	3 0	.07	*	11		*	*	0.01	0.09
	@ 50	°F & 4K	*		*	*		•	*		*	•	*			*	*	
@ 20	@ 20°F& 📳		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/ (composite) (compo			iposite}	site} [g/mi] [USC				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
F					,	CERT	STD	CERT	STD	CERI	r∣ st	D (ERT	STD	CERT	STD	CERT	STD
CERT	2.1				SFTP 1	•	*	+	*	0.01	0.6	10	3.5	11.8	0.03	0.44	0.4	4.0
STD	12.5	2.4			SFTP 2	*	*	+	+	*	*		*	*	+	•		+
					_Y 1	EVA	PORATIV	E FAMIL	EVAPORATIVE FAMILY 3					EVAPORATIVE FAMILY 4				
	3-D	2-D	D RL		ÖRVR	3-D	2-D	RL	ORVR	3-D	2-D							
CERT	0,36	0.3	6 (0.004	0.03	*	*	*			- 2-0	_ <u> </u> _'			3-D	2-D	RL	ORVR
STD	0.90	1.1		0.05		<u> </u>					↓		-	*	*	*	*	
5.0	0.80	1,13		0.05	0.20		-	•	*	*	*		*	*	*	*	*	± 1

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2005.

Replace Journourt

Mobile Source Operations Division