California Environmental Protection Agency										
✐≣	AIR	RESO	URCES	BOARD						

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	-		-							······································				
MODI					VEHICLE TYPE PC=passenger car; LDT=light-dut MDV=medium-duty vehicle; LVW= vehicle weight; GVW=gross v	STANDA (LEV=low en transitional	UST EMISSION ARD CATEGORY nission vehicle; TLEV LEV: ULEV=ultra LEV V=super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
			(T03.914		LDT: <6000# GVW, 3751-5750			SEPA Bin 5 s ARB "LEV II" LEV	/ 120K / 150K	Flexible Fuel: Ethanol (E85) / Gasoline (Tier 2 Unleaded)				
No.				No	SPECIAL FEA	TURES	& MS (ECS)	* = not applicable	WU= warm-up cat. O2S/H	cat. ADSTWC=adsorbing TWC O2S=oxygen sensor/heated O2S ensor/heated AFS_EGR=exhaust				
	FAMILY (EVAF)						S(2),OBD (F)	and an all shows AIP(PA)	gas recirculation AIR/PAIR=secondary air injection/puise					
1	7GMXR0170956 1			<u> </u>	,, ,, , ,, ,, ,, ,, , ,, ,, ,, , ,, ,, ,, , ,, , , ,			TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2	7Gl	7GMXR0203958 2 + 3												
3						•	•							
EVA No.		ECS No.	SIZE (1) MAKES & MODELS STA		NDARDS AF	BUBJECT TO SFTP ABBREVIATIONS: ARE UNDERLINED								
			3.9	-+		Chevrolet Uplander FWD, Pontiac Montana SV6 FWD								
1	+				Chevrolet IIn	Chevrolet Uplander FWD, Pontiac Montana SV6 FWD, Buick Terraza FWD, Saturn Relay FWD								
2		1	3.9	_+	Clievioler.op									
+	_	*	•											

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi] NMOG @ RAF = * (*); CH4 RAF = *		NMOG or NMHC	of nitrogen diurnal+ho	t-soak RL	ormaldehyd [g/mi]=runi	organic gas le PM=par ting loss (X0 miles	ORVR [p/g	allon	RAF=reac dispensed] ahrenheit	n hisodence	O=carbon mo tment factor refueling vapo plemental feo	or recovery	ģ=gram			
CERT	STD	NMOG NMHC			STD	trig mining and			(g/mi)		HCHO [mg/m		PM (Hwy NOx [g/mi]	
0.054	0.055		RT		[g/mi]	CERT	STD	CERT	ŚTD	CEF	<u> </u>	STD	CERT	STD	CERT	STD
0.004	0.000	[g/mi]		[Bund		1.1 3.4	0.04	0.05			15			0.02	0.07	
1.95	a 50)		056	•	0.075	(1.7)	(3.4)	(0.03)	(0.05)	c c		(15)	-		(0.03)	(0.07)
	S. N	10.1	032)		0.090	1.3	4.2	0.06	0.07	1		18	t	•	0.04	0.09
2.4.9.00	🦓 🖉 🖉 U		061	•	(0.090)	(1.9)	(4.2)	(0.05)	(0.07)	i C)	(18)		<u></u>	(0.05)	(0.09
1.	A 14 14	10.	036)	<u> </u>	10.0001	•		+	*	•		•	*	•	*	•
@ 50°F & 4K * *							NMHC			0 [g/ml]	NA	NMHC+NOx		[g/mi]		
CO [g/mi] SFTP 1 = @ 4K (SULEV, ULEV,				MHC+NOx [g/mi] CO [g (composite) (comp							[g/mi] [SC03]		[SC03]			
@ 20°F& 2 LE		LEV) or 50K (Tier 1, TLEV) 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	ST	
			C. C. Street					<u> </u> †	*	*	-	· · ·	*	*	*	
CERT	(3.5)		(A. 181)	@ 4K	•	•		\ <u>'</u>	(0.08)	(0.25)	{2.	3) (10	.5) (0.0	8) (0.27)	(2.4)	(3.5
	(3.3) •			@ UL	*	*	•	•	•	*	12	6) (14	6) *		(2.7)	(4.9
STD	(12.5)	85 day	领表、		(0.11)	(0.95)		<u></u>		00170			<u></u>	EVAPORAT		LY 4
	EVAPO	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3						ORV	
@ UL -		2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL		K 3-D			
CERT		.26	0.00	(0.04)	0.22	0.35	0.00	(0.04)	*	*	*		<u> </u>	_	-+	*
STD		.85	0.05	0.20	0.65	0.85	0.05	0.20	*	•	•	*				

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to Title 40, Code of Federal Regulations (40 CFR), Section 1811-04(p).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-006-1383 dated April 27, 2006.

Executed at El Monte, California on this

3 day of August 2006 H

Annette Hebert, Chief Mobile Source Operations Division