

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			(P M	VEHICLE TYPE C=passenger car; LDT=light-duty tr DV=medium-duty vehicle; LVW=loz vehicle weight; GVW=gross VW)	aded	STAND (LEV=low of transitions	AUST EMISSION DARD CATEGORY emission vehicle; TLI II LEV; ULEV=ultra LI EV=super ULEV)	ĖV≕	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		7GMXT05.3386			L,	LDT: 6001-8500# GVW, 3751-5750# ALVW			'LEV II" LEV		120K / 150K	Gasoline (Tier 2 Unleaded) plus Battery- Assist			
No.		APORATIVE MILY (EVAF)			ło.	SPECIAL FEATUR EMISSION CONTROL SY	RES & 'STEMS (I	ECS)	* = not applicable	e [OC/TWC=oxidizing/3-way car	. ADSTWC=adsorbing TWC			
1	7GMXR0176820			100	1	2TWC, 2HC				WU= warm-up cat. 02S/H02S=oxygen sensor/heated 02S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger					
2		•			2		*								
3		•			3		*								
4		*			4		*			CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVA	FII	ECS	ENGIN	ΙĒ		VEHICLE	VEHICL	ES SLIB I	ECT TO SFTP	- 10					
No.		No.	SIZE (L)			MAKES & MODELS	BREVIATIONS:								
1		1	5.3			MAKES & MODELS STANDARDS ARE <u>UNDERLINED</u> ABBREVIATIONS: Chevrolet: C1500 Silverado Classic Hybrid 2WD, K1500 Silverado Classic Hybrid 4WD									
1		1	5.3			GMC: C1500 Sierra Classic Hybrid 2WD, K1500 Sierra Classic Hybrid 4WD									
*		* *													
*		* *													

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE [NMOG @ RAF= * CH4 RAF = *			NMOG or									arbon mono		
CER	CERT STD		NMOG CERT		NMHC CERT	NMHC STD	mg=millig	ram mi	⊏ [Ձ/Ուոյ~ւ	unning los 1000 mile	S UK	rk įgrgano	n dispensed Fahrenheit]≖on-board i	refueling vap plemental fe	or recovery	g=gram
0.05	4	0.055	[g/mi]		[g/mi]	[g/mi]	CERT	[g/mi] STD	CER	Ox [g/mi] TD	HCHO	[mg/mi]	PM [g/mi)	Hwy NO	x [g/mi]
	4 1140	@ 50K	0.0	147	*	0.075	1.9	+			-	CERT	STD	CERT	STD	CERT	STD
	1640						1.9	3.4	0.03	3 0	05	*	15	*	1 *	0.01	0.07
2.2	<u> </u>		0.0	58	*	0.090	2.0	4.2	0.04	1 0.	07	*	18	*	*	0.01	0.09
	@ 50	F & 4K	•	•		_ *	•	*			•	*	*	*	•	*	*
CO [@ 20 50	°F&	LE	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			NMHC+NO (comp	osite)	(com	g/mi] posite)		IC+NC		CO [g/mi] [US06]		HC+NOx ni) [SC03]		[g/mi] C031
	<u> </u>	SFIF Z	- @ UI	_ (Tier 1	, ILEV)	CERT	STD	CERT	STD	CERT	S	TD CE	RT ST	D CER	T STD	CERT	STD
CERT	3.5	17.10		SF	TP @ 4K	. •	*	*	*	0.04	0.	40 5	.9 10.	5 0.02	0.31	1.4	3.5
STD	12.5	444		SF	TP @ UL	*	*	*			١.,	•	* +	•	*	•	•
@ UL		VAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAP					APOR	ATIVE F	AMILY 3	E	EVAPORATIVE FAMILY 4		
_	3-D	2-D		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-0	RI	ORV		2-D	RL	ORVR
CERT	0.48	0.35	<u>. </u>	0.00	0.03		*	•	-	*		*	*		+	*	•
STD	0.90	1.15		0.05	0.20	*	•	*	*	*	*	*	-	+	*	+	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of March 2006.

Allen Lyens, Chief

Mobile Source Operations Division