

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

WINCH	CEI	uncar	101113	9,	ante	·u.									
MOD! YEA		TEST GROUP			(P	VEHICLE TYPE C=passenger car; LDT=light-duty truck DV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	STAND (LEV=low of transitional	AUST EMISSION DARD CATEGORY emission vehicle; TLEV= at LEV; ULEV=ultra LEV; LEV=super ULEV)	EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	7	7GMXT06.0394			MDV: 8501-10000# GVW	USE	EPA Bin 8a (opt) d as ARB LEV2-LEV	EXH/ORVR: 120K EVAF: 150K	Gasoline (Tier 2 Unleaded)						
No.			APORATIVE MILY (EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYST	& EMS (ECS)	- 1104 abbitamin	MARIE WARRANT COL (125/HO)	t. ADSTWC=adsorbing TWC 2S=oxygen sensor/heated O2S					
			XR0223841			2TWC, 2HO2S	(2), SFI, OBD (and recirculation AIR/PAIRs	sor/heated AFS EGR=exhaust secondary air injection/pulsed						
							*	NAID MEI/SEL multiport fi	uel infection/sequential MFI						
2	7G	MXR0260843			2			TBI= throttle body injection	TC/SC=turbo /super charger D (F) / (P)=full /partial on-board						
3		*	*		3			diagnostic prefix 2=paralle	(2) suffix=series						
4		*	•		4		*								
EVA	F	ECS ENGINE		NE	\top		EHICLES SUB.	JECT TO SFTP	BBREVIATIONS:						
No		No. SIZI				MAKES & MODELS STANDARDS ARE UNDERLINED ABBREVIATION STANDARDS ARE UNDERLINED									
1	1		4.8			Chevrolet G1500/2500 Express 2WD, GMC G1500/2500 Savana Passenger 2WD									
1	-	4	8.1	6.0		Chevrolet: G15/25 Van 2WD Conv, G1500/2500 Express 2WD, G3500 Express 2WD; GMC: G15/25 Savana 2WD Cargo Conv, Chevrolet: G15/25 Van 2WD Conv, G1500/2500 Express 2WD, G3500 Express 2WD; GMC: G15/25 Savana 2WD Cargo Conv,									
1 1	1		6.0	<i>J</i>											
2	2 1		6.0	3.0		Chevrolet: C2500 Suburban 2WD, K2500 Suburban 4WD; GMC: C2500 Yukon XL 2WD, K2500 Yukon XL 4WD									
	\neg				\top										
	- 1		1	_											

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

tooting	on gass.		,						1104110	6	14 hudroon	han COsc	arbon mono	vide NOx=	oxides of
NMOG FLEET NMC AVERAGE [g/mi] Ch			NMOG @ RAF=* CH4 RAF = *		nitrogen diurnal+ho	HCHO≕ion ot-soak RL	naldehyde` [g/mi] ≠runi	PM≡parti ning loss	ORVR [g/	gallon	dispensed]	=on-board i	arbon mono ent factor efueling vap plemental fe	or recovery	g=gram
CERT	STD	NMOG	NMHC CERT	NMHC	mg=milligram mi=mi CO [g/mi]		NOx [g/mi]		r≖aegi	F=degrees Fahrenheit HCHO [mg/mi]		PM [Dietiticinal to	Hwy NOx [g/mi]	
*	*	CERT [g/mi]	[g/mi]	[g/mi]	CERT	STD	CERT	STD			STD	CERT	STD	CERT	STD
10.00	@ 50K			0.125	1.9	3.4	0.07	0.14	,	•	15	*	*	*	*
					2.2	4.2	0.08	0.20	, ,	*	18	*	*	*	*
\times (a, b, b)	@ UL	0.100		0.156	2.2	4.2	0.00			*	*	*	*	*	*
(₫ 50°F & 4K								110		O faimil	I MIL	HC+NOx	CO	[g/mi]
CO [g/m	SFTP 1	@ 4K (SULI	V, ULEV,	NMHC+N		CO [g		NMHC [g/mi]		'	CO [g/mi] [US06]		ni] [SC03]		C03]
@ 20°F & 50K	LE LE	V) or 50K (Tie ∈ @ UL (Tier	er 1, TLEV) [1, TLEV)	(comp	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD
ERT *			TP @ 4K	*	*		*	*	*	,		*	*	*	•
			TP @ UL	—	*	*		*	*	,		*	*	*	*
STD		ORIGINAL PROPERTY.		F144	DODATO	E FAMILY	(2)	ΕVΑ	PORATI	VE FA	MILY 3		VAPORAT	IVE FAM	ILY 4
@ UL	EVAPORA		_		2-D	RL	ORVR	3-D	2-D	RI		R 3-D	2-D	RL	ORV
	3-D 2-D		ORVR	3-D 0.38	0.28	0.00	0.02	•	*	*		*	*	*	*
	.41 0.54		0.09	1.00	1.25	0.05	0.20	*	*	*	*	*	*	*	*
TD 1	.00 1.2	0.03	3.20	1.00									. 11		a. T :41.

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______ day of January 2006.

Allen Lyons, Chief

Mobile Source Operations Division