

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

daide	005	Hificati	on is t	ar	ante	ed.								
MODE	L	tification is grat			(P	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STAND (LEV=lo	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
					+	PC and LDT ≤ 6,000 pounds GVW C; LDT 3,751 – 5,750 pounds LVW)	pounds GVW LEV ILEV			Gasoline				
200°	ΕV	7FJXB02.5PRA			No.	SPECIAL FEATURES &	IS (EUS)	* = not applicable	WU= warm-up cat. U25/Ht	at. ADSTWC=adsorbing TWC D2S=oxygen sensor/heated O2S insor/heated AFS EGR=exhaust				
1	7F	JXR012	MILY (EVAF) XR01253BG			TWC(2), HAFS, HO2S, SFI,	AIR, TC, CA	AFS/HAFS=air-fuel ratio sension and are injection/pulsed gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MF/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3	7F	JXR01253CH			3									
4		*			4	VEHICLE VEH	ICLES SUB	JECT TO SETP						
	EVAF E		SIZE	<u>(L)</u>		MAYES & MODELS STANDARDS ARE STOCKED BY OTO MADDEZA WAGON WRX								
$\frac{1}{2}$	$\frac{1}{2}$ $\frac{1}{1}$		2.5 2.5	i _		SUBARU: (PC) FORESTER 2.5XT, IMPREZA (WRX, S1), IMP								
2	2 1 2.5			· 	_									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based are as follows (compliance with the 50 °F testing requirement). on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet on the manufacturer's submitted compliance plan in flied of testing). Any depit in the manufacturer's Niviod Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

ual- or	flexibl	e-fue	eled ven	icles, in	esiba	11G OLI		304	ale oze	- NMHC	=non-CH4	hydrocar	bons CO=0	carbon mo	noxide NO	x=oxides
NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *			AF = '	NMOG or NMHC	of nitroger	n HCHO⊐io ot-soak RL	(g/mi]≃run		ORVR (g/g F=degre	ialion dist ees Fahre	ensed)=0 nhelt S	n-board ren FTP=supple	mental fed		ocedure	
STD			NMOG CERT	NMHC CERT [g/mi]	STD [g/mi]	mg=mliligi CO			x [g/mi]		HO (mg/		PM [g/r	STD	CERT	STD
PC/LDT			[g/mi]			CERT	STD	CERT	STD				*	•	0.01	0.07
0.043			0,025	*	0.075	0.8	3.4	0.01	0.05	0.4		15	+		0.01	0.09
	9 9 9 9			 	0.090	1.0	4.2	0.01	0.07	1		18		+		*
1427	· · · · · · · · · · · · · · · · · · ·	UL	0.029		0.150	1.7	3.4	0.01	0.05	0.	3	30	<u> </u>			(arlumi)
	@ 50°F & 4K 0.109 *						CO [g/mi]		NMHC	+NOx		[g/mi]	NMH [a/mi]	C+NOx [SC03]		[g/mi] C03]
CO [9	/mi] 5	SFTP 1 =	@ 4K (SUL	EV, ULEV,	NMHC+NOx [g/mi] (composite)		(composite)		[g/mi]	US06] STD	CERT	S06] STD	CERT	STD	CERT	STD
@ 20°	O 200E 9		v) or suk (≀ ₌@ UL (Tlei	or 50K (Tier 1, TLEV) D UL (Tier 1, TLEV)		STD	CERT	STD	CERT		4.5	8.0	0.03	0.20	1.2	2.7
	5.1	le sirûe		SFTP 1	*		İ . <u>* _</u>	*	0.04	0.14	4.5	*	-	*	 	*
CERT				SFTP 2	*	•	•	*		*		l	<u> </u>	ADODAT	IVE FAM	I Y 4
STD	STD 10.0 SFIP 2 EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				2-D	RL	ORVR	
@ UL				ORVR		2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-0	+ - 2-D	+	•
1	3-D	2-D		_ +	0.30	0.40	0.00	0.02		*		-	-	 	+	•
CERT	0.34		_ +		0.50	0.65	0.05	0.20				<u>. </u>		.l — -—		
STD	0.50	0.6	_ +		0.50	0.65	0.05	0.20			L—		tod to o	omnlia	nce wif	h 7

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-002-0148 dated April 21, 2006.

Executed at El Monte, California on this ______ day of June 2006.

Rayhoel Surrourt

Mobile Source Operations Division