Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

/hich certification is gra  MODEL TEST GROUP  2007 7MBXB03.5U2A			(PC	VEHICLE TYPE c=passenger car; LDT=light-duty ty=medium-duty vehicle; LVW=lo ehicle weight; ALVW=adjusted L PC and LDT> 5,000 pounds 0 C; LDT 3,751 – 5,750 pounds 1	truck; C saded VW) I	ATEGORY vehicle; Ti ULEV≃ultra L	LEV= transitional LEV; EV; SULEV=super ULE\ LEV II ULEV	USEFUL LIFE (UL) (miles) 120K / 150K	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas) Gasoline (Tier 2 Unleaded)			
No. FA	EVAPORATIVE FAMILY (EVAF) 7MEXR0197LNC		No. 1 2 3	SPECIAL FEAT EMISSION CONTROL 2TWC, 2HC	URES & SYSTEMS	(ECS) R, SFI, OBD		OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/H02S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAF No.	EC S No.	ENGIN E SIZE (L) 3.5	-	VEHICLE MAKES & MODELS	STANE	ARDS AR	ECT TO SFTP E UNDERLINED (LDT) ML 350 4MAT)	C, R 350 4MATIC				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, Average" (PC and LDT) and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE STD [g/mi]		NMOG @ RAF= * CH4 RAF = *		NMOG or NMHC	CH4=meth: nitrogen diumai+ho mg=milligr	HCHU≕forn t-soak RL	io/mij≃runi nakianyoa	organic gas PM=partic ning loss 100 miles	ORVR In/o	ter RAF allon dis ses Fahre	pensed]=	ion CO=cally adjustment on-board re SFTP=suppl	nt factor 2 fueling vapo lemental fed	leral test p	ocedure	
	C/LDT1 LDT2		NMOG	NMHC	ן אוט	<u> </u>		NOx [g/mi]		HC	HCHO [mg/ml]		PM [g/mi]		Hwy NOx [g/mi]	
0/20 .			CERT	CERT	[g/mi]		g/mi]		STD	CEF		STD	CERT	STD	CERT	STD
0.043	0.0	55	[g/ml]	[g/mi]		CERT	STD	CERT			<del></del>		*	*	0.01	0.07
		2016	0.026		0.040	0.7	1.7	0.03	0.05	0.3	<u> </u>	8.				0.09
		50K	0.026			<del>                                     </del>	2.1	0.04	0.07	0.4	4	11.	* 1	•	0.01	0.03
		@ UL	0.044	*	0.055	1.0	2.1	0.07		<del></del>		-	-	-	•	•
	<b>建筑的线线</b>				*	T -	*	*						10:10:	CO.	[g/mi]
@ 50°F & 4K				NO CLICA N	Ox [n/mi] CO [g		o/mil	NMHC	+NOx		[g/mi]	NMI	IC+NOX		SC031	
CO Inimil B CEID 1			= @ 4K (SULEY, ULEY,		NMHC+NOx [g/mi] (composite)				[g/mi] [US06]			JS06]		i] [SC03]		STD
@ 20	1	1 F	'V) or 50K (∏	ler 1. TLEV)		STD	CERT	STD	CERT	STD	CERT	STE	CERT	SID		
50	K	SFTP 2	= @ UL (Tie	71, (LEV)	CERT	310	1		0.08	0.14	2.4	8.0	0.04	0.20	0.6	2.7
ERT	3.3			SFTP 1	*	•	l		0,00			<del></del> -	<del>-                                    </del>	-	•	-
ERI	3.3			0		•	•	*		*	*					
STD	STD   10.0		nga (ania) (T. Y	SFTP 2				<u> </u>	EVAPORATIVE I			ILY 3	E'	EVAPORATIVE FAMILY 4		
		/APOR	RATIVE FAMILY 1		EVAPORATIVE FAM			1 2			RL	ORV	3-D	2-D	RL	ORVR
@ UL	3-D	2-1			3-D	2-D	RL	ORVR	3-D	- 2-0		+ ***	•		+	Τ ̄• _
					-	-	•	*	*			+	-	*	-	•
CERT	0,51	0.4 1.1			+	•	*	•	•	*						

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards and Tool Procedures for 2004 and Subsequent Model DC | DT and MDVA (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 31 day of May 2006.

Allen Lyons, Chief
Mobile Source Operations Division