GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1407-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for

MODEL YEAR 2007	TEST GROUP		_	VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=tow emission vehicle; TLEV-transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)	EXHAUST & ORVR FUEL TYP / EVAPORATIVE (CNG/LNG=compr USEFUL LIFE (UL) liquefied natural (miles) LPG=liquefied petr				
yo EV	7 SIMABUS. 3048 D. EVAPORATIVE FAMILY (EVAF) 7 GMXR0117809 7 GMXR0117811 7 CMXR0117811 7 CMXR0117811		No.	PC and LDT <6,000 pounds GVW (PC; LDT 3,751-5750 pounds LVW) SPECIAL FEATURES &	"LEV II" ULEV	120K / 150K	gas) Gasoline (Tier 2 Unleaded)			
1 7GI 2 7GI 3 4			1 2 3 4	EMISSION CONTROL SYSTEMS TWC, HO2S(2), EGR	G (ECS) *= not applicable S, SFI, OBD (F)	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWU= warm-up cat. O2S/HO2S=oxygen sensor/heated AFSHAFS=air-luel ratio sensor/heated AFS EGR=exh. AIR MFUSFi= multiport fuel injection/sequential MFITBI= throttle body injection TC/SC=turbo /super charge CAC=charge air necessary.				
				(LDT2): Che	LES SUBJECT TO SFTP ARDS ARE UNDERLINED AE	diagnostic prefix 2=parallel	(c) / (P)=full /partial on-boal (2) suffix=series			
				(LDT2): Chevrolet Equinox FWD/AWD, Pontiac Torrent FWD/AWD (LDT2): Chevrolet Equinox FWD/AWD, Pontiac Torrent FWD/AWD						

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, ULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable

NMOG FLEET AVERAGE [g/mi]		NMOG @ CH4 R	AF = *	NMOG o	CH4=me	thane NM HCHO=	OG=non-CH formaldehyd Rt fo/mil-n	4 organic	gas NMHO	=non-CH4	hydrocar	bon COzc	rhon mon			
STD-F		-LDT2 055	NMOG CERT	NMHC CERT	1 .010	mg=mill	gram π	i=mile K=	1000 mile:	s ORVR[F=de	natter RA g/gallon di grees Fahi	Spensed)=	on-board re	fueling var	Z/3 D [g/ies	t]=2/3 da
0.04	u.	055	[g/mi]	[g/mi]	[g/ml]	CERT) [g/mi] STC	N	Ox [g/mi]	<u> </u>	ICHO [mi	g/mi]	SFTP=supp PM [g	rentientan 10	Hwy NC	rocedure
	100	@ 50K	0.022		0.040	1.3					ERT	STD	CERT	STD	CERT	STD
	975 A.F	@ UL	0.022	<u> </u>	 	 	1.7	0.02	D.()5	*	8	+	*	0.01	0.07
depart of			U.UZZ	<u> </u>	0.055	1.3	2.1	0.03	0.0	17	*	11	*			
@ 50°F & 4		F & 4K	•	*	*	*	*	-	-			-			0.02	0.09
00 [g/mi]	SFTP 1 =	@ 4K (SULE	VIHEV	NMHC+NC)x (a/mi)	1 00	[g/mi]	1 1114/7	C.NO			•	*	_ *	*
(@)20°F&L (∰) LE		LEV)	EV) or 50K (Tier 1, TLEV) ? = @ UL (Tier 1, TLEV)		(composite)		te) (composite		NMHC+No [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi]	
		OI II Z - (washing and a		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	203]
ERT	3.8		SF	TP @ 4K	*	*	*	*	0.05	0.14	3.1	8.0	0.04	+		STD
STD	10.0		SF	TP @ UL	*	*	*	*	•	*	+	- 5.0	0.04	0.20	1.4	2.7
a	EVAPORATIVE FAMILY 1				EVA	PORATIV	E FAMIL	Y 2	EVA	POPATIL	/E FAMIL	V 2		10000		*
@ UL ∤	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D					VE FAMIL	
ERT	0.42	0.46	0.00	0.02	0.42	0.46	0.00	0.02	3-0	2-0	RL	ORVR	3-D	2-D	RL	ORVE
TD	0.65	0.85	0.05	0.20	0.65	0.85	0.05	0.02	*	+				*	*	- *

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1976(b)(1)(F) footnote 4.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-006-1407 dated April 10, 2006. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division