

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR TEST GROUP			P	VEHICLE TYPE (PC=passenger car; LDT=iight-du truck; MDV=medium-duty vehicle LVW=loaded vehicle weight; ALVW=adjusted LVW)	ity STANDA (LEV=low em transitional I	ST EMISSION RD CATEGORY Ission vehicle; TLEV= LEV; ULEV=ultra LEV; V=super ULEV)	EXHAUST & ORVR /EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	2007 7TYXT03			1	LDT: < 6000# GVW, 3751-5750# LVW		V II SULEV	120K / 150K	Gasoline plus Battery-Assist					
No.		APORATIVE MILY (EVAF)		No.	SPECIAL FEATURE EMISSION CONTROL S		* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC≃adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	7TYXR	YXR0160E52		1	2WU-TWC, TWC,	2HAFS, 2HO2S, SF	AFS/HAFS=air-fuel ratio s	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust pas recirculation AIR/PAIR=secondary air injection/pulsed						
2		•		2		*	·	AIR MFI/SFI= multiport fuel injection/sequential MFI						
3	* :			3		*		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.	ECS No.		ENGIN' SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB. STANDARDS AR	ABBREVIATIONS:							
1	1		3.3		Toyota Highlander Hybrid 2WD/4WD, Lexus RX 400h 2WD/4WD									
*			•				*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NMOG FLEET NMOG @ RAF AVERAGE [g/mi] CH4 RAF =				NMOG or	1100000011	DVD-rar	mainenvoi	ı PMEDAD	ticiliate m	ialder h	A Ezrosztiv	ita adiucima	arbon mono	1/2 D [-	Named In Land	
CER			NMOG NMHC		NMHC STD	mg=mittig	ram mi=	nile K=1	nning loss 1990 miles	OKVK [6	g/gallon ·	dispensed):	on-board re	efueling vap	Ot tecovery	/ o≖oram
0,05	2 .	0.055	CERT [g/mi]	CERT [g/ml]	[g/mi]		[g/mi]	NC			HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
			fatturi	[g/iii]		CERT	STD	CERT	ST	C	ERT	STD	CERT	STD	CERT	STD
		@ 50K	•	•	*	•	•	•	•		+	*	*	•	*	*
		@ UL	0.007	*	0.010	0.02	1.0	0.01	0,0	2	•	4	*	•	0.005	0.03
第4 章	@ 50	°F & 4K	•	•	•	*	*	*	•		*	•	*	•	*	*
CO [@ 20		LE	V) or 50K	ULEV, ULEV, (Tier 1, TLEV)	NMHC+NOx [g/mi] CO [g/mi] (composite) (composite)				NMHC+NOx CO [g/mi] [g/mi] [US06] [US06]			NMHC+NOx [g/ml] [SC03]		CO [g/mi] [SC03]		
50K		SFTP 2	= @ UL (T	@ UL (Tier 1, TLEV)		STD	CERT	STD	CERT	STD	CER	T STD			CERT	STD
CERT	2.0	1000	i ir	SFTP 1	•	*		•	0.03	0.25	0.0	2 10.5	0.02	0.27	0,02	3.5
STD	12.5		nt in	SFTP 2	•	•	*	٠	*	•		*	•		1 -	•
@ UL			ATIVE F		EVA	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-0	R	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	3-D	2-D	RL	ORVR
CERT	0.22	0.13	0.0	1 0.03	*	•	•	*	• 1	*	•	*	•	*	-	
STD	0.50	0.5	0.0	5 0.20	•	•	•	*		*	*	*	*	•	 • • • • • • • • • • • • • • • • • • •	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

BE IT FURTHER RESOLVED: That at the request of the manufacturer, the listed vehicle models are certified to the optional zero-fuel evaporative emission standards in 13 CCR Section 1976 (b)(1)(E) which allows an exhaust NMOG credit of 0.002 grams per mile to be applied against the measured NMOG emissions in certification and in-use testing pursuant to CCR Section 1961(a)(11).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 20 day of July 2006.

Annette Hebert, Chief

Mobile Source Operations Division