TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0580 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty to NDV=medium-duty vehicle; LVW=lovehicle weight; ALVW=adjusted LV	truck; C aded VW) U	ATEGORY vehicle; TL JLEV=ultra Li	EV= transitional LEV; EV; SULEV=super UL	ion EV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)		
200	7	7TYXT04.7BEV			LDT: 6,001-8,500 pounds GV 5751-8500 pounds ALVW	W,		Itra-Low Emission e (LEV II ULEV)		120K /150K	Gasoline		
No.		VAPORATIVE AMILY (EVAF) No.			SPECIAL FEATUREMISSION CONTROL S		(ECS)	* = not applicable	WU	= warm-up cat. O2S/H	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S		
1	1 7TYXR0190P32			1	2WU-TWC,2TWC,2				AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed				
2		•				*			AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger				
3		* 3				*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4		*				*			diagnostic prefix 2=parallel (2) suffix=series PTOX= Periodic Trap Oxidizer				
EVA No.		ECS No.	ENGINE SIZE (L		VEHICLE MAKES & MODELS						Buick /C/ = Chevrolet /CD/ = = Oldsmobile /P/ = Pontiac		
1		1	4.7			<u>WD</u>	<u>VD</u>						
	_												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *				CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of introgen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram												
CER	RT STD		NMOG	NMHC	NMHC STD	mg=millig			nning ioss 1000 miles					eruenng vap plemental fe			
0.052	, ,	0.055	CERT	CERT	[g/mi]		[g/mi]	NO	Ox [g/mi]	Н	CHO [n	[mg/mi]	PM [g/mi]	Hwy NO	k [g/mi]	
0.002			[g/mi]	[g/mi]	191	CERT	STD	CER	r st	D CE	RT	STD	CERT	STD	CERT	STD	
		@ 50K	0.030	*	0.040	0.2	1.7	0.03	0.0	5	*	8.	*	*	0.01	0.07	
		@ UL	0.037	•	0.055	0.3	2.1	0.03	0.0	7	*	11.	*	0.01	0.01	0.09	
	@ 50	°F & 4K	*	•	*	*	•	•	*		*	٠	•	٠	٠	*	
CO [@ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/r (composite) (compos				NMHC+NOx [g/mi] [US06]		C	O [g/mi] [US06]		HC+NOx ni] [SC03]		[g/mi] 203]	
50	50K		= @ UL (Tid	er 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T STE	CER	T STD	CERT	STD	
CERT	2.3			SFTP@4K	*	*	•	*	0.01	0.60	0.4	11.8	0.03	0.44	0.1	4.0	
STD	12.5		Name:	SFTP 2	*	*	*	•	•	•	•	•	•	•	•	•	
@ UL	Е	VAPOR	ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2					EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-1	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR	
CERT	0.36	0.3	6 0.00	4 0.03		*	•	*	*	*	*	*	*	*	*	*	
STD	0.90	1.1	5 0.0	0.20	•	*	•	*	•	*	*		*	*	•	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ___

Annette Hebert, Chief

Mobile Source Operations Division