## TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0560 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD: YEA		TEST GROUP			VEHICLE TYPE (PC≖passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			STANDA (LEV=low am transitional L SULE)	ST EMISSION RD CATEGORY ission vehicle; TLEV= .EV; ULEV=ultra LEV; /=super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		7TYXV01.5HC1				Passenger Car	Emis (LE	Super-Ultra Low sion Vehicle VII SULEV)	150K / 150K	Gasoline plus Battery-Assist				
No.	FAM	ILY (E	ATIVE EVAF)	N	0.	SPECIAL FEAT EMISSION CONTROL	TURES SYSTE	& MS (ECS)	*= not applicable	OC/TWC=oxidizing/3-way	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S			
1	7TYX	7TYXR0030A42			1			, HO2S,SFI, C	"  ArS/MArS=a)r-fuel ratio sensor/heated AFS_FGR=avhaust					
2		•			2			*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / {P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
3	<b>★</b>				3			±						
ÉVAF No.				VEHICLE MAKES & MODELS	VE ST/	HICLES SUBJ	ECT TO SFTP E UNDERLINED	ABBREVIATIONS:	iller (2) sumix=sèries					
1	_	1 1.5		$\dashv$		Toyota Prius								
									*					

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NM AVE	OG FL RAGE	EET [g/mi]	NMOG @ CH4 R		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG	NMHC	NMHC STD	diurnal+h mg=millig		terial transfer	nning loss 1000 miles	OKVK	∖ [g/ga⊞oi	i dispensed ahrenheit	}=on-boar₫ i	refueling vap plemental fe	or recovery	/ g=gram	
0.03	1   (	0.043	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		Ox [g/mi]			[mg/mi]	PM [	a/mi]	Hwy NC		
100000000000000000000000000000000000000	Welling (Phys., pp. )					CERT	STD	CER.	T ST		CERT	STD	CERT	STD	CERT	STD	
		@ 50K			•	*	*		•		*		*	*	*	*	
Karan P		@ UL	0.009	•	0.010	0.10	1.0	0.01	0.0	2	*	4	*	•	0.010	0.03	
(40-144.pg) (40-144.pg)	@ 50°	F & 4K	*	*	*	*		•	•		•	*	*			*	
CO [ @ 20	°F&	∐ LE	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	50K		SFTP 2 = @ UL (Tier 1, TLEV)			STD	CERT	STD	CERT	STE		RT ST			CERT	STD	
CERT	1.3	Tegati.		SFTP 1	*		*	+	0.03	0.14	4 0.				0.1	2.7	
STD	10.0			SFTP 2	SFTP 2 *		*		*		-			* 0.20	- 0,1	2.1	
@ UL			TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				F	VAPORATI	VE EAM	1 0 4	
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	l RL			1 2-D	I RL		
CERT	0.16	0.14	0.01	0.00	*	•	*	*	*		*	*	3.0	¥ -U	KL.	ORVR	
STD	0.35	0.35	0.05	0.20	*	•	*	•	*		+	<del></del>	-	<del></del>		ļ <u></u>	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models have been certified as an advanced technology (AT) partial zero emission vehicle (PZEV)—Type E Hybrid Electric Vehicle (HEV) and are granted a baseline PZEV allowance of 0.2 and additional PZEV allowances under 13 CCR Section 1962(c).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

Rophal Susmourty

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2006.

Annette Hebert, Chief

Mobile Source Operations Division