New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full In-use; h. / evap, late in-use)	FUEL TYPE	
2008	8GMXT04.3186	LDT: 6001-8500# GVW, 3751- 5750# ALVW	"LEV II" Low Emission Vehicle (LEV II LEV)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2	
		The same of the sa		150K 150K			•	Unleaded)	
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE I	EAMILY (EV)	LE)	372			
1	2TWC, 2	HO2S(2), SFI, OBD(F)	\$80	8GMXR0176820					
*		*	- BUNKRU	176820	\$				
				223840					
		•				4.	.3		
•		*				7.0			
			*						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50 Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

Annette Hebert, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.) NMOG FLEET NMOG @ RAF=*

AVERAG	E [g/mi]		g KAF="	NMOG or	CH4=meth	ane; NMOG=	non-CH4 org	anic gas; NI	MHC=non-CH	4 hydrocarbo	on; CO≃carbo	n monoxide	NOx=oxides o	d miles and
CERT	STD	NMOG	NMHC	INDIC	THUI-SUAK: N	tr ici/mil≅nio	aina issee: At	31/D /=/#		,	V.O 20 0 191	いしらいーと/ふ ロヨヤ	diumal+ ram; mg=milli	r nau ogen;
0.047	0.050	CERT	CERT [g/m]]	STD [g/mi]	CO	=1000 mies; [g/mi]	F≍degrees (ahrenheit; 9 [g/mi]	FTP=suppler HCHO	nental federa	test procedu	ecovery; g≕g	ram; mg=milli	
	@ 50K	0.064		<u> </u>	CERT	STD	CERT	STD	CERT	STD	CERT	STD	Hwy NO	x [g/mi]
建筑 (本版)				0.075	2.2	3.4	0.03	0.05	*	15,	OLA:	310	CERT	STD
4.1	@ UL	0.072	•	0.090	3,1	4.2	0.06	0.07					0.004	0.07
. @	50°F & 4K	0.129	*	0.150	1.9	3.4	0.02		<u> </u>	18.	*	0.01	0.004	0.09
	2	A Super				0.4	0.02	0.05		30.	*	4		•
1 -	- The state of the		100	NMHC+NC	by failmit		- 19							_

		i de la compania		NMHC+N	lOx [g/mi]	0.4	0.02				30.	*	•	•	•
@ 2	O [g/ml] 0°F & 50K			(comp	osite)	CO [g/mi] posite)		+NOx [US06]	CO	[g/mi] \$06]		C+NOx I (SC03)	CO	[g/mi]
	· · · · · · · · · · · · · · · · · · ·			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		03]
CERT	4.6	SFTP @	1000 miles	*	*								310	CERT	STD
STD	12.5	SFTP	@ miles	•				0.06	0.40	10.2	10.5	0.06	0.31	2.3	3.5
									•	*	•	*	*	•	•
1			3-Dave Di										4		

Evaporative Family	(grams/te	al + Hot Soak est) @ UL	2-Days Diurn (grams/to	est) @ UL		ig Loss	On-Board Ref	fueling Vapor				
	CERT	STD	CERT	STD	CERT		Recovery (gram	s/gallon) @ U				
8GMXR0176820	0.48	0.90		 	CERT	STD	CERT	STD				
BGMXR0223840			0.35	1.15	0.00	0.05	0.03	0.00				
	0.71	0.90	0.65	1.15	0.00	0.05		0.20				
	•	*	•			0.05	0.03	0.20				
•	•					•	*	•				
ot applicable; UL=useful life; F				• [•							

*= not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=uthra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; OZS=oxygen sensor; HO2S=heated OZS; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust CAC=charge air cooler; OBD (F)(P)=fullyparital on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2008 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=exi	MEDIATE USE LIANCE full in-use; h. / evap. ate in-use)	PHASE-IN STD.	OBD								
CHEVROLET	G1500/2500 VAN 2WD	CONTRACTOR (C	-	-	EXH	EVAP		_								
CUC/DOLET		8GMXR0223840	1	4.3	*	•	SFTP	Full								
CHEVROLET	C15 SILVERADO 2WD	8GMXR0223840	1	4.3	*	*	SFTP	Full								
CHEVROLET	K15 SILVERADO 4WD	8GMXR0223840	1	4.3	*	•										
GMC	G1500/2500 SAVANA CARGO 2WD	8GMXR0223840	1	4.3	•	-	SFTP	Full								
GMC	C15 SIERRA 2WD	8GMXR0223840				•	SFTP	Full								
GMC			1	4.3	*	*	SFTP	Full								
	K15 SIERRA 4WD	8GMXR0223840	1	4.3	•		SFTP	Full								
CHEVROLET	C15 SILVERADO 2WD	8GMXR0176820	1	4.3	*	*	SFTP									
CHEVROLET	K15 SILVERADO 4WD	8GMXR0178820			-			Full								
GMC	C15 SIERRA 2WD		-	4.3		•	SFTP	Full								
GMC		8GMXR0176820	1	4.3	•	•	SFTP	Full								
	K15 SIERRA 4WD	8GMXR0176820	1	4.3	•	*	SFTP	Full								
CHEVROLET	G15/25 VAN 2WD CONV	8GMXR0223840	1	4.3			SFTP	Full								