GENERAL MOTOR'S CORPORATION

EXECUTIVE ORDER A-006-1474-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (*=N/A or A/E=ex	IEDIATE USE LIANCE full in-use; h. / evap. late in-use)	FUEL TYPE
2008		LDT: 6001-8500# GVW, 3751-	"LEV I!" Low Emission	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2 Unleaded)
	8GMXT06.0387	5750# ALVW	Vehicle (LEV II LEV)	150K	150K	•		l
No.		SPECIAL FEATURES	EVAPORATIVE					
1	2TWC, 2	8GMXR	0176820					
•					5.3, 6			
•		•	±	*** 45				•
•		*						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50 Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1474 dated April 6, 2007.

Executed at El Monte, California on this _______ day of June 2007.

Annette Hebert, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG AVERAG			@ RAF=* !AF = *		CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=o: CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOX=o: NHCH0=non-CH4 organic gas; NOX=o: NHCH0=non									
CERT	STD	NMOG	NMHC	NMHC STD	mi=mite; K=	L įg/mij≂runi •1000 miles;	F=degrees I	ahrenheit; S	FTP=supple	nental federa	i test procedu	re		
	2.252	CERT	CERT	[g/mi]	CO	g/mi]	NOx	[g/mi]	HCHO	[mg/mi]	PM [g/mi]	Hwy NO	x [g/mi]
0.047	0,050	[g/mi]	[g/mi]	[Bum]	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
erig alle	@ 50K	0.048	•	0.075	1.1	3.4	0.02	0.05	•	15,	•		0.01	0.07
	@ UL	0.069	*	0.090	1.5	4.2	0.03	0.07	*	18.	*	0.01	0.02	0,09
(C) (C)	50°F & 4K		*	•	*	•	•	*	*	•	*	*	*	•
				NMHC+N	Ox fa/mil	CO (a	/mil	NMHC+N	Юx	CO [g/mi]	NM	+C+NOx	CO	[g/mi]

CO [g/mi]			NMHC+N (comp		CO (NMHC [g/mi]	:+NOx [US06]	CO [NMHC [g/mi]	+NOx [SC03]	co [cs]	
@ 20	0°F & 50K		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	3.0	SFTP @ 4000 miles	*	•	•	•	0.04	0.40	0.6	10.5	0.04	0.31	1.4	3.5
STD	12.5	SFTP @ * miles	*	•	*		*	*	*	*	•	*	*	*

Evaporative Family	3-Days Diurna (grams/te		2-Days Diurn: (grams/te	al + Hot Soak est) @ UL	Runnin (grams/m		On-Board Refueling Va Recovery (grams/gallon)		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
8GMXR0176820	0.48	0.90	0.35	1.15	0.00	0.05	0.03	0.20	
*	•	*	•	4	*	•	•	*	
•	+	*	•	+	*	*	* .	*	
+	•	*	•	+	*	•	•	•	

^{*=} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler, OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2008 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or A/E=exi	IEDIATE USE LIANCE full in-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II Fuil Full
					EXH	EVAP		
CHEVROLET	TRAILBLAZER AWD	8GMXR0176820	1	6	•		SFTP	Full
CHEVROLET	TRAILBLAZER 2WD	8GMXR0176820	1	5.3	•	*	SFTP	Full
CHEVROLET	TRAILBLAZER 2WD	8GMXR0176820	1	6	*	*	SFTP	Full
CHEVROLET	TRAILBLAZER 4WD	8GMXR0176820	1	5.3	• .	*	SFTP	Full
GMC	ENVOY 2WD	8GMXR0176820	1	5.3	*	*	SFTP	Full
GMC	ENVOY 4WD	8GMXR0176820	1	5.3	•	*	SFTP	Full
SAAB	9-7X AWD	8GMXR0176820	1	5.3	*	*	SFTP	Full
ŞAAB	9-7X AWD	8GMXR0176820	1	6	*	•	SFTP	Full