FUJI HEAVY INDUSTRIES, LTD.

EXECUTIVE ORDER A-002-0156 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-dut MDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	STAND, (LEV=lor UL	UST EMISSION ARD CATEGORY Wemission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE {CNG/LNG≂compressed/ liquefled natural gas; LPG=liquefled petroleum gas}				
2008		8FJXB02.5NVD			PC and LDT ≤6,000 pounds GVW (PC; LDT 3,751 – 5,750 pounds LVW)			EV II SULEV	150K / 150K	Gasoline			
No.		APORA MLY (E		No.	SPECIAL FEAT EMISSION CONTROL	URES &	S (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	8FJ	8FJXR01254CE			TWC(2), HAFS			AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI					
2	8FJXR01254CK			2									
3		•				*		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4		+		4		*		diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.					ECT TO SFTP EUNDERLINED								
1		1	2.5			(2.5X, 2.5XS)							
2		1	2.5		SUBAR	U: (PC)), LEGACY WAGON AW	D 2.5i					
2	1 2.5				SUBARU: (LDT 3,751-5,750 pounds LVW) OUTBACK WAGON AWD (BASE, Ltd.)								
*		* *		<u> </u>		•							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram												
	STD STD PC/LDT1 LDT2		NMOG	NMHC CERT	NMHC STD [g/mi]	mg=millig	ram ml	rulle K≃1 -mile K≃1	nning loss 1000 miles	ORVR F≖d	i [g/gallor legrees F	n dispensed) ahrenheit	=on-board r SFTP=sum	efueling vap elemental fe	or recovery Jeral test o	g≖gram ocedure
			CERT			CO [g/mi]		NO	NOx [g/mi]					/mi]	Hwy NOx [g/mi]	
0.040	0]	0.050	[g/ml]	[g/mi]	15	CERT	STD	CER	T ST	D (CERT	STD	CERT	STD	CERT	STD
		@ 50K	•	*		*	*		٠.		*	٠	*	•	*	*
		@ UL	0.007	*	0.010	0.3	1.0	0.02	0.0	2	0.5	4	*	0.01	0.01	0.03
	@ 50	°F & 4K	0.015	*	0.020	0.3	1.0	0.01	0.0	2	1	8	*	•	*	*
	@ 20°F& 📓		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)				g/mi] posite)	NMHC+NOx [g/mi] [US06]				HC+NOx ii] [SC03]	CO [g/mi] [SC03]			
50K		SFTP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER1	F STD	CERT	STD
CERT	2.1		Control of	SFTP 1	*	*	+	•	0.02	0.14	1 2	.6 8.0	0.02	0.20	0,01	2.7
STD	10.0			SFTP 2	*	•	•	*		*		•	•	*	•	
@ UL	E	VAPOR	ATIVE FAM	AILY 1	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E'	EVAPORATIVE FAMILY 4			
	3-D	2-1	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
CERT	0.24	0.2	3 0.00	0.02	0.22	0.24	0.00	0.02	*	•	*	*		† *	+	*
STD	0.35	0.3	5 0.05	0.20	0.35	0.35	0.05	0.20	*	•	•	•	*	* -	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962 (c)(2).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______day of M

Annette Hebert, Chief

Mobile Source Operations Division