

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MODI |                | TEST                    | ST GROUP                  |    | VEHICLE TYPE<br>(PC=passenger car; LDT=flight-du:<br>MDV=medium-duty vehicle; LVW:<br>vehicle weight; ALVW=adjusted | =loaded                                 | CATEGORY<br>vehicle; T | EMISSION STANDA!  / (LEV=low emiss 'LEV= transitional LEV; LEV; SULEV=super ULE                                   | on / EVAPORATIVE<br>USEFUL LIFE   | FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) |  |  |  |  |
|------|----------------|-------------------------|---------------------------|----|---|---|------------------------|---|---|--|--|--|--|--|
| 200  | 8              | 8MBXB06.3L2A            |                           |    | PC and LDT> 6,000 pounds (PC; LDT 3,751 – 5,750 pounds  |   |                        | LEV II LEV  | 120K / 150K   | 50K Gasoline (Tier 2<br>Unleaded)  |  |  |  |  |
| No.  |                | VAPORATIVE AMILY (EVAF) |                           | No | SPECIAL FEA<br>EMISSION CONTROL   |   |                        | * = not applicable  | OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S |  |  |  |  |  |
| 1    | 1 8MBXR0170LNS |                         |                           | 1  | 2TWC, 2F  | O2S(2),                                 | AIR, SFI, OBD          | AFS/HAFS-air-fuel ratio sensor/heated AFS EGR=exhaust   |   |  |  |  |  |  |
| 2    | 8ME            | MBXR0155LNC             |                           |    | 2WU-TWC, 2TV  | VC, 2HO                                 | 2S(2), AIR, SF         | AIR MFI/SFI= multipo  | rt fuel injection/sequential MFI  |  |  |  |  |  |
| 3    | 8MBXR0170LNC   |                         |                           | 3  | 1   | •                                       |                        | TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board |   |  |  |  |  |  |
| 4    |                | *                       |                           |    |   | 4                                       | •                      | diagnostic preflx 2=par   | allel (2) suffix=series   |  |  |  |  |  |
| EV.A |                | EC<br>S<br>No.          | ENGIN<br>E<br>SIZE<br>(L) |    | VEHICLE<br>MAKES & MODELS   |   |                        | ECT TO SFTP<br>E <u>UNDERLINED</u>  |   |  |  |  |  |  |
| 1    |                | 1                       | 6.3                       | T  |   | Mercedes Benz: (PC) S 63 AMG, CL 63 AMG |                        |   |   |  |  |  |  |  |
| 2    |                | 2                       | 6.3                       |    | Mercedes Benz: (PC) CLK 63 AMG (CABRIOLET), E 63 AMG, E 63 AMG (WAGON), CLS 63 AMG, CLK 63 AMG (Coupe), C 63 AMG    |   |                        |   |   |  |  |  |  |  |
| 3    |                | 1                       | 6.3                       |    | Mercedes Benz: (LDT) ML 63 AMG, R 63 AMG  |   |                        |   |   |  |  |  |  |  |
| •    |                | *                       | *                         | _  |   |   |                        | *   |   |  |  |  |  |  |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| NMOG FLEET<br>AVERAGE STD<br>[g/ml] |                      |        | NMOG @ RAF= *<br>CH4 RAF = * |       |                                  | NMOG or | nitrogen<br>diurnal+h | HCHO=fo<br>ot-soak R                      | rmaldehyde<br>L [g/ml]≕rur | PM≔par<br>ining loss             | ticulate n<br>ORVR [ | natter i<br>g/gallon                   | RAF≕reactiv<br>dispensed]: | bon CO=ca<br>ity adjustme<br>on-board re | nt factor 2<br>fueling vap | 2/3 D [g/test<br>or recovery | ]=2/3 day<br>g=gram |
|-------------------------------------|----------------------|--------|------------------------------|-------|----------------------------------|---------|-----------------------|---|----------------------------|----------------------------------|----------------------|--|----------------------------|--|----------------------------|------------------------------|---------------------|
| PC/LD                               | T1 L                 | DT2    |                              |       | IHC                              | STD     | mg=millig             |   |                            | ile K=1000 miles i<br>NOx [g/mi] |                      | F=degrees Fahrenhelt S<br>HCHO [mg/mi] |                            | SFTP=supplemental fer PM [g/mi]          |                            | Hwy NOx [g/mi]               |                     |
| 0.040                               | ) (                  | 0.050  | CERT<br>[g/mi]               |       | RT<br>mi]                        | [g/ml]  | CERT                  | [g/mi]<br>STD                             | CERT                       |                                  |                      | ERT                                    | STD                        | CERT                                     | STD                        | CERT                         | STD                 |
| E W                                 |                      | @ 50K  | 0.014                        |       | •                                | 0.075   | 0.8                   | 3.4                                       | 0.02                       | 0.0                              | 5                    | 0.3                                    | 15.                        | *  | •                          | 0.01                         | 0.07                |
| 7 44                                |                      | @ UL   | 0.015                        |       | •                                | 0.090   | 1.0                   | 4.2                                       | 0.03                       | 0.0                              | 7                    | 0.4                                    | 18.                        | *  | 0.01                       | 0.01                         | 0.09                |
|                                     | @ 50°                | F & 4K | 0.056                        |       | •                                | 0.150   | 1.1                   | 3.4                                       | 0.04                       | 0.0                              | 5                    | 1.0                                    | 30.                        | •  | *                          | *                            | *                   |
|                                     | STORE SANSER         |        |                              | LEV.  | NMHC+NOx [g/mi]<br>(composite) ( |         |                       | CO [g/mi] NMHC+N<br>(composite) [g/mi] [U |                            |                                  |                      |  | NMHC+NOx<br>[g/mi] [SC03]  |  | CO [g/mi]<br>[SC03]        |                              |                     |
|                                     |                      |        | 2 = @ UL (Tier 1, TLEV)      |       |                                  | CERT    | STD                   | CERT                                      | STD                        | CERT                             | STD                  | CE                                     | RT ST                      | CERT                                     | STD                        | CERT                         | STD                 |
| CERT                                | 5.3                  | 88     | 142                          | SF    | TP 1                             | •       | *                     | *   | •                          | 0.03                             | 0.14                 | 4.                                     | 7 8.0                      | 0.02                                     | 0.20                       | 0.4                          | 2.7                 |
| STD                                 | 10.0                 |        |                              | SF    | TP 2                             | *       | *                     | *   | •                          | *                                | *                    | *                                      | •                          | •  | •                          | *                            | *                   |
|                                     | EVAPORATIVE FAMILY 1 |        |                              |       | EVAPORATIVE FAMILY 2             |         |                       |   | EVA                        | EVAPORATIVE FAMILY 3             |                      |  |                            | EVAPORATIVE FAMILY 4                     |                            |                              |                     |
| @ UL                                | 3-D                  | 2-1    | D F                          | iL 0  | RVR                              | 3-D     | 2-D                   | RL  | ORVR                       | 3-D                              | 2-D                  | RL                                     | ORV                        | ₹ 3-D                                    | 2-D                        | RL                           | ORVR                |
| CERT                                | 0.39                 | *      | 0.0                          | 000 0 | .004                             | 0.45    | *                     | 0.000                                     | 0.004                      | 0.40                             | *                    | 0.00                                   | 0.11                       | *  | *                          | <u> </u>                     | •                   |
| STD                                 | 0.50                 | 0.6    | 5 0.                         | 05 (  | 0.20                             | 0.50    | 0.65                  | 0.05                                      | 0.20                       | 0.90                             | 1.15                 | 0.0                                    | 5 0,20                     | *  | •                          | *                            | •                   |

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-003-0350 dated April 30, 2007.

Executed at El Monte, California on this 27 day of March 2008.

Annette Hebert, Chief

Mobile Source Operations Division