

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD	ıR	TEST GROUP			1.	VEHICLE TYPE (PC=passenger car; LDT=light-di MDV=medium-duty vehicle; LVW vehicle weight; GVW=gross	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)					
200			GMXB03.6148			PC and LDT <8500 pounds (PC; LDT 3,751-5750 pounds		"LEV II" LEV		150K / 150K	Gasoline (Tier 2 Unleaded)					
No.	FAM.	ILY (E	EVAF)		No.	SPECIAL FEAT EMISSION CONTROL :	URES & Systems (1	ECS)	OC.	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	8GM	BGMXR0117811			1	2TWC, 2	)= warm-up cat. O25/HO2: S/HAFS=air-fue) ratio sens	S=oxygen sensor/heated O2S ior/heated AFS_EGR=exhaust								
2	2 8GMXR0133810				2		*	—⊌ga:	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
3	3 8GMXR0133814				3		•	E MIN								
4	8GM)				4			BUM								
EVA		CS	ENGIN			VEHICLE	VEHICL	ES SUBJ	ECT TO SFTP	8		(L) outlix-series				
No.		No.	SIZE (I	<u>L)</u>		MAKES & MODELS	STANDA	rds ari	EUNDERLINED		REVIATIONS:					
1_		1	3.6			(LDT2 <6000# GVW) Chevrolet Equinox; FWD, AWD; (LDT2) Pontiac Torrent: FWD, AWD										
2		1	2.8			(PC): Cadillac CTS										
2		1 3.6				(PC): Cadillac CTS, Cadillac CTS AWD, Chevrolet Malibu, Pontiac G8, Saturn Aura										
. 3		<u>1</u> ]	3.6				(LDT2 M	INGIIU	D. COV. AMD	Aura						
4		1	2.8		T	(LDT2 6001-8500# GVW) Cadillac; SRX 2WD, SRX AWD (PC): Cadillac CTS										
4		1 3.6			T	(PC): Cadillac CTS, Cadillac CTS AWD										
				_				IFU: Cac	mac C 15, Cadillac	CIS/	AWD					

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	OG FL RAGE I	[g/mi]	NMO:	G@ 4RA	RAF= *	NMOG o	CH4=met nitrogen	hane NMO HCHO=fo	G=non-CH rmaldehyd	4 organic le PM≃pa	gas NMH irticulate	C=non-C	H4 hydroca	rbon CO=c	arbon mono	xide NOx	oxides of
STD-P		NMOG NMHC		NMHC CERT	NMHC	mg=millig	ram mi	- [5]	mning los 1000 mile:	a DULK	LANDAROL	dispensed)	lty adjustme =on-board re SFTP=supp	efueling var	OF TOCOVER	/ Amaram	
0.040	0.050				[g/mi]	[g/mi]	CERT	[g/ml] STD		Ox [g/ml]		HCHO	mg/mi]	PM [g	/mi]		x [g/mi]
	@ 50K		0040				<del> </del>		CER	T S	D	CERT	STD	CERT	STD	CERT	STD
			0.046			0.075	1.4	3.4	0.03	0.0	05	*	15		•	0.01	0.07
Sales In	@ UL		0.046		*	0.090	1.4	4.2	0.03	3 0.1	07	•	18	•	0.01	0.01	0.09
	@ 50	°F & 4K	. •		•	•	•		•		, +	*	•		•		0.05
CO [ @ 20 50	го в	SE LC	1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) 2 = @ UL (Tier 1, TLEV)					(composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [U\$06)	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
		CONTROL OF THE PARTY OF THE PAR		CERT	STD	CERT	STD	CERT	STD	CE	RT STE			CERT	STD		
ERT	1.8	, Svore		SFT	P @ 4K	*	*	*	•	0.09	0.14	2.	5 8.0	0.05	0.20	1.5	2.7
STD	10.0			SFT	P@UL	•	*	•	•	†	•			+ +	0.20	1.5	2.1
2 UL	JL EVAPORATIVE FAMILY 1						EVAPORATIVE FAMILY 2				PORAT	IVE FA	MII V 3		/APORATI	WE FAMIL	   W 4
	3-D	2-D	R	L [	ORVR	3-D	2-D	RL I	ORVR	3-D	2-D	RL					
ERT	0.42	0.46	0.0	00	0.02	0.22	0.18	0.00	0.01						2-D	RL	ORVR
TD	0.65	0.85	0,0	15	0.20	0.50				0.32	0.46	0.00	0.01	0.22	0.18	0.00	0.01
				~	0.20	0.00	0.65	0.05	0.20	0.90	1.15	0.05	0.20	0.50	0.65	0.05	0.20

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the vehicle models with evaporative families 2 and 4 are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1976(b)(1)(F) footnote 4.

**BE IT FURTHER RESOLVED:** Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of March 2007.

Annette Hebert, Chief

Mobile Source Operations Division