

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			VEHICLE TYPE C=passenger car; LDT=light-duty DV=medium-duty vehicle; LVW=ic vehicle weight; ALVW=adjusted L	aded	STANDAR (LEV=low ( ULEV	ST EMISSION RD CATEGORY emission vehicle; feultra LEV; esuper ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)    FUEL TYPE (CNG/LNG=compressed.   iquefied natural gas;   LPG=liquefied petroleum g				
2008	8 8	8BMXB03.0N52		F (F	PC and LDT ≤ 6,000 pounds € PC; LDT 3,751-5,750 pounds L	LE\	/ II ULEV	150K / 150K Gasoline					
No.		VAPORATIVE No.		No.	SPECIAL FEATI EMISSION CONTROL S	URES SYSTEM	& MS (ECS)	* = not applicable	13440- warm-up car. Ozo/nozo-oxygen sensor/neared Ozo				
1	1   BBMXR0128E85			1	2WUTWC, 2TWC,	2HAFS	, 2HO2S, SFI,	FishHAFS-air-fuel ratio sensor/heated AFS EGR=exhaust gas decirculation AIR/PAIR≖secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle					
2		•				•	· · · · · · · · · · · · · · · · · · ·						
3		•		3		*			body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAF	1		NGINE		VEHICLE	VE	HICLES SUBJ	ECT TO SFTP					
No.	No	No. SIZE (L) MAKES & MODELS STA		NDARDS AR	E UNDERLINED								
1_	_		2.5		BMW: (PC, OBD (F)) 323i								
1	1		3.0		BMW: (PC, OBD)	Sport Wagon,							
1	1		3.0		328Cl, 328Cl Convertible, 328Cxl, 528l, 528xi BMW: (PC, OBD (P)) Z4 3.0i, Z4 3.0si, Z4 3.0si Coupe								
1	1		3.0	$\top$	BM				OBD (F)) X3 3.0i, X3 3.0si				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]			MOG @	RAF="	NMOG or	CH4=meth of nitroge	nane NMO	G≃non-CH4 formaideh	organic g	ases particu	NMHC=no	r RAFares	carbons C	O=carbon n	nonoxide	Ox=oxides
PC/LE	DT1	LDT2		MOG	NMHC	NMHC STD [g/mi]	diurnal+hi  mg≖millig	DI-BOAK K	∟ լց/ույյ=ւս	nning loss :1000 miles	ORV	R ig/gallor	n dispensed) Fahrenheit	=on-board i	efueling var	or recovery	/ g≃gram`
0.04	10	0.050	1	ERT /mi]	CERT [g/mi]		CERT	[g/mi]	NO	Ox [g/ml]		HCHO	[mg/mi]	PM [	g/mi]	Hwy NC	x [g/mi]
PARTY NEWSFILM		99	1 -		[2]		LEKI	STD	CER	T STI	D	CERT	STD	CERT	STD	CERT	STD
		@ 50	_	.025	•	0.040	0.1	1.7	0.01	0.0	5	*	8	*	*	0.001	0.07
		@ UL	. 0	.028		0.055	0.2	2.1	0.01	0.0	7	•	11	•	0.01	0.002	0.09
	@ 5	0°F & 4H	0	.068		0.080	0.2	1.7	0.01	0.0	5	•	16	•	•	*	*
CO @ 20°F	[g/mi] = 2.504	, I	TP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] (composite)			g/mi] posite)	NMH(	C+NO		CO [g/mi] [US06]		HC+NOx iii [SC03]	CO	[g/mi] C031
20 1	u 501	SFTP	2 = @	UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD
CERT	1.2				SFTP 1	•	*.	*	•	0.01	0:1	14 0	.1 8.0	0.01	0.20	0.1	2.7
STD	10.0				SFTP 2	*		•	*	•	*	<u> </u>	* *	-	•	•	<del> </del>
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2 EVAPOR					PORA	RATIVE FAMILY 3 EVAPORATIVE FAMILY 4					
<u></u>	3-D	2	-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D				2-D	RL	ORVR
CERT	0.38	3 0.	35	0.02	0.04		*	*	4	-	4	<del>                                     </del>		*	+	1	
STD	0.50	0.	65	0.05	0.20	•	*	*	•	*	•	*	*	*	+	+	+

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

**BE IT FURTHER RESOLVED:** Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-008-0220 dated April 13, 2007.

Executed at El Monte, California on this

day of December 2007.

Annette Hebert, Chief

Mobile Source Operations Division