## FORD MOTOR COMPANY

**EXECUTIVE ORDER A-010-1434** New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TES			TEST GROUP			VEHICLE TYPE C=passenger car; LDT=light-duty DV=medium-duty vehicle; LVW=l vehicle weight; GVW=gross Vi	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitionar LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	3	BFMXT04.65E9				MDV: 8,501 10,000 # GV	USEPA Bin 8a(Opt) Counted as ARB LEV II LEV			120K / 150K	Flexible Fuel: Ethanol (E85) / Gasoline (Tier2 Unleaded)					
No.		APORATIVE MILY (EVAF)			No.	SPECIAL FEATI EMISSION CONTROL S	S (ECS)	* = not applicable	C	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust ga						
1	8FMX	AXR0265GAS			1	2TWC(2), 2HC	D2S(2), E	GR, SFI, OI	Π∦A							
2		*			2						Fecirculation AIR/PAIR=secondary air injection/puised AIR  MF/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC≖charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix  2=parallel (2) suffix=series					
3		*			3	•										
4		*			4	*										
EVAF No.		CS lo.	ENGIN SIZE (			VEHICLE MAKES & MODELS	CLES SUBJECT TO SFTP DARDS ARE UNDERLINED			REVIATIONS:						
1	1 1		1 4.5			Ford: E-150 CLUB WAGON FFV, E-150 ECONOLINE 2WD FFV, E-250 ECONOLINE 2WD FFV										
		•	•		<u> </u>				*							

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF AVERAGE [g/mi] CH4 RAF = *				RAF=* AF = *	NMOG or	CH4=methane NMOS=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day distributions with the control of the control											
CER	T	STD	NMOG	NMHC	NMHC STD	diurna!+h   mg=millig	Ct-SCar	RL (g/mi)≐ru i≃mile K≃'	ming 1055	OKVK	g/gallon di grees Fah	spensed)=c	n-board ref FTP≃supple	ueling vap	OF FECOVERY	a=aram	
•		*	CERT [g/mi]	CERT [g/mi]	[g/mi]	CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
SECTION AND A	CONTRACTOR OF THE PARTY OF THE				<u> </u>	CERT	STD	CER	T ST	D C	ERT	STD	CERT	STD	CERT	STD	
	@ 50K @ UL		0.057 (0.062)		0.125 (0.125)	0.7 (0.9)	3.4 (3.4)	0.05			1 (*)	15 (15)	•	*	*	•	
			0.081 (0.086)	*	0.156 (0.156)	1.3 (1.5)	4.2	0.11	0.2	ō	2	18 (18)	(*)	0.01 (0.01)	•	•	
	@ 50	0°F & 4K *		+	· ·	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•	*	7 (0.2	·	+						
@ 20		LEV	@ 4K (SULEV, ULEV, ) or 50K (Tier 1, TLEV) @ UL (Tier 1, TLEV)				(composite)		NMHC+NOx C [g/mi] [US06]			[g/mi] JS06]		NMHC+NOx [g/mi] [SC03]		CO [g/ml] [SC03]	
50K		Srir 2 - Q UL		, ILEY)	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
CERT	(*)		SFTP	@ 50K	• ]	*	•	•	•		•	*	•	*	*	*	
STD	_(*)		SFTP	@ UL	•	•	•	*	*	•	•	<del>  -</del>	<del>                                     </del>	*	*	*	
@ UL	E\	/APORAT	TIVE FAMI	LY 1	EVAPORATIVE FAMILY 2 EVAPOR					PORATI	ATIVE FAMILY 3 EVAPOR				N/C EALA	34.4	
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR					
CERT	0.52	•	0.00	*	<del>  • •  </del>					2-0	RL.	URVR	3-D	2-D	RL	ORVR	
STD	1.00	1.25	0.05		<b>!</b>	*						<del>  `</del> -	<u> </u>	-:-			

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_ day of November 2007.

mette Hebert, Chief

Mobile Source Operations Division