Californ
AIR

is Environmenial Protection Agency	DAIMLERCHRYSLER CORPORATION	New Passend
RESOURCES BOARD	BAIMEERON TOLER OOR ORTON	

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROUP			t groui	>	VEHICLE TYPE (PC=passenger car; LDT=light-du MDV=medium-duty vehicle; LVW vehicle weight; ALVW=adjusted	=loaded	STAND (LEV=lo	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
2008 8CRXB0241M80			(B0241M	30	PC; LDT 0 -3750 # LVW a < 6000 # GVW	ind	1	EV II ULEV	120K / 150K Gasoline						
No.	EVAPORATIVE FAMILY (EVAF) No.				SPECIAL FEAT EMISSION CONTROL			* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	8CF	RXR013	0GMA	1	2TWC, 2HC	02S(2), E	GR, SFI, OBI	AFS/HAFS=air-fuel ratio se	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed						
2	BCRXR0130GMB 2							AIR MFI/SFI= multiport fuel injection/sequential MFI							
3	8CF	RXR017	7GNA	3		*		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
4	BCF	RXR015	OGNA	4		*									
EV/ No					STAN	DARDS AR	IECT TO SFTP E <u>UNDERLINED</u>	ABBREVIATIONS:							
1		1	3.5		DODGE			BRING, SEBRING CONVE	RTIBLE						
2		1	3.5			DODGE: (PC) AVENGER AWD; CHRYSLER: SEBRING AWD									
3		1	4.0		Chrysler: (LDT) Pacifica AWD, Pacifica FWD										
4		1	4,0			Dodge: (LDT) Caravan 2WD; Chrysler: (LDT) Town & Country 2WD									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE STD [g/mi] NMOG @ RAF = *			NMOG or NMHC	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day dlurnah-hot-soak RL [g/m]=running loss CRVR [g/gallon dispensed]=on-board refueling vapor recovery g=rgam mo=millioram mi=mile K=1000 miles F=decrees Fahrenheit SFTP=supplemental federal test procedure												
CERT	RT STD NMOG NMHC STD													PM [g/mi] Hwy NOx [g/mi]		
PC/LD 0.045	•••	/LDT1	CERT [g/mi]	CERT [g/mi]	[g/mi]	CERT	[g/mi] STD							STD	CERT	STD
	Na can be store in the	@ 50K	0.026	*	0.040	1.7	1.7	0.01	0.0	5	*	8	•	*	0.000	0.07
	2 E 1	@ UL	0.026	*	0.055	1.7	2.1	0.01	0.0	7	*	11	•	0.01	0.000	0.09
1	<u>ത</u> 50°	F & 4K	*	*	+	*	•	*	•		*	•	•	*	*	*
CO [					NMHC+N (comp			[g/ml] posite)		C+NOx [US06]		[g/mi] IS06]		C+NOx ] [SC03]	[S	[g/mi] 203]
50K SFT		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
CERT	4.4			SFTP 1	•	*	•	•	0.09	0.14	4.6	8.0	0.02	0.20	2.0	2.7
STD	10.0			SFTP 2	*	•	*	*	*	*	*	*	*	*	*	•
	E	VAPOR	ATIVE FA	VILY 1	EVA	EVAPORATIVE FAMILY 2 EVAPO				PORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
@ UL	3-D	2-	D RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.28	0.4	9 0.00	0.06	0.28	0.49	0.000	0.06	0.51	0.44	0,000	0.14	0.29	0.32	0.000	0.06
STD	0.50	0.6	5 0.05	0.20	0.50	0.65	0.05	0.20	0.65	0.85	0.05	0.20	0.65	0.85	0.05	0.20

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-009-0801-1 dated April 12, 2007.

Executed at El Monte, California on this \_\_\_\_\_ day of June 2007.

annet Dele

Annette Hebert, Chief Mobile Source Operations Division