| ſ | | Cali | forni | а Елт | ข้างคล | entai | Prote | ction / | gency | | |
|---|---|------|-------|-------|--------|-------|-------|---------|-------|----|----|
| Ś | 2 | A | R | RE | SO | U | RC | FS | BO | IΔ | RI |

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | * * * | | | | | | | | | | | | | | | |
|-----|---------------------------------|---------------------------------------------------------------------|--------------|------|----|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|---------------------|--|--|--|--|
| * | * * | | | | | | | Colowit Victoria Police Pry, Mercury Grand Marguls FFV | | | | | | | | |
| 1 | | 1 4.6 Ford Crown Victoria FFV, Ford Crown Victoria Police FFV, Merc | | | | | | | | Manager Care of M | | | | | | |
| No. | | | No. SIZE (L) | | | MAKES & MODELS | STA | NDARDS AR | ECT TO SFTP | ABBR | | | | | | |
| ËVA | | ECS | ENGI | JE 1 | | VEHICLE | | | | | | and (2) sum -series | | | | |
| 4 | * | | 10 | 4 | | | | | | CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallel (2) suffix=series | | | | | | |
| 3 | * | | | | 3 | • | * | | | | TITBI= throttle body injection TC/SC=turbo (super charger | | | | | |
| 2 | - 2 | | | | | | * | | - gas Air | as recirculation AIR/PAIR=secondary air injection/pulsed | | | | | | |
| 1 | BFMXR0115GAK | | | | 1 | 2TWC(2), 2 | HO2S(2), | EGR, SFI, Of | _ Ara | garo/naro=air-fuel ratio sensor/heated AFS_EGRaeyhaust | | | | | | |
| No. | EVAPORATIVE FAMILY (EVAF) No | | | | | SPECIAL FEA EMISSION CONTROL | TURES SYSTER | & MS (ECS) | * = not applicable | | OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S | | | | | |
| 200 | - | 8FMXV04.6VE | | | , | PC | USEPA Bin 5 Counted as ARB LEV II LEV | | | 120K / 150K | Flexible Fuel: Ethanol (E85) / Gasoline (Tier 2 Unleaded) | | | | | |
| MOD | AR TEST GROU | | | | MC | VEHICLE TYPE =passenger car; LDT=light-du IV=medium-duty vehicle; LVW ehicle weight; ALVW=adjusted | EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV) | | | EXHAUST / FUEL TYPE EVAPORATIVE (CNG/LNG=compres USEFUL LIFE liquefied natural g (UL) (miles) LPG=liquefied petroleu | | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| AVE | OG FLEE RAGE [g/r | mi] | NMOG @ CH4 R | | NMOG or | | | | | | | | rbon CO=c /ity adjustme | | | | | |
|--------------------|----------------------|-----------------|-----------------------------------------------------------------------------------------------------------------|----------------|---------------------------|--------------------------|--------|------------------|---------------------------|-------------------------------------------------|-----------|------------------------|----------------------------|--------------|-------------------|------------------------|--|--|
| CER | T ST | TD OT | NMOG | NMHC | | diurnal+ho mg≖milligi | | - [Bunni]-17 | inning loss 1000 miles | DAMA | [g/galion | dispensed] hrenheit | =on-board r | étuelina yan | OF RECOVERY | dadram | | |
| 0.03 | 8 0.0 | 40 | CERT [g/mi] | CERT [g/mi] | [g/mi] | CO | [g/mi] | N | Ox (g/mi] | | HCHO [| | SFTP=supp PM [g | a/mil | Hwy NC | | | |
| | | | 0.043 | [8] | L | CERT | STD | CER | | DC | CERT | STD | CERT | STD | CERT | STD | | |
| | @ 50 | 50K | (0.045) | + | 0.075 (0.075) 0.090 | 0.9 | 3,4 | 0.02 | | | 1 | 15 | • | | 0.02 | 0.07 | | |
| Area Carl | | <u> </u> | 0.059 | <u> </u> | | (1.0) | (3.4) | (0.02 | | | <u>()</u> | (15) | | | (0.02) | (0.07) | | |
| | | ⊉ur¦ | (0.060) | • | (0.090) | (1.2) | (4.2) | 0.05 | | | <u>a</u> | 18 | * | 0.01 | 0.05 | 0.09 | | |
| 10. Mar 1998 | @ 50°F (| 8 4K | * | • | + | * | * | 10.03 | | <u>"1 </u> | <u>U</u> | (18) | (*) | (0.01) | (0.05) | (0.09) | | |
| | 1 | | | | | | | | | | | • | . * | * | * | * | | |
| CO [@ 20 50 | °F& ∰ | LE/ | • @ 4K (SUL V) or 50K (Ti • @ UL (Tier | er 1, TLEV) | NMHC+NC (comp | osite) | (com | g/mi] posite) | | C+NOx [US06] | | :O [g/mi] [US06] | | HC+NOx | | (g/mi] 203] | | |
| <u> </u> | | | . S. O. LINK | 1, 1224) | CERT | STD | CERT | STD | CERT | STD | CEF | RT STE | CERT | STD | CERT | STD | | |
| CERT | (4.5) | di iri Ali i | ្រ ី | TP @ 4K | • | • | | • | (0.02) | | | | | | + + | + | | |
| STD | | | | TP @ UL | • | * | • | | [0.02] | (0.14) |) (1. | 2) (8.0 |) (0.02) | (0.20) | (0.8) | (2.7) | | |
| | (10.0) | | and the state of the second | | (0.10) | (0.65) | - | | • | * | 1 (1.0 | 8) (11 | n I * | •. | (1.3) | (3.7) | | |
| | | | TIVE FAM | | EVA | PORATIVE | FAMILY | 2 | EVA | PORAT | IVE FA | | | | PORATIVE FAMILY 4 | | | |
| - | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORV | | 2-D | RL | ORVR | | |
| CERT | 0.29 | 0.26 | 0.00 | 0.01 | | • | - | * | * | * | | + | | + . | * | * | | |
| STD | 0.50 | 0.65 | 0.05 | 0.20 | * | * | + | • | * | • | | | | | | | | |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____day of April 2007.

Annette Hebert, Chief

Mobile Source Operations Division