California Environmental Protection Agency AIR RESOURCES BOARD	BAYERISCHE MOTOREN WERKE AG	EXECUTIVE ORDER A-008-0225-1
		New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LIFE (miles)		INTERMEDIATE IN-USE COMPLIANCE ("=N/A or fuil In-use; A/E=exh. / evap. Intermediate In-use)		FUEL TYPE	
2008	8BMXV03.0N51	Passenger Car	"LEV II" Super Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Gasoline	
		-	SULEV)	150K	150K	•	*		
No.	ECS & SPECIAL FEATURES		Extension 1	EVAPORATIVE FAMILY (EVAF)		DISPLACEMENT (L)			
1	2WU-TWC, 2TWC, 2HAFS, 2HO2S, SFI, AIR, DOR, OBD(P)		8BMXR0	8BMXR0141N51					
•	•		*	*					
•	*			*					
•	•		•	*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962 (c)(2).

#### **BE IT FURTHER RESOLVED:**

The listed vehicle models are granted a 0.005 g/mi NMOG credit for all certification and in-use testing pursuant to 13 CCR Section 1961(a)(12) [direct ozone reduction].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-008-0225 dated September 27, 2007.

Executed at El Monte, California on this \_\_\_\_\_ day of April 2008.

Annette Hebert, Chief Mobile Source Operations Division

California Environmental Protection Agency AIR RESOURCES BOARD

**BAYERISCHE MOTOREN WERKE AG** 

EXECUTIVE ORDER A-008-0225-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.) NMOG @ RAF= CH4 RAF = \* CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ NMOG FLEET NMOG or AVERAGE [g/mi] hot-soak, RL [g/m]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure NMHC NMOG CERT STD NMHC STD CERT CERT Hwy NOx [g/mi] CO [g/mi] NOx [g/mi] HCHO [mg/mi] PM [g/mi] [g/mi] 0.037 0.040 [g/mi] [g/mi] CERT STD CERT STD CERT STD CERT STD CERT STD @ 50K . \* ٠ . 0.03 . 0.01 0.02 0.0003 0.005 0.010 0.4 1.0 4. 0.01 @ UL @ 50°F & 4K 0.020 0.3 1.0 0.01 0.02 8. 0.016 ٠ CO [g/mi] NMHC+NOx NMHC+NO<sub>X</sub> CO [g/mi] [SC03] NMHC+NOx [g/ml] CO [g/mi] 4 CO [g/mi] [g/mi] [US06] [g/mi] [SC03] (composite) (composite) [UŚ06] @ 20°F & 50K CERT STD CERT STD CERT STD CERT STD CERT STD CERT STD 0.001 0,20 2.7 CERT 1.5 0.004 0.14 0.2 8.0 0.2 SFTP @ 4000 miles STD 10.0 SFTP @ \* miles 3-Days Diurnal + Hot Soak 2-Days Diurnal + Hot Soak **Running Lose On-Board Refueling Vapor** Recovery (grams/gallon) @ UL (grams/test) @ UL (grams/mile) @ UL (grams/test) @ UL **Evaporative Family** CERT STD CERT STD CERT STD CERT STD 0.20 0.03 8BMXR0141N51 0.35 0.02 0.05 0.15 0.35 4 ٠ . . ٠ . ٠ . -\* . . \* ٠ . . . \*

\* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttie body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=\*85%\* Ethanol Fuel

# 2008 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	EVAPORATIVE FAMILY MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E==exh. / evap. intermediate in-use)		PHASE-IN STD.	obd II
					EXH	EVAP		
BMW	328Ci	8BMXR0141N51	1	3	*	-	SFTP	Partial
BMW	328CI CONVERTIBLE	8BMXR0141N51	1	3	*	*	SFTP	Partial
BMW	328Cx	8BMXR0141N51	1	3	*	•	SFTP	Partial
BMW	328i	8BMXR0141N51	1	3	*	•	SFTP	Partial
BMW	328xi	8BMXR0141N51	1	3	*	•	SFTP	Partial
BMW	128i	8BMXR0141N51	1	3	•	+	SFTP	Partial
BMW	128I CONVERTIBLE	8BMXR0141N51	1	3	*	+	SFTP	Partial