

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP				VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STANDAF (LEV=low emi- transitional Li	ST EMISSION RD CATEGORY ssion vehicle; TLEV= EV; ULEV=ultra LEV; =super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≃compressed/ liquefled natural gas; LPG=liquefled petroleum gas)		
200	2008 8NSXT02.585			A	(0-	LDT <6,000 pounds GVW 3750 # LVW; 3,751-5750 # LVW)	LEV	II SULEV	120K / 150K	Gasoline		
No.		EVAPORATIVE FAMILY (EVAF)			).	SPECIAL FEATURES EMISSION CONTROL SYSTI		* = not applicable	WU= warm-up cat. O2S/i	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S		
1	BNSXR0105PBA					TWC+ADS-TWC,TWC, A	FS, HO2S(2), S	AFS:HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFUSFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
2	•						*					
3	•						*					
EVAI No.	F	ECS No.	ENGIN SIZE (L				EHICLES SUBJ ANDARDS ARI	ECT TO SFTP UNDERLINED	ABBREVIATIONS:			
1		1 2.5			(LDT1) NISSAN ROGUE: FWD S, FWD SL, AWD S; (LDT2) NISSAN ROGUE AWD SL							
*		* *			•							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NMOG FLEET AVERAGE [g/mi]			NMOG ( CH4 F	ĝ RAF= * RAF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day   diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
STD-L	STD-LDT1 STD-LDT2		NMOG	NMHC	NMHC STD		mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure										
0.04	10	0.050	CERT	CERT [g/mi]	[g/mi]		[g/ml]	, NO	NOx [g/ml]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/ml]		
0.04			[g/mi]			CERT	STD	CER	T ST	D CI	ERT	STD	CERT	STD	CERT	STD	
LE A		@ 50K	*	•	•	*	•	•	*		•	•	*	*	*	•	
		@ UL	0.006	•	0.010	0.2	1.0	0.012	0.0	2	•	4	*	0.01	0.004	0.03	
	@	50°F & 4K	*	٠	•	•	•	*	*		*	•	*	*	*	*	
							+NOx [g/mi] CO [g/m mposite) (composi			NMHC+NOx [g/ml] [US06]				HC+NOx ii] [SC03]	CO [g/mi] [SC03]		
50		SFTP 2 = (	UL (Tier 1	I, TLEV)	CERT	STD	CERT	ŞTD	CERT	STD	CE	RT ST	CERT	r std	CERT	STD	
CERT	2.7		SF	TP @ 4K	•	•		•	0.01	0.14	0.	8 8.0	0.00	0.20	0.4	2.7	
STD	10.0		SF	TP @ UL	*	•	•	•	*	*	*	*	٠	*	*	•	
@ UL	E	VAPORAT	VE FAM	LY 1	EVAPORATIVE FAMILY 2 EVAPO				PORATI	ORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	0.16	0.48	0,00	0.03	*	•	*	*	*	. *	•	. *	*	*	. •	•	
STD	0.65	0.85	0.05	0.20	•	•	*	•	*		•	*		*	*	*	

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2007.

Annette Hebert, Chief

Mobile Source Operations Division