Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| EVAF No. | ECS No. | ENGINE SIZE (L 5.0 | | VEHICLE MAKES & MODELS | STANDARDS A | RE UNDERLINED Lexus LS 600hL | ABBREVIATIONS: | | | |
|-----------------------|----------------------|--------------------------|-----|--|---|--|--|--|--|--|
| 3 | * | * | | | VEHICLES SUB | diagnostic prefix 2=parallel (2) sumx=series | | | | |
| 2 | * | | 2 | | | | TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-boar | | | |
| 1 | 1 8TYXR0180E12 | | | 2WU-TWC, 2TWC, 2AF | FS, 2HO2S, 2ADS-H | gas recirculation AIR/PAIR=secondary air injection/puiser AIR MFI/SFI= multiport fuel injection/sequential MFI | | | | |
| No. | EVAPORA FAMILY (E | | No. | SPECIAL FEATURE EMISSION CONTROL S | URES & SYSTEMS (ECS) | * = not applicable | WU= warm-up cat, O2S/I | y cat. ADSTWC=adsorbing TWC HO2S=oxygen sensor/heated O2S sensor/heated AFS EGR=exhaus | | |
| 2008 8TYXV05.0CC4 | | | | Passenger Car | Emis | Super-Ultra Low sion Vehicle VII SULEV) | 120K / 150K | Gasoline plus Battery-Assist | | |
| MODEL YEAR TEST GROUP | | | (| VEHICLE TYPE PC=passenger car; LDT=light-dut truck; MDV=medium-duty vehicle LVW=loaded vehicle weight; ALVW=adjusted LVW | ty STANDAI (LEV=low emi transitional L SULEV | ST EMISSION RD CATEGORY Ission vehicle; TLEV= EV; ULEV=utra LEV; V=super ULEV | EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles) | FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas) | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

| NMOG FLEET AVERAGE [g/mi] | | | CH4 KAI - | | NMOG or | nitrogen diurnal+ho | HCHO≃forr t-soak RL | naktenyde [g/mi]=run; | PM=paru ning loss | ORVR [q | /gallon | RAF=reacti dispensed ahrenheit | leon-board | arbon mono ent factor refueling vap plemental fe | OF PECOVERY | g=gram | |
|------------------------------|--------------------|--------------|----------------------|----------------|----------------------|------------------------|------------------------------|--|---------------------------|---------|-----------------|--------------------------------------|------------------|---|----------------|--------|--|
| CERT | | | NMOG | NMHC | STD | mg=millign | | | 000 miles x [g/mi] | | | mg/mi] | PM [g/mi] | | Hwy NOx [g/mi] | | |
| 0.000 | 0.04 | 0 | CERT | CERT | [g/ml] | | g/ml] STD | CERT | STD | | ERT | STD | CERT | STD | CERT | STD | |
| 0.030 | 0.04 | 0.040 [g/mi] | | [g/mi] | 1 | CERT | | CERT | 1 | | • | | | - | | • | |
| arer. | a a | 50K | * | . * | | • | * | <u> </u> | | | | | | | | 0.03 | |
| | | | 0.0058 | | 0.010 | 0.17 | 1.0 | 0.002 | 0.02 | ! | • | 3 | · | 0.01 | 0.004 | 0,03 | |
| | RANGE PROPERTY. | UL | | | | | | - | . | | • | * | * | | | * | |
| | @ 50°F 8 | 4K | * | | | | | <u> </u> | STATE OF | 110- | | CO [g/mi] | · N | AHC+NOx | T CO | [g/mi] | |
| CO [s | | _ | = @ 4K (SULEV, ULEV, | | NMHC+NOx [g/mi] | | ni] CO [g/ml] (composite) | | NMHC+NOx [g/mi] [US06] | | | [USO6] | [g/ | [g/ml] [SC03] | | [8003] | |
| @ 20 | ER 👹 | LE\ | /) or 50K (T | ier 1, TLEV) [| {comp | | | STD | CERT | STD | CE | RT S | | | CERT | STD | |
| 501 | K s | FTP 2 = | @ UL (Tier | 1, TLEV) | CERT | STD | CERT | | | | _ | | .0 0.0 | 13 0.20 | 0.01 | 2.7 | |
| CERT | 1.7 | | | SFTP 1 | * | | * | .* | 0.011 | 0.14 | U. | .02 8 | .0 0.0 | 13 0.20 | | + - | |
| | | | | SFTP 2 | * | | * | * | • | | | * ' | • * | * | | | |
| STD | 10.0 | | | | 1 | PARTIE CAMILY 2 FVAPOL | | | | PORAT | RATIVE FAMILY 3 | | | EVAPORATIVE FAMILY 4 | | | |
| @ UL | EVAPORATIVE FAMILY | | | | EVAPORATIVE FAMILY 2 | | | | 3-D | | 2-D RL | | VR 3-0 | 2-D | RL | ORVR | |
| | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | - 3-0 | | + : | - | | - | * | • | |
| CERT | 0.17 | 0.17 | 0.003 | 0.034 | • | | | - | + | - | + , | , - | - - | * | * | * | |
| STD | 0.50 | 0.65 | 0.05 | 0.20 | • | • | * | | | <u></u> | | | | | | | |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ________ day of May 2007.

Annette Hebert, Chief

Mobile Source Operations Division