| California Environmental Protection Agency | New Passenger Cars, Light-Duty Trucks<br>and Medium-Duty Vehicles |
|--|---|
| AIR RESOURCES BOARD                        |   |

EXECUTIVE ORDER A-014-0599

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MOD |     | TEST                      | GROUP              | (F  | VEHICLE TYPE<br>C=passenger car; LDT=light-duty<br>ruck; MDV=medium-duty vehicle;<br>LVW=loaded vehicle weight;<br>ALVW=adjusted LVW) | STANDAF<br>(LEV=low emi-<br>transitional L<br>SULEV | ST EMISSION<br>RD CATEGORY<br>ssion vehicle; TLEV=<br>EV; ULEV=ultra LEV;<br>=super ULEV)<br>(ra-Low Emission | EXHAUST & ORVR<br>/ EVAPORATIVE<br>USEFUL LIFE (UL)<br>(miles) | FUEL TYPE<br>(CNG/LNG=compressed/<br>liquefied natural gas;<br>LPG=liquefied petroleum gas)   |  |  |
|-----|-----|---------------------------|--------------------|-----|---|---|---|--|---|--|--|
| 200 | 8   | 8TYX                      | /03.5BEB           |     | Passenger Car   | 1   | /ehicle<br>VII ULEV)  | 120K / 150K  | Gasoline  |  |  |
| No. | FAN | APORA<br>MILY (E<br>XR016 | VAF)               | No. | SPECIAL FEATURES<br>EMISSION CONTROL SYST<br>2WU-TWC, 2TWC, 2AFS  | EMS (ECS)   | * = not applicable<br>SFI, OBD(F)   | AFS/HAFS=air-fuel ratio  | cat. ADSTWC=adsorbing TWC<br>HO2S=oxygen sensor/heated O2S<br>sensor/heated AFS EGR=exhaust<br>NR=secondary afr injection/pulsed<br>int fuel injection/sequential MFI |  |  |
| 2   |     | *                         |                    | 2   |   | *   |   | ·四丁Rie throttle hody inieta                                    | IOBD (F) / (P)=full /partial on-board   |  |  |
| EVA | . 1 | ECS                       | ENGINE<br>SIZE (L) | -   | VEHICLE V<br>MAKES & MODELS S   | EHICLES SUBJ<br>TANDARDS AR                         | EUNDERLINED   | ABBREVIATIONS:   | 7   |  |  |
| 1   |     | 1                         | 3.5                | -   |   |   | Lexus IS 350  |  | ······································  |  |  |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

|  | GE [g/mi]     | NMÔG @<br>CH4 R<br>NMOG          | RAF = *<br>AF = * | NMOG or<br>NMHC | nitropen                                    | HCHO=for<br>it-soak RL | i=non-CH4 (<br>maldehyde<br>. [g/mi]=run<br>mile K=10 | PM=part                   | ORVR [g/g<br>F=degre | ter RAP<br>Jallon dis<br>ses Fahre | pensed]=(            | on-board re | fueling vap | or recovery<br>leral test pr | g≖gram<br>ocedure |
|--|---------------|----------------------------------|-------------------|-----------------|---|------------------------|---|---------------------------|----------------------|------------------------------------|----------------------|-------------|-------------|------------------------------|-------------------|
|  |               | CERT                             | CERT              | STD<br>[g/ml]   |   | [g/mi]                 |   | x [g/ml]                  |                      | HO [mg                             |                      | PM [g       | /ml]<br>STD | Hwy NO<br>CERT               | STD               |
| 0.030                                  | 0.040         | [g/mi]                           | [g/mi]            | [Aunu]          | CERT  | STD                    | CERT  | STL                       | CEF                  | <u> </u>                           | STD                  | CERT        | 510         |                              |                   |
| Sec. as i                              | @ 50K         | 0.025                            | +                 | 0.040           | 0.2   | 1.7                    | 0.02  | 0.05                      | 5   *                |                                    | 8                    | *           | *           | 0.01                         | 0.07              |
|  | @ UL          | 0.036                            | +                 | 0.055           | 0.3   | 2.1                    | 0.03  | 0.07                      | *                    |                                    | 11                   | *           | 0.01        | 0.02                         | 0.09              |
| an an sa in si<br>Sectoria             | @ 50°F & 4K   | *                                | •                 | · · .           |   | *                      | *   | *                         | *                    |                                    | *                    | *           | *           | *                            | *                 |
| CO. [g/mi] SETP 1 = @ 4K (SULEY, ULEY, |               |                                  |                   |                 | NOx [g/mi] CO [g/mi]<br>noosite) (composite |                        |   | NMHC+NOx<br>[g/mi] [US06] |                      |                                    | CO [g/mi]<br>[US06]  |             |             |                              | [g/mi]<br>C03]    |
| @ 20°F                                 |               | .EV) or 50K (T<br>2 = @ UL (Tier | 1, TLEV)          | CERT            | STD   | CERT                   | STD   | CERT                      | STD                  | CERT                               | STD                  | CERT        | <u> </u>    | CERT                         | STD               |
| CERT                                   | 2.1           | 1                                | SFTP 1            |                 | *   |                        | *   | 0.02                      | 0.14                 | 0.0                                | 8.0                  | 0.03        | 0.20        | 0.0                          | 2.7               |
|  | 10.0          | A.                               | SFTP 2            | *               | *   | •                      |   | *                         | *                    | *                                  | 4                    | *           |             | *                            | *                 |
| 310                                    | 10 10 X 10 10 |                                  |                   | EVU             | PORATIV                                     | E FAMU                 | Y 2   | EVAPORATIVE FAMILY 3      |                      |                                    | EVAPORATIVE FAMILY 4 |             |             |                              |                   |
| OUL-                                   |               | RATIVE FAI                       |                   | 3-D             | 2-D   | RL                     | ORVR  | 3-D                       | 2-D                  | RL                                 | ORVE                 | 2 3-D       | 2-D         | RL                           | ORVR              |
| -                                      |               | D RL                             | ORVR              | 3-0             | 2-0   | *                      | *   | *                         | *                    | *                                  | *                    | *           | *           | .*                           | *                 |
| CERT                                   |               | 25 0,00                          |                   |                 | *   |                        |   | *                         | *                    | *                                  | *                    | *           |             | *                            |                   |
| STD                                    | 0.50 0.       | 65 0.05                          | 0.20              |                 | 1   |                        |   |                           |                      |                                    |                      |             | 4           |                              |                   |

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2007.

Annette Hebert, Chief

Mobile Source Operations Division