EXECUTIVE ORDER A-023-0447 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			STANDA (LEV=lov UL	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≐compressed/ liquefled natural gas; LPG=liquefled petroleum gas)			
200		8HNXV01.3ZCP			PC				EV II SULEV	150K / 150K	Gasoline (Tier 2 Unleaded) plus Battery-Assist			
No.		MILY (EVAF)			No.	SPECIAL FEA EMISSION CONTROL	s (ECS) *= not applicable		OC/TWC=oxidizing/3-way					
1	8HNXR0096BCA				1	WUTWC, TWC,	HAFS HO	S SELECT	OC/FWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated 02S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MF/ISFi= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix-series					
2		•			2		1171 0, 1102	23, 3F1, EGF						
3		•			3	<del></del>								
4		•			4	<del> </del>	*							
EVAF		CS	ENGIN			VEHICLE	VEUZ	CL CC CUS II		diagnostic prefix 2=paralle	el (2) suffix=series			
No.	N			DARDS ARI	ECT TO SFTP	-								
	1 1.3				DARDS ARE UNDERLINED HONDA CIVIC HYBRID									
*	* *				MONDA CIVIC HYBRID									
*	T	•	•			<del></del>								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

CERT	·   §	g/mi]	NMOG @ RAF = * CH4 RAF = *		NMOG o	CH4=met r of nitroge	hane NMO on HCHO=	G≃non-CH formaldeh	4 organic	gases N	MHC=nor	-CH4 hydro	carbons C	O≕carbon m nent factor	onoxide N	0x=oxides
	CERT         STD         NMOG CERT         NMHC CERT           0.037         0.040         [g/mi]         [g/mi]		NMHC STD	diurnai+h mg≃millig	ot-soak R <u>ram m</u> i:	L[g/mi]=n =mile K=	unning los 1000 mile	s ORVR F≖d	[g/gallon	dispensed	vity adjustn =on-board i	1911 factor efueling var	2/3 D [g/tes	t]=2/3 day		
0.037					[g/mi]	CERT	[g/mi] STD	CER	Ox [g/ml]		HCHO (	mg/mi]	PM [	plemental fe g/ml]		rocedure 0x [g/mi]
4.44	@ 50K		+		_	+	1 310	CER	T ST	ים ו	CERT	STD	CERT	STD	CERT	STD
350					<b>├</b>	<del>                                     </del>		•	'	•	•	*	*	*	*	*
4	CONTRACTOR OF THE PARTY OF THE	@ UL	0.004	*	0.010	0.4	1.0	0.01	0.4	02	•	4	*	0.01	0,004	0.00
	@ 50°F	8.4K	*	•	•	•		•		,		<del>-                                    </del>	<del></del>	0.01	0.004	0.03
CO [g/ @ 20°F 50K	F& 🛭	LIE1	@ 4K (SULI V) or 50K (Tie : @ UL (Tier	BY 1. TLFVAL	NMHC+No (comp	Ox [g/mi] osite) STD		g/mi] posite)		C+NOx [US06]		O [g/mi] [US06]	[g/m	HC+NOx i] [SC03]	CO [S	* [g/mi] C03]
CERT	3.1			SFTP 1	<del>-</del>	<del>-</del> -				+			CERT	STD	CERT	STD
STD 1	10.0			SFTP 2	<del></del>	<del></del> _		ļ	0.002	0.14	3.8	8.0	0.003	0.20	0.3	2.7
	2						_ •	•	<b> </b> •			*	•			$\vdash$ -
_ UL			TIVE FAMI		EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				<del></del>	/ADODAT	VE EARN	<u> </u>
	3-D	2-D	RL.	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		/APORAT		
ERT	0.16	0.22	0.003	0.01	•	•	•	*	*	*	1	J. OKVI	3-D	2-D	RL	ORVR
TD	0.35	0.35	0.05	0.20	*	*	-	-	<del>-</del> -	-	-	+	+	<u> </u>	<b>*</b>	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models have been certified as an advanced technology (AT) partial zero emission vehicle (PZEV) -- Type D Hybrid Electric Vehicle (HEV) and are granted a baseline PZEV allowance of 0.2 and additional PZEV allowances under 13 CCR Section 1962(c).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Replace Sunaint

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2007.

Annette Hebert, Chief

Mobile Source Operations Division