ROUSH INDUSTRIES INC.

EXECUTIVE ORDER A-344-0010

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE			EXHAUST EMISSION ANDARD CATEGORY	USEFU (mil		IN COMI (*=N/A o A/E≖e	MEDIATE -USE PLIANCE r full in-use; ch. / evap.	FUEL TYPE	
2008	8RIIT05.4RI7	LDT: 6001-8500# GVW, 5751- 8500# ALVW		USEPA Bin 4 counted as ARB LEV2	EXH / ORVR EVAP		EXH	EVAP	Gasoline (Tier 2	
				ULEV	120K	150K	•	*	Unleaded)	
No.	ECS &		EVAPORATIVE FAMILY (EVAF)			DISPLACEMENT (L)				
1	2TWC, 2HO2		8RIIR0240NBR							
-	•			*					5.4	
*	•			•		•).4			
*		*		*						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 20 day of September 2007.

Annette Hebert, Chief

Mobile Source Operations Division

ROUSH INDUSTRIES INC.

EXECUTIVE ORDER A-344-0010

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

111100		412466			Tarre	LILLOO	OLI A			- CILCL-I				(C	C = :4 = = = = =	
NMOG FLEET NMOG @ 1 AVERAGE [g/ml] CH4 RAI			NMOG or	HCHO=fo	rmaldehyde; i	PM=particu	iate matter	RAF=reac	tivity adjusti	ment factor	r; 2/3 D (g/te	st]=2/3 day	lOx≔oxides o diurnal+ ram; mg =milli			
CERT	STD	NMOG	NMHC	NMHC STD [g/mi]	ml=mile; l	(=1000 miles	; F=degree	s Fahrenhe	eit; SFTP=si	upplementa	l federal te	st procedure	204ery, g -gr	anı, n ıy -mın	grani	
0.055	0.075	CERT	CERT [g/mi]			[g/mi]		x [g/mi]		CHO [mg/i		PM [g			x [g/mi]	
0.000	0.075	[g/mi]			CERT	STD	CERT	STD	CE	RT S	STD (CERT	STD	CERT	STD	
通数图	@ 50K	*	•	*	*	*	*		•		*	*	*	•	*	
	@ UL	0.040	*	0.070	0.8	2.1	0.03	0.04	4 *	٠ 1	11.	•	0.01	0.03	0.05	
	0 50°F & 4K	*	*	*	*	•	•	•	•	'	*	•	*	, R	*	
CO [g/mi] 20°F & 50K				NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
CERT	2.5		P @ 50000 miles	80,0	1.49	*	*	*	•	1.2	13.2	•		1.0	4.4	
STD	12.5	SFTP	@ 120000 miles	0.08	2.09	•	٠	*	*	1.4	19.3	*	•	1.2	6.4	
Evaporative Family			urnal + Ho s/test) @ l		2-Days Diurnal + Hot Soak (grams/test) @ UL		Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/gallon) @ UL						
		CERT	S	TD	CERT	CERT S		CER	т	STD		CERT		STD		
8RIIR0240NBR 0.10		0.10	0	0.90		0.23 1.		0.00)	0.05		0.07		0.20		
*		+	•		•		*	*		*		•		*		
+ +		-			*		*	*				*				

* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ALSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heared O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger, CAC=charge air cooler; OBD (F)/(P)=ful/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2008 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or A/E=exi	IEDIATE USE LIANCE fult in-use; 1. / evap. ata in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
ROUSH	STAGE 3 F-150 SUPER CAB 2WD	8RIIR0240NBR	1	5.4	*	•	SFTP	Full
ROUSH	STAGE 3 F-150 SUPER CAB 4WD	8RIIR0240NBR	1	5.4	•	•	SFTP	Full
ROUSH	STAGE 3 F-150 SUPER CREW CAB 2WD	8RIIR0240NBR	1	5.4	*		SFTP	Full
ROUSH	STAGE 3 F-150 SUPER CREW CAB 4WD	8RIIR0240NBR	1	5.4	*	•	SFTP	Full
ROUSH	STAGE 3 F-150 2WD	8RIIR0240NBR	1	5,4	•	*	SFTP	Full
ROUSH	STAGE 3 F-150 4WD	8RIIR0240NBR	1	5.4	*	*	SFTP	Full