California Environmental Protection Agency AIR RESOURCES BOARD	FUJI HEAVY INDUSTRIES, LTD.	EXECUTIVE ORDER A-002-0160-3 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST	GROUI	P	MDV=med	VEHICLE TYPE inger car; LDT=light-dut lum-duty vehicle; LVW= veight; ALVW=adjusted	loaded	STAND (LEV=10 UL	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ fiquefied natural gas; LPG=liquefied petroleum gas}			
2009 9FJXJ02.5MXG					(PĊ; LD	LDT ≤ 6,000 pounds T 0 – 3,750 pounds l /51 – 5,750 pounds L	.VW;		LEV II LEV	150K / 150K	Gasoline			
No.		APORA AILY (E		No	EN	SPECIAL FEAT			* = not applicable	OC/TWC=oxkilzing/3-way	cat. ADSTWC≖adsorbing TWC O2S≖oxygen sensor/heated O2S			
1	9FJ	XR012	53CJ	1	1 TWC(2), HAFS, HO2S, SFI, EGR, OBD (P)					AFS/HAFS=air-fuel ratio s	ensor/heated AFS EGR=exhaust			
2	9FJ)	XR012	53CM	2			÷		Agas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFi TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallet (2) suffix=series					
3		*	6	3			*							
4		*		4			*							
EVA		ECS	ENGIN			VEHICLE	VEHI	CLES SUBJ	ECT TO SFTP					
No.		No.	SIZE (L	.)	MAKE	ES & MODELS	STAN	DARDS AR	E UNDERLINED					
1	1.	1	2.5		SUBARU: (PC) LEGACY AWD (2.5), 2.5)-Ltd.), LEGACY WAGON AWD 2.5)									
2		1	2,5		SUBARU: (PC) IMPREZA AWD 2.51, IMPREZA WAGON AWD 2.51, IMPREZA WAGON OUTBACK AWD 2.51									
2		1	2.5		SUBARU: (LDT 0-3,750 pounds LVW) FORESTER 2.5X, FORESTER 2.5XS									
1		1	2.5		SUBARU: (LDT 0-3,750 pounds LVW) OUTBACK WAGON AWD (BASE, Ltd.) (Manual Transmission models)									
1		1	2.5		SUBARU: (LDT 3,751-5,750 pounds LVW) OUTBACK WAGON AWD (BASE, Ltd.) (Automatic Transmission mode									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
STD	+	STD	NMOG	NMHC	NMHC STD	mg=millig	nam mi	:L (g/mi]=rui =milie K≃1	nning loss 1000 miles	ORVR [g F≂deo	gallon grees Fa	dispensed) hrenheit	on-board r SFTP=sum	efueling vap plemental fe	or recovery derail test p	g=gram
PC/LD		LDT2	CERT CERT		[g/ml]	CO	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.03	8 (0.047	[g/mi]	[g/mi]	19,]	CERT	STD	CERT	r stē) CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	0.050	*	0.075	0.6	3.4	0.02	0.05	5	1	15	•	*	0.01	0.07
		@ UL	0.060	*	0.090	0.9	4.2	0.02	0.07	7	1	18	•	0.01	0.01	0.09
	@ 50'	°F & 4K	0.121	•	0.150	1.1	3.4	0.01	0.08	5	1	30	*	•	*	*
@ 20°F& 📓		🛱 LE	1 = @ 4K (SULEV, ULEV, EV) or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/mi] (composite) (composite			NMHC+NOx ([g/mi] [US06]			O [g/mi] [U\$06]		HC+NOx i] [SC03]		[g/mi] C03]	
50	К	SFTP 2	= @ UL (Ti	er 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEF	T STC	CER	r STD	CERT	STD
CERT	2.8			SFTP 1	*	•	*	*	0.03	0.14	2.9	8.0	0.02	0.20	0.1	2.7
STD	10.0			SFTP 2	*	*	*	+	•	+	*	*	•	•	*	•
QUL	E	VAPOR	ATIVE FA	MILY 1	EVA	APORATIVE FAMILY 2 EVAPORAT					RATIVE FAMILY 3			EVAPORATIVE FAMILY 4		
	3-D	2-0) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR
CERT	0.24	0.3	3 0.0	0.02	0.15	0.19	0.00	0.01	*	*	*	+	+	*	+	+
STD	0.50	0.6	5 0.0	5 0.20	0.50	0.65	0.05	0.20	•	*	*	•	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-002-0160-2 dated July 8, 2008.

Executed at El Monte, California on this _____ day of January 2009.

Annette Hebert, Chief Mobile Source Operations Division