

## **FUJI HEAVY INDUSTRIES, LTD.**

EXECUTIVE ORDER A-002-0161-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE  PC=passenger car; LDT=light-duty truck;  MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STAND (LEV=lo	UST EMISSION ARD CATEGORY w emission vehicle; EV≔ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	9F	9FJXJ02.5NVD			PC and LDT ≤ 6,000 pounds GVW (PC; LDT 0 - 3,750 pounds LVW; LDT 3,751 - 5,750 pounds LVW)	L	EV II SULEY	150K / 150K	Gasoline					
No.		APORATIVE MILY (EVAF)			SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TW WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O						
1	9FJXR0	JXR01254CK			TWC(2), HAFS, HO25	, SFI, EGR, O	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust							
2	9FJXR0	JXR01254CP					gas recirculation AIR/PAIR=secondary air Injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger JCAC=charge air cooler OBD (F) / (P)=full /partial on-board							
3	•	•												
4	1	*			Ţ		diagnostic prefix 2=parallel (2) suffix=series							
EVAI No.	ECS No.		GINE E (L)				ECT TO SFTP UNDERLINED							
1	1	] 2	2.5		SUBARU: (Po	C) LEGACY A	.), LEGACY WAGON AW	D 2.5I						
2	1	7	2.5		SUBARU: (LD	T 0-3,750 pc	0-3,750 pounds LVW) FORESTER 2.5X, FORESTER 2.5XS							
1	1	1 2.5		-	SUBARU: (LDT 0-3,750 pounds LVW) OUTBACK WAGON AWD (BASE, Ltd.) (Manual Transmission models)									
1	1	1 2.5		S	SUBARU: (LDT 3,751–5,750 pounds LVW) OUTBACK WAGON AWD (BASE, Ltd.) (Automatic Transmission models)									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF≃* CH4 RAF≈*			NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day											
STD	D STD		NMOG			NMHC STD [g/mi]	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
PC/LD	DT1 LDT2		CERT CERT				CO [g/mi]		NC	)x [g/mi]	. [g/mi] H		[mg/mi]	PM [g/ml]		Hwy NOx [g/mi]		
0.038	B   C	0.047	[g/ml]	/ml] [g/ml]	[Shini]	CERT	STD	CERT	r s	D	CERT	ŞTD	CERT	STD	CERT	STD		
	@ 50K		ŧ		*	*	. •	*	*	-	•	+	*	*	•	*	*	
		@ UL	0.007		*	0.010	0.3	1.0	0.01	0.	02	. 0.5	4	*	0.01	0.01	0.03	
	@ 50°F & 4K		0.015		*	0.020	0.3	1.0	0.01	0.	02	1	8	*	•	*	*	
	CO [g/mi] @ 20°F &		1 = @ 4K (SULEV, ULEV, .EV) or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]				IHC+NOx ni] [SC03]	CO [g/mi] [SC03]				
50	K	SFTP 2	= @ UL (	Tier 1, TL	.EV)	CERT	STD	CERT	STD	CERT	S	TD C	ERT ST	D CER	T STD	CERT	STD	
CERT	2.1			SI	FTP 1	*	*	•	*	0.02	0	.14 2	2.6 8.	0.02	0.20	0.01	2.7	
STD	10.0			SI	FTP 2	*	ŧ	•	*	*		•	* *	*	*	•	•	
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4				
W 0L	3-D	2-1	) F	≀L (	DRVR	3-D	2-D	RL	ORVR	3-D	2-	D R	L ORV	R 3-D	2-D	RL	ORVR	
CERT	0.22	0.2	4 0.	.00	0.02	0.25	0.19	0.00	0.02	*	*	, 1		*	*	•	•	
STD	0.35	0.3	5 0.	.05	0.20	0.50	0.50	0.05	0.20	*	*		*	*	ŧ		*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962 (c)(2).



## **FUJI HEAVY INDUSTRIES, LTD.**

EXECUTIVE ORDER A-002-0161-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-002-0161-1 dated April 22, 2008.

Executed at El Monte, California on this day of January 2009.

Annette Hebert, Chief

Mobile Source Operations Division