California Environmental Protection Agency AIR RESOURCES BOARD	FUJI HEAVY INDUSTRIES, LTD.	EXECUTIVE ORDER A-002-0163 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2
---	-----------------------------	--

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE						VEHICLE TYPE PC=passenger car; LDT=light-dub MDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	oaded	STAND/ (LEV=lov UL	UST EMISSION ARD CATEGORY wemission vehicle; EV=ultra LEV; EV=super ULEV;	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2009	009 9FJXJ03.6TSF					PC and LDT ≤ 6,000 pounds PC; LDT 3,751 – 5,750 pounds		I	EV II LEV	150K / 150K	Gasoline				
No.	EVAP FAMIL			14.27 H	No.	SPECIAL FEAT EMISSION CONTROL		ECS)	WU= warm-up cat. O2S/HC	WC=oxidizing/3-way cat. ADSTWC=adsorbing TWC warm-up cat. 02S/H02S=oxygen sensor/heated 02S					
1	9FJXF	R012	53CJ		1	TWC(3), HAFS(2	, HO2S(2), S		nsor/heated AFS_EGR=exhaust						
2	9FJXF	R013	73CL	100	2		*		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		+			3		+		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
4		*			4		*			diagnostic prefix 2=parall	el (2) suffix=series				
EVAF No.		CS   lo.	ENC			VEHICLE MAKES & MODELS									
1		1		<u>- 1 -</u>	/	MARES & MODELS	MAKES & MODELS STANDARDS ARE UNDERLINED SUBARU: (PC) LEGACY 3.0L SPEC. B								
1	-	1	3	.0		SUBARU: (LDT 3.751-5.750 pounds LVW) OUTBACK 3.0R-Ltd.									
2		1	3	6		SUBARU: (LDT 3,751–5,750 pounds LVW) TRIBECA AWD									
*		*		•		•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = AVERAGE [g/mi] CH4 RAF = *			) RAF = * (AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day Idiurnat+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
STD		STD	NMOG NMHC			mg=millig		anille K≕1	000 miles	F=deg	rees F	ahrenhelt	SFTP=sup	plemental fe	deral test p	ocedure
PC/LD	T1   L	DT2	CERT	CERT	[g/mi]		CO [g/ml]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.038	3 0	0.047	[g/mi]	[g/mi]		CERT	STD	CERI	r   STD	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	0.035	•	0.075	0.6	3.4	0.01	0.05	;         ·	1	15 *		*	0.004	0.07
		@ UL	0.046	•	0.090	0.9	4.2	0.01	0.07		1	18	*	0.01	0.01	0.09
	@ 50°	F & 4K	0.118	•	0.150	1.0	3.4	0.01	0.05	i	1	30 *		*	*	*
				4K (SULEV, ULEV, NMHC+NO or 50K (Tier 1, TLEV) (compo					NMHC+NOx [g/mi] [US06]				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50		SFTP 2	= @ UL (Tie	r 1, TLEV)	CERT	STD	CERT	STD	CERT	\$TD	CE	RT ST	CER	T STD	CERT	STD
CERT	3.4	1.1		SFTP 1	•	•	*	•	0.03	0.14	1	.7 8.0	0.03	0.20	0.3	2.7
STD	10.0	Sec.3		SFTP 2	•	*	*	*	*	*		• •	*	*	*	•
au	E	VAPOR	ATIVE FAI	MILY 1	EVA	APORATIVE FAMILY 2 EVAPORATIVE FAMILY 3						E	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-0	) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	- ORV	R 3-D	2-D	RL	ORVR
CERT	0.24	0.3	3 0.00	0.02	0.28	0.39	0.00	0.01	*	*	•	*	*	*	*	*
STD	0.50	0.6	5 0.05	0,20	0.65	0.85	0.05	0.20	•	*	*	*		•	*	*

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

**BE IT FURTHER RESOLVED:** The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 22 day of April 2008.

Annette Hebert, Chief Mobile Source Operations Division