

CHRYSLER LLC

EXECUTIVE ORDER A-009-1029 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TES1	TEST GROUP			VEHICLE TYPE C=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV-transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)		FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)					
200	9	9CRXT05.74P1			'	LDT: 6001-8500# GVW, 3751-5750# ALVW	"LEV II" LEV	150K / 150K	Gasoline (Tier 2 Unleaded)					
No.		APORATIVE MILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		OC/TWC=oxidizing/3-way ca WU= warm-up cat. O2S/HO2	t. ADSTWC=adsorbing TWC 2S=oxygen sensor/heated O2S					
1	9CR	RXR0190RC0			1	2TWC, 2HO2S(?), SFI, OBD (P)	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AiR/PAIR=secondary air injection/pulled AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2	9CR	XR022	R0225RC0			,								
3		•			3									
4	•	•			4									
EVAI No.		ECS ENGINE No. SIZE (L)			VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED ABBREVIATIONS:									
1		1 5.7			Dodge: Ram 1500 Pickup 2WD, Ram 1500 Pickup 4WD									
2		1 5.7			Dodge: Ram 1500 Pickup 2WD, Ram 1500 Pickup 4WD									
*					•									
*		*					*	7.1.						

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]			MOG @ CH4 RA		NMOG or	nitrogen	HCHO=fo	rmaldehyd	e PM≃pa	rticulate n	natter F	AF=reactly	rbon CO=c	ent factor	2/3 D (a/test	1=2/3 dav
CERT	ERT STD			NMOG NMHC		NMHC STD	mg=millig	ram mi	ı∟ (g/mı)≕ru =mile K≕	inning ios: 1000 miles	S ORVR[g/gailon grees Fa	aispensea) hrenheit	on-board r	etueling vap elemental fe	or recovery derail test or	g=gram ocedure
0.047	0.047				CERT	[g/mi]		[g/mi]		Ox [g/mi]	F	(CHO	ng/mi]	PM [g		Hwy NO	
			[g/mi]		[g/ml]	1.5	CERT	STD	CER	T ST	D C	ERT	STD	CERT	STD	CERT	STD
61.0	66.67		@ 50K 0.0		*	0.075	1.6	3.4	0.04	l 0.0)5	•	15	*	*	0.02	0.07
		@ UL	0.0	048	*	0.090	1.6	4.2	0.04	0.0	07	*	18		0.01	0.02	0.09
	@ 50	F & 4K		•	*	*	*	*	•	^		*	*	*	*	*	•
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)						[g/mi] NMHC+N posite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50						CERT	STD	CERT	STD	CERT	STD	CE	RT STI	CER	STD	CERT	STD
CERT	7.9			SF	TP @ 4K	*	*	•	•	0.13	0.40	1.2	2 10.	5 0.05	0.31	1.1	3.5
STD	12.5			SF	TP@UL	*	*	*	*	*		*	*	•	•	*	•
@ UL	Ε	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
(W) OL	3-D	2-[)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL.	ORVI	₹ 3-D	2-D	RL	ORVR
CERT	0.51	0.6		0.000	0,05	0.51	0.50	0.000	0.05	*	*	*	*	*	*	*	*
STD	0.90	1.1	5	0.05	0,20	0.90	1.15	0.05	0.20	*	*	*	•	*	*	•	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

CHRYSLER LLC

EXECUTIVE ORDER A-009-1029 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The listed vehicle models have been certified on the condition that the manufacturer provide all the on-board diagnostic data required by 13 CCR Section 1968.2(i)(2.4) by October 10, 2008. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

BE IT FURTHER RESOLVED: Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of July 2008.

Annette Hebert, Chief

Mobile Source Operations Division