AIR RESOURCES BOARD

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-di MDV=medium-duty vehicle; LVV vehicle weight; ALVW=adjuste	STAND: (LEV=lo UL	UST EMISSION ARD CATEGORY w emission vehicle; EV≃ultra LEV; EV≃super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	9	9CR)	KJ02.4FF	80	PC; LDT 0-3750 # LVW : < 6000 # GVW	Li	EV II SULEV	150K / 150K	Gasoline					
No.			PORATIVE No		SPECIAL FEA  EMISSION CONTROL			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1		RXR012		1	TWC, HC	02S(2), SF	I, AIR, OBD	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed						
2	901	RXR0126FE0 2				*		AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger						
3		* 3				*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4						•								
EVA No		EC S No.	ENG!		VEHICLE MAKES & MODELS			ECT TO SFTP E <u>UNDERLINED</u>	ABBREVIATIONS:					
1		1	2.4				EY 2WD							
<u>_</u>		1	2.4			(PC) DODGE AVENGER; CHRYSLER SEBRING								
2		1	2.4			(PC) DODGE: CALIBER								
2		1 2.4				(LDT) JEEP: COMPASS 2WD, PATRIOT 2WD								
*		* *												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	G FLEE RAGE ST [g/ml]	D O	NMOG @ RAF = *		NMOG or NMHC STD [g/mi]	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=oxad refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
CERT			NMOG CERT [g/mi]			NMHC CERT [g/mi]	CO [g/mi]		NOx [g/mi]		Н	HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
PC/LD 0.041							CERT	STD	CERT	STD		ERT	STD	CERT	STD	CERT	STD
0.041		50K		<del>'</del>		·	*	•	1	*	_	*	•	•	*	*	•
		@ UL	0.00	8	•	0.010	0.4	1.0	0.003	0,02		*	4	*	0.01	0.001	0.03
	@ 50°F	_	0.01	5	•	0.020	0.4	1.0	0.002	0.02		•	8	•	•	*	•
	CO [g/mi] SFTP 1 = @ 4K (S					NMHC+NC				NMHC+NOx [g/mi] [US06]		C	O [g/mi] [US06]		HC+NOx i] [SC03]	[S	[g/mi] C03]
	@ 20°F & SFT		2 = @ UL (Tier 1			CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD
CERT	1.4		o en		SFTP 1	•	*	•	*	0.07	0.14	1.8	8 8.0	0.01	0.20	1.5	2.7
STD	10.0				SFTP 2	*	+	*	*	*	+		*	*	*	*	*
<del></del>	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2					EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
@ UL	3-D	2-D		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL			2-D	RL	ORVR
CERT	0.24	0.32	2 (	0,000	0.08	0.30	0.32	0.000	0.16	*	*	*		*	<u> </u>	*	
STD	0.35	0.3	5	0.05	0.20	0.35	0.35	0.05	0.20	*	*	*	*		*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

## **CHRYSLER LLC**

EXECUTIVE ORDER A-009-1038 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

**BE IT FURTHER RESOLVED:** That the listed vehicle models are granted a baseline partial zero emission vehicle (PZEV) allowance of 0.2 under 13 CCR Section 1962(c).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of July 2008.

Annette Hebert, Chief

Mobile Source Operations Division