EXECUTIVE ORDER A-086-0292 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light- truck; MDV=medium-duty vehi LVW=loaded vehicle weight; ALVW=adjusted LVW)	icle;	STANDAF (LEV=low emi- transitional L	ST EMISSION RD CATEGORY ssion vehicle; TLEV= EV; ULEV=ultra LEV; =super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)		
2009	9	9MTXV02.0G8G				Passenger Car		LEV	'II SULEV	150K / 150K	Gasoline		
No.		VAPORATIVE No.				SPECIAL FEA EMISSION CONTROL			WU= warm-up cat. O2S/i	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S			
1	9MT)	9MTXR0135A2C			1	WU-TWC, ADS-TWO	C, TWC,	H02S(3), EGR	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air Injection/pulsed				
2		*			2		*	1	AIR MFI/SFI= multipor	ÄIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC≖turbo /super charger			
3	*			9119	3		•		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAF No.						CT TO SFTP UNDERLINED	ABBREVIATIONS:						
11	1 2.0)		Mitsubishi Lancer							
•		*	**		1				*				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

	OG FL RAGE		NMOG (CH4 F	RAF = *	NMOG or	Initrogen	HCHO≕fo	mnaidehyde	t PM≖nari	ticulate m	atter R	AFEreactiv	dty adjustm	arbon mond ent factor	2/3 Fi Indian	1=2/2 day
CER	T	STD	NMOG NMHC		NMHC STD [g/mi]	mg=millig	ram mis	. [g/mi]≃rui :mile K≖1	nning loss 1000 miles	F≖deç	grees Fa	hrenheit	on-board ı SFTP≂sup	refueling vap plemental fe	or recovery derail test p	g=gram rocedure
0.04			CERT [g/mi]	CERT [g/mi]			[g/mi]				HCHO [mg/mi]		PM [Hwy NC	
			farmi	[Bittil]		CERT	STD	CERT	STO	CE	ERT	STD	CERT	STD	CERT	STD
	26.5 @		*	*	*		*	*	*	•			•	*	•	*
	@ U		800.0	•	0.010	0.2	1.0	0.01	0.02	0.02		4	•	0.01	0.01	0.03
(F	@ 50	°F & 4K	0.012	*	0.020	0.1	1.0	0.01	0.02	2	ń	8	+	•	•	* "
	@ 20°F & LEV) or 50K (Tier 1, TLEV)							[g/mi] NMHC+N posite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	888.	= @ UL (Tie		CERT	STD	CERT	STD	CERT	STD	CER	T STI) CER	T STD	CERT	STD
CERT	2.2	三		SFTP 1	_ •	*	*	*	0.05	0.14	6.0	8.0	0.01	0.20	1.4	2.7
STD	10.0	100	100	SFTP 2	•	*	•	•	*	*		•	*	*	 	*
@ UL			ATIVE FAI	AILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
CERT	0.10	0.1	2 0.00	0.06	*	•	*	*	•	*	*	•	*	*	•	*
STD	0.35	0.3	5 0.05	0.20	•	+	•	•	*	*	*		•	 	•	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are granted a baseline partial zero emission vehicle (PZEV) allowance of 0.2 under 13 CCR Section 1962(c).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______ day of December 2007.

Annette Hebert, Chief

Mobile Source Operations Division