Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TEST GRO			r grou	P	VEHICLE TYPE (PC=passenger car; LDT=light-d truck; MDV=medium-duty vehic LVW=toaded vehicle weight; ALVW=adjusted LVW)	le; CATEGOR	EMISSION STANDA Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super UL	ation E	XHAUST (EXH)/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
201	0	ACRXT03.3UPA			LDT: 6001-8500# GVW, 3751-5750# ALVW	Countee	USEPA Bin4 ( as ARB LEV !! ULE	iv .	120K / 150K	Flexible Fuel: Ethanol (E85) / Gasoline (Tier2 Unleaded)			
No.		APORA MILY (E		No.	SPECIAL FEATU		₩U=wa	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1		ACRXR0150RKA			- TWC, HO25	S(2), SFI, EGR, OB(		AFS/HAFS=air-fuel ratio sensor/hested AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI  TBI= throttle body injection TC/SC=turto/super charger					
2		*				*	ÄIR						
3	*			3		*		CAC=c	CAC=charge air cooler OBD (F) / (P)=full /partial on-board				
4		*		4	·	*	diagnostic prefix 2=parallel (2) suffix=series						
EVA No.		ECS No.	ENGIN SIZE (		VEHICLE MAKES & MODELS		JECT TO SFTP	ABBREV		······································			
1		1 3.3					Dodge Carava	<u>n</u>					
1	1 3.		3.3			Chrysler Town & Country							

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *				NMOG or	The second refueling vector for an interview land ODVD introlling discovery refueling vector fectorery deprint												
CERI	r i	STD	NMOG		NMHC	NMHC STD	mg≂millig	ram mi≠	<u>mile K=10</u>	1000 miles F=d		-degrees Fahrenheit HCHO [mg/mi]		SFTP=supplemental fe PM [g/mi]		deral test procedure Hwy NOx [g/mi]		
0.035	5 0.043 @ 50K @ UL		0.050		*	[g/mi] * 0.070 (0.070)	CERT	[g/mi] STD 2.1 (2.1)		x [g/mi] STD	CE			CERT	g/mij STD 0.01 (0.01)	0.01 (0.01)	0.05 (0.05)	
							0.8		0.01 (0.02)		•		*	*				
										0.04 (0.04)		,	11 (11)	(*)				
<u>├──</u>	@ 50°	F & 4K	*	<u>"</u>	*	*	•	*	*	•	*		*	*	*	*	•	
CO [	g/mī]	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					g/mi] oosite)					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
@ 20		SFTP 2 = @ UL (Tie				CERT	STD	CERT	STD	CERT	STD	CEF	रा ऽा	D CER	T STD	CERT	STD.	
CERT	(2.7)		<u> </u>	SF	TP @ 4K	•	*	•	*	(0.05)	(0.4)	(0.9	9) (10.	5) (0.05	) (0.31)	(1.4)	(3.5)	
STD	(12.5)			SF	TP @ UL	(0.05)	(0.97)	*	*	•	*	(1.:	2) (16.	9) *	<u> </u>	(1.8)	(5.6)	
<u> </u>	_	VAPOR	ATIVE	FAM	LY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-	D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR	
CERT	0.48	Ö.4	17	0.00	0,10	*	•	*	*	*	*	•	*		*		•	
STD	0.90	1.1	5	0.05	0.20	4	*	*	•	•	t	*	*	<b>•</b>	<b>*</b>	•	•	

**BE IT FURTHER RESOLVED**: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2010 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2010 model year vehicles.

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 27 day of April 2009.

Annette Hebert, Chief Mobile Source Operations Division