	Californi	ia Environmental Pro	lection Agency	
C P	AIR	RESOURC	ES BO	ARD

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

No. 1	_	No. 1	SIZE (1 3.3	_)		MAKES & MODELS	ST	ANDARDS AR	brid 4WD				
EVA	F T	ECS	ENGIN			VEHICLE			ECT TO SFTP	ABBREVIATIONS:			
3	* 3				3			*	CAC=charge air cooler idiagnostic prefix 2≖pa	OBD (F) / (P)=full /partial on-board			
2		*]		2			*	TBI= throttle body injec	TBI= throttle body injection TC/SC=turbo /super charger			
1	AT	YXR016	D160E62 1			2WU-TWC, TWC	, 2AF	S, 2HO2S, SFI,	gas recirculation AIR/P	gas recirculation AIR/PAIR=secondary air injection/pulsed			
No.		VAPORATIVE No. E				SPECIAL FEATU EMISSION CONTROL S			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated Q2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust				
201	2010 ATYXT03.3CC4					LDT: 6001 - 8500# GVW, 3751-5750# ALVW	LEV II SULEV			120K / 150K	Gasoline plus Battery-Assist		
MODI YEA		TEST	T GROUP truc			VEHICLE TYPE PC=passenger car; LDT=light-du ruck; MDV=medium-duty vehicle LVW=toaded vehicle weight; ALVW=adjusted LVW)	STANDAI (LEV=low emi transitional L	ST EMISSION RD CATEGORY Ission vehicle; TLEV= EV; ULEV=ultra LEV; /=super ULEV)		FUEL TYPE (CNG/LNG≖compressed/ liquefied natural gas; LPG≕liquefied petroleum gas)			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *			RAF = * AF = *	NMOG or	nitrogen	HCHO=for	maidehyde	PM=par	ticulate m	latter F	AF=reacti	rbon CO≖c ∕ity adjustm =on-board r	ent factor	2/3 D [g/test)=2/3 day		
CERT	T ST	D	NMOG NMHC		NMHC STD	ng≃millig		. įganų–rur mile K=1	000 miles	F=deg	grees Fa	hrenheit	SFTP=supp	eruenny vap	deral test pr	ocedure	
0.045		CERT				[g/m]]	CO [g/mì]		NO	NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/ml]	
0.045	0.045 0.045		[g/mi]	[g/mi]	[ä]	CERT	STD	CERT	ST	D CE	ERT	STD	CERT	STD	CERT	STD	
"是"是"这	0 2 0	@ 50K *		*	*	*	* *			* *		*	*	*	*	*	
- 20		2) UL	0.008	*	0.010	0.05	1.0	0.01	0.0	2	*	4	*	0.01	0.01	0.03	
1. A. S.	@ 50°F	& 4K	*	٠	+	•	*	*	*		*	*	*	*	*	*	
	CO [g/mi] SFTP 1 = @ 4K @ 20°F & LEV) or 5		4K (SULEV, ULEV, NMHC+NC v) or 50K (Tier 1, TLEV) (compo					NMHC+NOx [g/mi] [U\$06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/ml] [SC03]			
50			🕲 UL (Tier		CERT	STD	CERT	STD	CERT	STD	CEF	T ST	D CERT	STD	CERT	STD	
CERT	1.5	的论论的	1997 - 19 1 97	SFTP 1	*	*	*	*	0.01	0.40	1.0) 10.	5 0.003	0.31	0.03	3.5	
STD	12.5			SFTP 2	*	*	+	*	*	*	. *	*	*	*	*	*	
@ UL -	EVA	PORA'	TIVE FAN	ILY 1	EVAPORATIVE FAMILY 2 EV					EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ÓRV	R 3-D	2-D	RL	ORVR	
CERT	0.22	0.12	0.01	0.03	*	*	*	*	*	*	*	*	*	*	*	*	
STD	0.75	0.75	0.05	0.20	*	*	*	*	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That at the request of the manufacturer, the listed vehicle models are certified to the optional zero-fuel evaporative emission standards in 13 CCR Section 1976 (b)(1)(E) which allows an exhaust NMOG credit of 0.002 grams per mile to be applied against the measured NMOG emissions in certification and in-use testing pursuant to CCR Section 1961(a)(11).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte. California on this 23 day of July 2009.

mutt Akken

Annette Hebert, Chief Mobile Source Operations Division