

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=ligi truck; MDV=medium-duty ve LVW=loaded vehicle weig ALVW=adjusted LVW)	hicle; ht;	STANDA (LEV=low emitransitional L	ST EMISSION RD CATEGORY ssion vehicle; TLEV= EV; ULEV=ultra LEV; /=super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE  {CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2010		ATYXV01.8HC3			Passenger Car	Emis	Super-Ultra Low sion Vehicle VII SULEV)	150K / 150K	Gasoline plus Battery-Assist				
No.		APORATIVE NILY (EVAF)			SPECIAL FE EMISSION CONTRO			* = not applicable	134-0- Marini-up car. Ozoriozo-oxygen sensonneated Ozo				
1	ATY	ATYXR0110P42			WU-TWC, TW	C, AFS, I	HO2S, EGR, SF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AR/PAIR=secondary air injection/pulsed AIR MFVSFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger					
2		•					4						
3		*					*	CAC=undo body injection   U/SC=undo /super charger   CAC=charge air cooler OBD (F) / (P)=full /partial on-board   diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.					ECT TO SFTP E UNDERLINED	ABBREVIATIONS:							
1		1	1 1.8		Toyota Prius								
*		*						*					

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

AVERAGE [g/ml]				NMOG @ RAF = * CH4 RAF = *			nitrogen	HCHO=for	rmaidehyde	organic gas PM≖partic	culate ma	atter RAI	F=reactiv	ity adjustme	ent factor	2/3 D (a/test	1=2/3 day
CER	┖	STD NMOG			NMHC	NMHC	diurnal+hot-soak RL [g/mt]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=mtiligram mi=mtile K=1000 mtles F=degrees Fahrenheit SFTP=supplemental federal test procedure										
0.02	в	0.035	_	ERT	CERT [g/mi]	(g/mi)	CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
				g/mi]		101	CERT	STD	CER	_ STD	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K		*	*	*	*	*	*	*		*	*	* 1	*	+	*
		@ UL		.005		0.010	0.04	1.0	0.003	0.02	•	•	4	•	0.01	0.002	0.03
. 4	@ 50			•		•	*	•	*	•	*	* *		*	•	*	•
CO [ @ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)						g/mi] oosite)					NMHC+NOx [g/mi] [SC03]		CO [g/ml] [SC03]		
	50K		SFTP 2 = @ UL (Tier		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CERT	STE	CERT	STD	CERT	STD
CERT	0.6				SFTP 1	*	*	•	*	0.01	0.14	0.1	8.0	0.01	0.20	0.1	2.7
STD	10.0				SFTP 2		•	*	*	•	*	*	<b>*</b>	*		•	*
@ UL	EVAPORATIVE FAMILY 1					EVA	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3 <b>-</b> D	2	Ò	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	₹ 3-D	2-D	RL	ORVR
CERT	0.20	0.	28	0.00	0.01	1	*	*	*	*	*	*	*	*	*	*	*
STD	0.35	j 0.	35	0.05	0.20	*	•	*		- •		•		*	*	+ +	+

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models have been certified as an advanced technology (AT) partial zero emission vehicle (PZEV)—Type E Hybrid Electric Vehicle (HEV) and are granted a baseline PZEV allowance of 0.2 and additional PZEV allowances under 13 CCR Section 1962(c).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2010 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2010 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of March 2009.

Annette Hebert, Chief
Mobile Source Operations Division