

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

1		1 3.5					Lexus GS 450h					
EVA!							EHICLES SUBJECT TO SFTP ANDARDS ARE <u>UNDERLINED</u> ABBREVIATIONS:					
3	•			3 .	,	•	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
2		•				*	igas recirculation AiR/PAIR≕secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI ■ TBI= throttle body injection TC/SC=turbo /super charger					
1	ATY	ATYXR0160E12			2WU-TWC, 2TWC, 2A	AFS, 2HO2S,DGI,						
No.		APORATIVE			SPECIAL FEATUR EMISSION CONTROL SY		* = not applicable	MOC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S — AFS/MAFS=air-fuel ratio sensor/heated AFS EGR=exhaust				
2016	0	ATYXV03.5CC4			Passenger Car	Emi:	Super-Ultra Low ssion Vehicle EVII SULEV)	120K / 150K	Gasoline plus Battery-Assist			
MODE		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STANDA (LEV=low en transitional SULE	UST EMISSION ARD CATEGORY hission vehicle; TLEV= LEV; ULEV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)    EXHAUST & ORVR (CNG/LNG=compress)				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

	NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *			) RAF = * AF = *	NMOG or	nitrogen	HCHO=for	maldehyde	PM≖par	ticulate m	atter	RAF reactive	rity adjustn	arbon mono ent factor i efueling vap	2/3 D [g/test	]=2/3 day
CER	т [ :	STD NMOG NMHC		NMHC	mg=millig			000 miles			shrenheit	SFTP=sup	plemental fe	deral test p	rocedure	
0.02		0.035	CERT [g/mi]	CERT [g/mi]	[g/mi]	CO	[g/mi]	, NC	x [gimi]	Н	сно [	[mg/mi]	PM [	/ml]	Hwy NC	x [g/ml]
	-   -					CERT	STD	CERT	r STO	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	*		•	٠	•	•	*		*	*	*	*	*	*
		@ UL	800.0	•	0.010	0.1	1.0	0.01	0.0	2	*	4	*	0.01	0.01	0.03
	<b>@</b> 50°	F & 4K	•	*	+	*	*	*	*		*	*	*		*	*
	CO [g/mi] SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)						D [g/mi] NMHC+ mposite) [g/mi] [L					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CER	T STD	CERT	STD	
CERT	1.6			SFTP 1	*	*	*	*	0.02	0.14	0.	8 8.0	0.02	0.20	0.01	2.7
STD	10.0			SFTP 2	*	*	*	*	•	•	•		*	•	•	•
<b>45.11</b>	E,	VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2			EVA	EVAPORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	₹ 3-D	2-D	RL	ORVR
CERT	0.41	0.4	5 0.01	0.03	•	•	•	•	•	•		•	*	*	•	•
STD	0.50	0.6	5 0.05	0.20	*	*	*	*	* '	*	*	*	*	•	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

EXECUTIVE ORDER A-014-0673 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

<u>3<sup>22</sup></u> day of Augut 2009. Executed at El Monte, California on this

Annette Hebert, Chief
Mobile Source Operations Division