	Protection Agency	RYLFORMEN	California		
ADD	Protection Agency RCES BOA	EGOI	AID D	フラー	$\mathbf{\epsilon}$
	RCES BO/	FSOL		ノミレ	C

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE	VUEL TEET CONID			•	VEHICLE TYPE (PC=passenger car; LDT=light-dut; truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)		EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2010	2010 ATYXV05.0CC4			4	Passenger Car	Emis	Super-Ultra Low sion Vehicle VII SULEV)	120K / 150K	Gasoline plus Battery-Assist			
No.		NPORA		No.	SPECIAL FEATU EMISSION CONTROL S		WU= warm-up cat. 02S/	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S				
1	ATY	XR018	30E12	1	2WU-TWC, 2ADSTWC	, 2AFS, 2HO2S, DO	gas recirculation AIR/PA	ensor/heated AFS EGR=exhaust IR=secondary air injection/pulsed				
2		*	1	2		*		AIR MFI/SFI= multipor	t fuel injection/sequential MFI on TC/SC=turbo /super charger			
3	* 3			3		*		OBD (F) / (P)=full /partial on-board				
EVAF No.		ECS No.	ENGINE SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB	JECT TO SFTP RE <u>UNDERLINED</u>	ABBREVIATIONS:				
1		1	5.0		Lexus LS 600hL							
*		*	*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *				NMOG or	nitrogen	HCHO=fo	rmaldehyde	s PM≃pa	rticulate m	natter	RAF=reactiv	ity adjustm/	arbon mono ent factor efueling vap	2/3 D [a/test]=2/3 dav								
CERI	r s	STD	NMOG	NMHC	NMHC STD	mg=millig			000 miles			hrenheit		plemental fe									
0.028	2 0	.035		CERT CERT [g/mi] [g/mi]								[g/mi]		[g/mi])x [g/mi]			ng/mi]	PM (g		Hwy NO	x (g/mi)
0.020			[g/mi]			CERT	STD	CERI	r st	D CI	ERT	STD	CERT	STD	CERT	STD							
	(@ 50K	*	*	*	*	*		•		*	*	*	*	*	*							
		@ UL	0.006	*	0.010	0.17	1.0	0.002	2 0.0	2	*	4	•	0.01	0.004	0.03							
	@ 50°F	F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*							
	CO [g/mi] SFTP 1 = @ 4K (SULEV, ULEV @ 20°F & LEV) or 50K (Tier 1, TLE		.EV, ULEV, ler 1, TLEV)		NOx [g/mi] CO [g/mi] posite) (composite)			NMHC+NOx CO [g/mi] [g/mi] [US06] [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]										
50		SFTP 2	= 🧑 UL (Tie	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEI	RT STI	CER	r std	CERT	STD							
CERT	2.0			SFTP 1	*	*	*	*	0.01	0.14	0.0	2 8.0	0.013	0.20	0.01	2.7							
STD	10.0			SFTP 2	*	*	*	*	*	*	*	*	*	*	•	*							
@ UL	EVAPORATIVE FAMILY 1				EVA	EVAPORATIVE FAMILY 2 EVA			VAPORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4										
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ÖRV	R 3-D	2-D	RL	ORVR							
CERT	0.17	0.1	7 0.003	0.034	*	*	*	*	*	*		*	*	*	*								
STD	0.50	0.6	5 0.05	0.20	*	*	-*- T	*	*	*		*	*	*	*	*							

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

California Environmental Protection Agency

TOYOTA MOTOR CORPORATION

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of November 2009. Heken l

Annette Hebert, Chief Mobile Source Operations Division