

MITSUBISHI MOTORS CORPORATION

EXECUTIVE ORDER A-086-0301 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			VEHICLE TYPE {PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)			EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=utra LEV; SULEV=super ULEV) "LEV II" Low Emission Vehicle (LEVII LEV)			EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles) FUEL TYPE (CNG/LNG=compre liquefied natural LPG=liquefied petro gas)			
201	0	AMTXT02.4GRB				LDT <6,000 pounds GVW 0-3750 # LVW; 3,751-5750 # L	120K / 150K				Gasoline			
No.			PATIVE Y (EVAF)			SPECIAL FEATU EMISSION CONTROL S		S (ECS)	0	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated C2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=ascondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=tunb super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
1	1 AMTXR0135A1D			1		TWC(2), HO2	S(2), E(GR, SFI, OBI	A					
2		•			T		*		Ä					
3		•					*		C					
4							*		ď					
EVAI No.		ECS ENGINE VEHICLE VEHICLES SUBJECT No. SIZE (L) MAKES & MODELS STANDARDS ARE U						ABE	BREVIATIONS:					
1	1	1 2.4			(LDT1) MITSUBISHI OUTLANDER 2WD; (LDT2) MITSUBISHI OUTLANDER 4WD									

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG (CH4 F	® RAF≖* RAF = *	NMOG or NMHC STD	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment facbr 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=nunning loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
STD-L	STD-LDT1 STD-LDT2		NMOG NMHC			mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
0.03	E	0.043	CERT	CERT [g/mi]	[g/mi]		g/mi]		x [g/mi]			[mg/mi]		g/mi]	Hwy NO:		
0.03	,5	0.045	[g/mi]			CERT	STD	CERT	STE) C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.035 *		0.075	0.4	3.4	0.03	0.08	5	*	15	*	* .	0.01	0.07	
	@ UL		0.046	•	0.090	0.8	4.2	0.05	0.07	7	*	. 18	•	0.01	0.03	0.09	
	@	50°F & 4K	0.094	*	0.150	0.7	3.4	0.02	0.08	5	•	*	*	*	*	*	
CO [@ 20			9 4K (SULEV, ULEV, or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NO [g/mi] [US0				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50K			UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD	
CERT	1.9		SF	TP @ 4K		*	*	*	0.01	0.14	4.	.4 8.0	0.01	0.20	0.5	2.7	
STD	10.0		SF	TP@UL	•	*	*	*	*	*	•	*	*	*	*	•	
@ UL		EVAPORAT	VE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3			MILY 3	E	VAPORAT	IVE FAMILY 4		
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	0.12	2 0.14	0.01	0.02	*	*	*	٠	•	*	*	*	*	*	*	*	
STD	0.65	0.85	0.05	0.20	+	*	*	•	*	-		*	+	*	•	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law.



MITSUBISHI MOTORS CORPORATION

EXECUTIVE ORDER A-086-0301 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: That at the request of the manufacturer, LDT models in this test group with a GVW over .6,000 pounds are certified to, and shall be required to comply with, the evaporative emission standards applicable to LDT under 6,000 pounds GVW. That at the request of the manufacturer, LDT models in this test group with a LVW 3751 to 5750 pounds are certified to, and shall be required to comply with, the passenger car SFTP standards.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

_ day of July 2009.

Annette Hebert, Chief

Mobile Source Operations Division