California Environmental Protection Agency

EXECUTIVE ORDER A-002-0170-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

tes	TEST GROUP			DV=medium-duty vehicle; LVW=le	truck; STAN baded (LEV	IDARD CATEGORY low emission vehicle; ULEV=ultra LEV;	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE		
BFJ	BFJXJ02.5NVD			(PC; LDT 0 - 3,750 pounds LV	/W;	LEV II SUL <b>EV</b>	15 <b>0K /</b> 150K	Gasoline		
			No.			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated Q2S				
BFJXR01	JXR01444DR			TWC(2), HAFS	HO2S, SFI, EGR	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed				
*	*		2		*	AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board				
*	*		3		.*					
*	*		4		*					
ECS	ENC	SINE		VEHICLE	VEHICLES SU	BJECT TO SFTP				
No. SIZE (L)		)	MAKES & MODELS	STANDARDS /	ARE UNDERLINED					
1	1 2.5			SUBARU: (PC) LEGACY AWD						
1	1 2.5			SUBARU: (LDT 0-3,750 pounds LVW) OUTBACK WAGON AWD (Manual Transmission models)						
1	1 2.5			SUBARU: (LDT 3,751-5,750 pounds LVW) OUTBACK WAGON AWD (Automatic Transmission models)						
*	* *			*						
	EVAPOR FAMILY ( BFJXR01) * * * ECS	EVAPORATIVE FAMILY (EVAF)       BFJXJ02.51       EVAPORATIVE FAMILY (EVAF)       BFJXR01444DR       *       *       *       *       *       1       1       1       1       2       1       2       1	EVAPORATIVE FAMILY (EVAF)       BFJXR01444DR       *       *       *       *       *       *       1       2.5       1       2.5	TEST GROUP     No.       BFJXJ02.5NVD     No.       EVAPORATIVE FAMILY (EVAF)     No.       BFJXR01444DR     1       *     2       *     3       *     3       *     4       ECS     ENGINE No.       NO.     SIZE (L)       1     2.5       1     2.5       1     2.5	L   TEST GROUP   (PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW=le vehicle weight; ALVW=adjusted L     BFJXJ02.5NVD   PC and LDT ≤ 6,000 pounds C     BFJXJ02.5NVD   (PC; LDT 0 - 3,750 pounds L)     EVAPORATIVE   No.   SPECIAL FEATL     FAMILY (EVAF)   No.   SPECIAL FEATL     *   2   *   3     *   2   *   3     *   4   ECS   ENGINE     No.   SIZE (L)   MAKES & MODELS     1   2.5   SUBARU: (LDT 0-3,751–	L TEST GROUP (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) STAM (LEV: MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)   BFJXJ02.5NVD PC and LDT 6,000 pounds GVW (PC; LDT 0 - 3,750 pounds LVW); LDT 3,751 - 5,750 pounds LVW) SPECIAL FEATURES & FAMILY (EVAF)   EVAPORATIVE No. SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS)   BFJXR01444DR 1 TWC(2), HAFS, HO2S, SFI, EGR, *   * 2 *   * 3 *   * 3 *   * 4 *   ECS ENGINE No. VEHICLE MAKES & MODELS STANDARDS   1 2.5 SUBARU: (LDT 0-3,750 pounds LV 1 2.5	L   TEST GROUP   (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)   STANDARD CATEGORY (LEV=low mission vehicle; ULEV=outernission vehicle; ULEV=outernission vehicle; ULEV=utra LEV; SULEV=super ULEV)     BFJXJ02.5NVD   PC and LDT ≤ 6,000 pounds GVW (PC; LDT 0 - 3,750 pounds LVW; LDT 3,751 - 5,750 pounds LVW; LDT 3,751 - 5,750 pounds LVW;   LEV II SULEV     EVAPORATIVE FAMILY (EVAF)   No.   SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS)   >= not applicable     *   2   *   *   3   *     *   3   *   *   2   *     *   3   *   *   *   5     ECS   ENGINE No.   SIZE (L)   MAKES & MODELS   STANDARD CATEGORY (LEV=outer)   *     1   2.5   SUBARU: (LDT 0-3,750 pounds LVW)   SUBARU: (PC) LEGA( 1   2.5   SUBARU: (LDT 0-3,750 pounds LVW) OUTBACK WAG	L   TEST GROUP   VEHICLE TIPE   STANDARD CATEGORY   EVAPORATIVE     MDV=medium-duty vehicle; LVW=loaded   Vehicle weight; ALW=adjusted LVW;   STANDARD CATEGORY   EVAPORATIVE     BFJXJ02.5NVD   PC and LDT 6,000 pounds GVW   LEV II SULEV   USEFUL LIFE (UL);   (miles)     EVAPORATIVE   PC and LDT 6,000 pounds GVW;   LEV II SULEV   150K / 150K     EVAPORATIVE   No.   SPECIAL FEATURES &   *   150K / 150K     FAMILY (EVAF)   No.   SPECIAL FEATURES &   *= not applicable   OC/TWC=oxidizing/3-way GWU = warm-up cat. 025/HL     *   2   *   *   2   *   AFS/HAPS=air-fuel ratio se gas recirculation AIR/PAIF     *   2   *   *   0C/TWC=oxidizing/3-way GWU = warm-up cat. 025/HL     *   2   *   *   0C/TWC=oxidizing/3-way GWU = warm-up cat. 025/HL     *   2   *   *   0C/TWC=oxidizing/3-way GWU = warm-up cat. 025/HL     *   2   *   *   0C/TWC=oxidizing/3-way GWU = warm-up cat. 025/HL     *   2   *   *   0C/TWC=oxidizing/3-way GWU = warm-up cat. 025/HL     *   2   *   *   0C/TWC=oxidig		

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

-		FLEET GE [g/mi] STD	CH NMOC	4 ŘAF	NMHC	NMOG or NMHC STD	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment fador 2/3 D [g/test]=2/3 day diumal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure										
[	COLDIT LOTZ		CERT	(g/mi] [g/m	CERT	[g/mi]		[g/mi]		x [g/mi]			mg/mi]		g/mi]	Hwy NO:	
- 1	0.035	0.043 (g/m)	<b>19/</b> mij		CERT		STD	CERT	STE	) C	ERT	STD	CERT	STD	CERT	STD	
102.00.0		@ <b>50</b> K	K *		*	•	*	*	*	*		*	*	*	*	*	*
1000		@ UL	0.007		*	0.010	0.3	1.0	0.01	0.0	2	*	4	*	0.01	0.004	0.03
	9	50°F & 4K	<b>0</b> .015		*	0.020	0.4	1.0	0.01	0.0	2	0.5	8	*	*	*	*
	CO [g/n @ 20°F				er 1, TLEV) (COMP					NMHC+NC [g/mi] [US0				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
	50K	SFTP 2	:=@UL(	Tier 1, '	TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD
	CERT 1	.0	an an		SFTP 1	*	*	*	*	0.01	0.14	3	.6 8.0	0.02	2 0.20	0.01	2.7
	STD 10	0.0	ale and		SFTP 2	*	*	*	*	*	*		* *	*	*	*	*
	au	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	@ UL	3-D 2-	D F	۲L	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	R 3-D	2-D	RL	ORVR
[	CERT	0.15 0.1	2 0	.00	0.01	*	*	*	*	*	*	*	*	*	*	*	*
Ĩ	STD	0.35 0.3	35 0	.05	0.20	*	*	*	*	*	*	*	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962.1 (c)(2).

California Environmental Protection Agency AIR RESOURCES BOARD

**BE IT FURTHER RESOLVED**: The vehicles in the test group certified in this Executive Order shall have the air/fuel (A/F) sensor protection strategy as submitted to the Air Resources Board on July 6, 2010. This Executive Order is effective and applicable to vehicles in the listed test group that are produced on and after July 21, 2010 and on this date supersedes Executive Order A-002-0170-1.

BE IT FURTHER RESOLVED: The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have six deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$125 per vehicle for the third through sixth deficiencies in the listed test group that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2011 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

**BE IT FURTHER RESOLVED:** The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

day of July 2010. Executed at El Monte, California on this

IL FOR ANWETTE HEBERT Annette Hebert, Chief

Annette Hebert, Chief Mobile Source Operations Division