

## **DAIMLER AG**

EXECUTIVE ORDER A-003-0414-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR		TEST GROUP		VEHICLE TYPE (PC=passenger car; LDT=ilght-dut) MDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	STAND: (LEV=lo: UL	UST EMISSION ARD CATEGORY w emission vehicle; EV=utra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE				
2011		BMBXJ05.5U2A		A	PC and LDT > 6,000 pounds ( PC; LDT > 5,750 pounds AL	L	EV 11 ULEV	120K / 150K	Gasoline (Tier 2 Unleaded)				
No.		APORA AILY (E		No	SDECIAL FEAT	URES &		* = not applicable	DC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC Wijs warm-up cat. O2S/HO2S=oxygen sensor/heated O2: AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaus				
1		XR016		1	2TWC,2H	028(2),5	FI, AIR,OBD	BAFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust					
2	BMBXR0170LNC			2	· ·	*		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFKSFI= multiport fuel injection/sequential MFI TBi= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)-full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
3	BMBXR0165LNC			3		*							
4	BMBXR0170LNS			4		*		diagnostic prefix 2=parallel (2) suffix=series					
EVAI	F	ECS No.	ENGIN SIZE (L		VEHICLE MAKES & MODELS	VEH	ICLES SUBJ	ECT TO SFTP E <u>UNDERLINED</u>					
1		1	5.5	<del>-</del>	MERCEDES-BENZ; (PC) SL550								
2		1	4.7	一	MERCEDES-BENZ; (LDT > 5.750 pounds ALVW) GL 450 4MATIC								
2		1	5.5		MERCEDES-BENZ: (LDT > 5.750 pounds ALVW) ML 550 4MATIC / GL 550 4MATIC / G550								
3	$\neg$	1	5.5	_	MERCEDES-BENZ: (PC) CLS 550 / E 550 / E 550 (coupe) / E 550 (Convertible) / E 550 4MATIC								
4		1	5.5		MERCEDES-BENZ: (PC) S 550 / S 550 4MATIC								
•	$\neg$	*	*	$\neg \uparrow$	*								
*		+	*		•								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (The STD and CERT in parentheses are those applicable to the LDT2 models, if different.)

NMOG FLEET AVERAGE [g/ml]			NMOG @ RAF = * CH4 RAF = *		NMOG or	of nitroger	· HOHOLE	أحددتها ومسوء	e Diamete	diculata n	witer	KAFERECKY	ALV BONISH	D=carbon mo ent factor : efueling vap	23 U   OVIESI	-203 GEY	
STD PC/LD1		STD LDT2	NMOG	NMHC	NMHC STD	diumal+ho mg=milligi		mile K=10	selim 000	F=deg	rees Fa	hrenheit	SFTP=sup;	olemental re	zerai test pi	ocedure	
- OILD			CERT	CERT	[g/mi]	CO [g/ml] N		NO:	x [g/ml]	H	HCHO [mg/mi]		PM (g/mi)		Hwy NOx [g/ml]		
0.035	;   C	0.043	[g/mi]	[g/ml]	(S)	CERT	STD	CERT	STD	CE	RT	STD	CERT	STD	CERT	STD	
		@ 50K	0.025	*	0.040	0.5	1.7	0.04	0.05	0	.4	8	*	*	0.02	0.07	
	1.5	€ UL	0.042	+	0.055	0.8	2.1	0.05	0.07	,	1	11	•	0.01	0.03	0.09	
الم المستمولة	Ø 50°	°F & 4K	•	•		*	•	•	*		*	*	*	*	*	*	
CÖ [	CO [g/mi] SFTP 1 = @ 4K (SULEY, ULEY, LEV) or 50K (Tier 1, TLEV)			EV, ULEV, ler 1. TLEV)	NMHC+NOx [g/mi] CO [g/mi] (composite) (composite				NMHC+NOx CO [g/mi] [g/mi] [US06] [US06]				NMHC+NOx [g/ml] [SC03]		CO [g/mi] [SC03]		
50		SFTP 2 = @ UL (Tier		1, TLEV)	CERT	ŞTD	CERT	STD	CERT	STD	CEI	RT ST	CER	T STD	CERT	STD	
CERT	3.5	· ·		SFTP 1	*	•	•	*	0.11	0.14	1.	1 8.0	0.05	0.20	1.8	2.7	
STD	10.0			SFTP 2	*	*	•	*	*	*	*		<u> </u>		*		
	F	VAPOR	ATIVE FAI	AILY 1	EVA	EVAPORATIVE FAMILY 2 EVAPORATIVE				ORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
@ UL	3-D			ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR	
CERT	0.45				0.53	*	0.00	80.0	0.29	*	0.0	0.01			0.00	0.00	
STD	0.50				0.90	1.15	0.05	0.20	0.50	0.65	0.0	5 0.20	0.50	0.65	0.05	0.20	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).



## **DAIMLER AG**

EXECUTIVE ORDER A-003-0414-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Orders A-003-0414 dated February 11, 2010 and A-003-0414-01 dated April 30, 2010.

Executed at El Monte, California on this \_\_\_\_\_\_day of August 2010

Annette Hebert, Chief

Mobile Source Operations Division