California Environmental Protection Agency		EXECUTIVE ORDER A003-0419-1
AIR RESOURCES BOARD	DAIMLER AG	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

## IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR			EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (*=N/A or A/E=ex	/EDIATE USE LIANCE full in-use; h. / evap. iate in-use)	FUEL TYPE	
2011	BMBXV06.3U2A	Passenger Car	"LEV II" Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2	
2011	BINDAVUG.302A	r assenger oa	ULEV)	120K	150K	*	*	Unleaded)	
No.	ECS & SP	ECIAL FEATURES	EVAPORATIVE	FAMILY (EV	DISPLACEMENT (L)				
1	2WU-TWC,2TWC, 2	2HO2S(2), SFI, AIR, OBD(P)	BMBXR0	165LNC					
*		*	BMBXR0	168LNA		6.2			
*		*	BMBXR0	170LNS					
*		*		*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

#### BE IT FURTHER RESOLVED:

The SLS AMG model within the listed models is conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the SLS AMG model alone has been determined to have three deficiencies. The SLS AMG model is approved subject to the manufacturer paying a fine of \$25 per SLS AMG vehicle with the third deficiency within the listed test group that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of SLS AMG model vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2011 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-003-0419 dated April 30, 2010.

Executed at El Monte, California on this <u>6<sup>+k</sup></u> day of July 2010.

0

FOR ANNETTE HEBERT u in **1**84-

Annette Hebert, Chief Mobile Source Operations Division

EXECUTIVE ORDER A-003-0419-1



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fue).

NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *		NMOG or	HCHO=forr	naldehyde; f	M=particu	late matter;	RAF=reac	tivity adjustr	nent facto	r; 2/3 D [g/te	st]=2/3 day				
CERT	STD	NMOG	NMHC	NMHC STD		1000 miles;								am; <b>mg</b> ≖milli	gram
0.019	0.035	CERT CERT		[g/mi]	CO [g/mi]		NOx [g/mi] H		H	HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.019	0.035	[g/mi] [g/mi]	/mi] [g/mi]	L91	CERT	STD	CERT	STC	CE	RTS	TD	CERT	STD	CERT	STD
	@ 50K	0.009	*	0.040	0.8	1.7	0.01	0.05	5 0.	2	B.	*	*	0.010	0.07
	@ UL	0.010	*	0.055	1.0	2.1	0.02	0.07	/ 0.	3 1	1.	*	0.01	0.015	0.09
0	50°F & 4K	0.039	*	0.080	0.7	1.7	0.005	0.05	5 0.	7 1	6.	*	*	*	*
CO [g				NMHC+NC (compo		CO [g (comp		NMHC [g/mi]	:+NOx [US06]		g/mi] i06]		C+NOx [SC03]		g/mi] :03]
@ 20°F (	£ 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	3.2	SFTP @ 4	000 miles	*	*	*	*	0.03	0.14	0.8	8.0	0.01	0.20	0.4	2.7
STD	10.0	SFTP	@ * miles	*	*	*	*	*	*	*	*	*	*	*	*

Evaporative Family	3-Days Diurn (grams/te		2-Days Diurn (grams/te			ng Loss nile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
BMBXR0165LNC	0.29	0.50	*	0.65	0.00	0.05	0.01	0.20	
BMBXR0168LNA	0.45	0.50	*	0.65	0.00	0.05	0.02	0.20	
BMBXR0170LNS	0.39	0.50	*	0.65	0.00	0.05	0.00	0.20	
*	*	*	*	*	*	*	*	*	

\* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=\*85%\* Ethanol Fuel

## 2011 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
MERCEDES-BENZ	C 63 AMG	BMBXR0165LNC	1	6.2	*	*	SFTP	Partial
MERCEDES-BENZ	E 63 AMG	BMBXR0165LNC	1	6.2	*	*	SFTP	Partial
MERCEDES-BENZ	SLS AMG	BMBXR0170LNS	1	6.2	*	*	SFTP	Partial
MERCEDES-BENZ	SL 63 AMG	BMBXR0168LNA	1	6.2	*	*	SFTP	Partial