

VOLVO CAR CORPORATION

EXECUTIVE ORDER A-018-0175 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT≖light-du MDV=medium-duty vehicle; LVW vehicle weight; GVW=gross	STAND (LEV=low of transitions	AUST EMISSION DARD CATEGORY Prinission vehicle; TLE ILEV; ULEV=ultra LI EV=super ULEV)	V=	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
201	1	BVV	XJ03.2S2	N	PC and LDT ≤ 6,000 pounds (PC; LDT 3,751-5,750 pound	"LEV II" Super Ultra Low Emission Vehicle (LEV II SULEV)			150K / 150K	Gasoline					
No.		EVAPORATIVE FAMILY (EVAF)			SPECIAL FEATEMISSION CONTROL				OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	1 BVVXR0141ZER			1	SFI, 2HO2S,	SFI, 2HO2S, HAFS, TWC, DOR, OBD(P)					AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed				
2	*			2	•					AIR MFI/SFI≖ multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=futl /partial on-board					
3	_	*			•										
4	*			4		diagnostic prefix 2=parallel (2) suffi									
EVAI No.		CS No.	ENGIN SIZE (VEHICLE MAKES & MODELS			ECT TO SFTP E UNDERLINED	AB	BREVIATIONS:					
1	1 3.2				VOLVO: (LDT 3,751-5,750 pounds LVW) XC70 3.2; XC60 3.2; XC70 3.2 AWD; XC60 3.2 AWD										
1	1 3.2				VOLVO: (PC) S80 3.2										
*		* *			<u>-</u>										
*	* *						*								

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	MOG F	LEET [g/mi]	NMOG @ RAF= * CH4 RAF = *		NMOG or NMHC	nitrogen	HCHO=for	rmaldehydd	e PM≕pai	rticulate m	atter RA	F≐reactivit	y adjustme	nt factor :	xide NOx= 2/3 D [g/test or recovery	=2/3 day
STE	TD STD		NMOG	NMHC		mg≂millig		∟ įg/mij–ru mile K=1	lining ioss 1000 miles	F=deg	rees Fahi	enheit S	FTP=suppl	emental fe	deral test pr	ocedure
PC	PC LDT2		CERT CERT		STD											
0.03	5	0.043	[g/mi]	[g/mi]	[g/mi]		[g/mi]		ox [g/mi]		CHO [m		PM [g/		Hwy NO	
	1					CERT	STD	CER	T ST	D CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	*	*	•	*	*	*	*		*	*	*	*	*	*
74		@ UL	0.005	*	0.010	0.4	1.0	0.01	0.0	2	*	4	*	0.01	0.005	0.03
	@	50°F & 4K	0.016	*	0.020	0.5	1.0	0.01	0.0	2	*	8	*	*	*	*
CO [@ 20	g/mi] °F &					IOx [g/mi] CO [g/mi] posite) (composite)			NMHC+NOx [g/mi] [US06]					IC+NOx] [SC03]		[g/mi] 203]
50		SFTP 2 = @ UL (Tier 1, T		i, TLEV)	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	1.0		SF	TP @ 4K	*	*	*	*	0.03	0.14	0.8	8.0	0.002	0.20	0.3	2.7
STD	10.0		SF	TP @ UL		*	*	*	*	*	*	*	*	*	*	*
@ UL	E	VAPORAT	VE FAMI	LY 1	EVAPORATIVE FAMILY 2					EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
W UL	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.20	0.21	0.02	0.06	*	*	*	*	*	*	*	*	*	*	*	*
STD	0.35	0.35	0.05	0.20	*	*	*	*	*	*	*	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume



VOLVO CAR CORPORATION

EXECUTIVE ORDER A-018-0175 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED:

That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962 (c)(2). The listed vehicle models are granted a 0.005 g/mi NMOG credit for all certification and in-use testing pursuant to 13 CCR Section 1961(a)(12) [direct ozone reduction]. The exhaust NMOG and fuel-evaporative certification emissions include application of the adjustment of 0.1g/test fuel-evaporative emission for 0.002g/mi NMOG emission. This adjustment can also be applied to all certification and in-use testing pursuant to 13 CCR Section 1976(b)(1)(E).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of June 2010.

Annette Hebert, Chief

Mobile Source Operations Division