GENERAL MOTORS LLC

EXECUTIVE ORDER A-006-1766 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR		TEST GROUP		VEHICLE TYPE (PC=passenger car; LDT=light-dt MDV=medium-duty vehicle; LVW vehicle weight; GVW=gross	STANDA (LEV=low en transitional	JST EMISSION ARD CATEGORY hission vehicle; TLE LEV; ULEV=ultra LE V=super ULEV)	V=	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
2012	2 C	SMXJ03.61	66	PC and LDT < 6000# G\ (PC; LDT 3751-5750# LV	USEPA Bin 4 Counted as ARB LEV2 ULEV			120K / 150K	Flexible Fuel: Ethanol (E85)/Gasoline (Tier 2 Unleaded)					
No.		RATIVE (EVAF)	No	SPECIAL FEATEMISSION CONTROL			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S							
1	CGMXR	0133810	1	2TWC(2),	, 2HO2S(2), DGI, OBD(P	ag.	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed						
2	CGMXR0170956			2TWC, TW	C, 2HO2S	(2), DGI, OBD		AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection DGI= direct gasoline fuel						
3		* 3			*		ir	injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic						
4		*			*			refix 2=parallel (2) suffi						
EVAF No.	ECS No.	ENGI		VEHICLE MAKES & MODELS			CT TO SFTP UNDERLINED	ABE	BREVIATIONS:					
1	1	1 3.6		CHEVROLET: (PC) CAPRICE PPV										
1	2	2 3.6			CHEVROLET: (PC) IMPALA									
1	2 3.6				BUICK; (PC) LACROSSE, LACROSSE AWD									
2	1	3.6			CADILLAC: (LDT 3751-5750 pounds LVW) SRX 2WD, SRX AWD									

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission, levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF= * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day											
STD STD		NMOG NMHC		NMHC STD	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
PC/LDT1 LDT2		LDT2	CERT CERT		[g/mi]	CO [g/mi]		NC	NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.03	0.035 0.043		[g/mi]	[g/mi]	[9,]	CERT	STD	CERT	STI) C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	*	*	*	*	*	*	•		*]	*	*	*	*	*	
		@ UL	0.049 (0.034)	*	0.070 (0.070)	0.6 (0.9)	2.1 (2.1)	0.02	0.0		1 (*)	11 (11)	*	0.01 (0.01)	0.02	0.05 (0.05)	
	@ 5	0°F & 4K	*	*	*	*	*	*			*	*	*	*	*	*	
CO [g/mi] SFTP 1 = @ @ 20°F & LEV)			9 4K (SULEV, ULEV, OF 50K (Tier 1, TLEV) (COMPO						NMHC+NOx [g/mi] [US06]		(O [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
			@ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CEI	RT ST	D CER	r STD	CERT	STD	
CERT	(2.0)		SF	TP @ 4K	*	*	*	*	(0.07)	(0.14)) (5.	1) (8.0	(0.02) (0.20)	(0.2)	(2.7)	
STD	(10.0)		SF	TP @ UL	(0.06)	* (0.63)	*	*	*	*	(5.	3) (11.	1) *	*	(0.4)	(3.7)	
@ UI	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2			EVAPORATIVE FAM			MILY 3	MILY 3 EV		APORATIVE FAMIL		
@ UL	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	0.25	0.30	0.000	(0.01)	0.38	0.26	0.000	(0.04)	*	*	*	*	*	*	*	*	
STD	0.50	0.65	0.05	(0.20)	0.65	0.85	0.05	(0.20)	*	* ,	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.



GENERAL MOTORS LLC

EXECUTIVE ORDER A-006-1766 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_day of May 2011

Annette Hebert, Chief

Mobile Source Operations Division