

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mi		INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		FUEL TYPE
0040	0.011/1/02 4004	Descensor Cor	"LEV II" Super Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2 Unleaded) plus
2012	CGMXV02.4061	Passenger Car	SULEV)	150K 150K		*	*	Battery-Assist
No.	ECS & S	PECIAL FEATURES	EVAPORATIVE	EVAPORATIVE FAMILY (EVAF)				
1	TWC(2), HO2	2S(2), DGI, AIR, OBD(P)	CGMXRC					
*			*			2.4		
* *			*	2404	2.4			
*	and the second second	*	*	*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust, the evaporative emission standards, and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50[°] Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962.1 (c)(2).

California Environmental Protection Agency

EXECUTIVE ORDER A-006-1754

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

day of June 2011.

Annette Hebert, Chief Mobile Source Operations Division

California Environmental Protection Agency

EXECUTIVE ORDER A-006-1754

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

CERT			NMHC	NMOG or NMHC STD	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [gt/est]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure											
	0.005	CERT	CERT	[g/mi]	CO [g/mi]			NOx [g/mi]		HO [mg		PM [g/mi]		Hwy NOx [g/mi]		
0.028	0.035	[g/mi]	[g/mi]		CERT	STD	CERT	STD	CER		*	CERT	STD *	CERT	STD *	
	@ 50K	*	*	*	*	*	*	*				*		0.003	0.03	
	@ UL	0.009	*	0.010	0.9	1.0	0.02	0.02			4.	*	0.01	0.003	0.03	
(@ 50°F & 4K	0.011	*	0.020	0.9	1.0	0.01	0.02			8.					
CO [g/mi]				NMHC+NC (comp			j/mi] osite)	NMHC+N [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
	F & 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER			STD	
CERT	2.4	SFTP @ 4	000 miles	*	*	*	*	0.04	0.14	3.1	8.0	0.02		0.9	2.7	
STD	10.0		@* miles	*	*	*	*	*	*	*	*	*	*	*	*	
Evaporative Family (gra			iurnal + Ho ns/test) @ l		2-Days Diu (grams	urnal + Ho s/test) @ l		Running Lo (grams/mile) (
			CERT	S	TD	CERT	S	TD	CER	CERT		TD CI				
CGMXR0123702		0.26	0.35		0.22	0	.35	0.000		0.05			0.01 0.20			
*		*		*	*	*		*		*		*		*		
		*	-	* *			*	*				*		*		
	*					* *			*		*		*		*	
* - not a		=useful life	* PC=passe		* DT=light-	duby truck:	MDV=m	* edium-du	ty vehicle	e; ECS=	emissio	n control	system: S	STD= stand	ard;	
CERT= way/oxid urea/am HO2S=h AIR=sec	* applicable; UL certification; dizing catalysi monia; NH3C heated O2S; / condary air in er; OBD (F)/(I ssed/liquefied	LVW=loade t; ADSTWC DC=SCR-U AFS/HAFS jection; PA	 c; PC=passed d vehicle w =adsorbing /SCR-N am =air- fuel ra IR=pulsed / artial/both c s; LPG=liq	enger car; L reight; ALV TWC; WU monia slip tio sensor / AIR; SFI/MI on-board dia uefied petro	.DT=light- W=adjuste =warm-up catalyst; C heated A FI= sequen agnostic; pleum gas	-duty truck; ed LVW; Li c catalyst; I CTOX/PTO .FS; NOXS ntia/ multip DOR=dire s; E85="85	MDV=me EV=low er NAC=NOx X= contin S= NOx se ort fuel inj ct ozone r %" Ethance	edium-du mission vo adsorpti uous/peri nsor; RD ection; D educing; ol ("15%"(ty vehicle ehicle; U on cataly odic trap QS=urea FI=direc prefix 2= gasoline	st; SCR oxidizer quality t fuel inje parallel; Fuel;	emissio ra LEV; -U/SCR- - ; HO2S/ sensor; ection; T (2) suffi:	N= selec O2S=he EGR=ex C/SC= tr x=series;	system; S super ULI tive cataly ated/oxyg naust gas urbo/supe	ytic reductic en sensor; recirculatio r charger; C	ard; C=3- n- n:	
CERT= way/oxid urea/am HO2S=h AIR=sec	applicable; UL certification; dizing catalyst monia; NH3C heated O2S; condary air in	LVW=loade t; ADSTWC DC=SCR-U AFS/HAFS jection; PA	 c; PC=passed d vehicle w =adsorbing /SCR-N am =air- fuel ra IR=pulsed / artial/both c s; LPG=liq	enger car; L reight; ALV TWC; WU Imonia slip tio sensor / AIR; SFI/MI	.DT=light- W=adjuste =warm-up catalyst; C heated A FI= sequen agnostic; pleum gas	-duty truck; ed LVW; Li c catalyst; I CTOX/PTO .FS; NOXS ntia/ multip DOR=dire s; E85="85	MDV=me EV=low er NAC=NOx X= contin S= NOx se ort fuel inj ct ozone r %" Ethance	edium-du mission vo adsorpti uous/peri nsor; RD ection; D educing; ol ("15%"(ty vehicle ehicle; U on cataly odic trap QS=urea FI=direc prefix 2= gasoline	st; SCR oxidizer quality t fuel inje parallel; Fuel;	emissio ra LEV; : -U/SCR- - - - - - - - - - - - - - - - - - -	N= select O2S=hea EGR=ex C/SC= tr x=series;	system; S super ULI tive cataly ated/oxyg haust gas irbo/supe CNG/LN	ytic reductic en sensor; recirculatio r charger; C	ard; C=3- n- n:	
CERT= way/oxid urea/am HO2S=h AIR=sec air coole compres	applicable; UL certification; dizing catalyst monia; NH3C heated O2S; condary air in	LVW=loade t; ADSTWC DC=SCR-U AFS/HAFS jection; PA	PC=passe d vehicle w =adsorbing /SCR-N am =air- fuel ra R=pulsed / artial/both c s; LPG=liq 20	enger car; L reight; ALV TWC; WU monia slip tio sensor / AIR; SFI/MI on-board dia uefied petro	.DT=light- W=adjuste =warm-up catalyst; C heated A FI= sequen agnostic; pleum gas	duty truck; ed LVW; LI o catalyst; I CTOX/PTO FS; NOXS ntia/ multip DOR=dire ; E85="85 AR: VI	MDV=me EV=low er NAC=NOx X= contin S= NOx se ort fuel inj ct ozone r %" Ethance	edium-du mission vo adsorpti uous/peri nsor; RD ection; D educing; ol ("15%"(ty vehicle ehicle; U on cataly odic trap QS=ured FI=direc prefix 2= gasoline ELS IN	st; SCR oxidizer quality t fuel inje parallel; Fuel;	emissio ra LEV; ; HO2S/ sensor; T (2) suffi MATIC	N= selec O2S=he EGR=ex C/SC= tr x=series;	system; S super ULI tive catal; ated/oxyg naust gas rrbo/supe CNG/LN ATE CE -use; rap.	ytic reductic en sensor; recirculatio r charger; C	ard; C=3- n- n; AC=char	
CERT= way/oxid urea/am HO2S=h AIR=sec air coole compres	applicable; UL certification; ilizing catalysi imonia; NH3C heated O2S; / condary air in er; OBD (F)/(I ssed/liquefied	LVW=loade t; ADSTWC DC=SCR-U AFS/HAFS jection; PA	PC=passe d vehicle w =adsorbing /SCR-N am =air- fuel ra R=pulsed / artial/both c s; LPG=liq 20	enger car; L reight; ALV i TVVC; WU imonia slip tio sensor / AIR; SFI/MI on-board dia uefied petro 012 MOE	.DT=light- W=adjuste =warm-up catalyst; C heated A FI= sequen agnostic; pleum gas	duty truck; ed LVW; LI o catalyst; I CTOX/PTO FS; NOXS ntia/ multip DOR=dire ; E85="85 AR: VI	MDV=me EV=low er NAC=NOX SX= contin S= NOX se ort fuel inj ct ozone r %" Ethand EHICLE	edium-du nission vi a dasorpti uous/peri nsor; RD ection; D educing; ol ("15%" E MOD	ty vehicle ehicle; U on cataly odic trap QS=ured FI=direc prefix 2= gasoline ELS IN	vst; SCR oxidizer a quality t fuel inje parallel; Fuel; NFORI	emissio ra LEV; ; HO2S/ sensor; T (2) suffi MATIC	N= selec O2S=he: EGR=exl C/SC= tr x=series; DN ERMEDI IN-USE DMPLIAN IA or full in E=exh. / er rmediate in	system; S super ULI tive catal; ated/oxyg naust gas rrbo/supe CNG/LN ATE CE -use; rap.	ytic reductic en sensor; recirculatio r charger; C IG= PHASE-IN	ard; C=3- n- n:	
CERT= way/oxid urea/am HO2S=+ AIR=sec air coole compres	applicable; UL certification; ilizing catalysi imonia; NH3C heated O2S; / condary air in er; OBD (F)/(I ssed/liquefied	LVW=loade t; ADSTWC DC=SCR-U AFS/HAFS jection; PA	; PC=passe d vehicle w =adsorbing (%CR-N am =air- fuel ra R=pulsed / artial/both c s; LPG=liq 20	enger car; L reight; ALV i TVVC; WU imonia slip tio sensor / AIR; SFI/MI on-board dia uefied petro 012 MOE	.DT=light- W=adjuste =warm-up catalyst; C heated A FI= sequen agnostic; pleum gas	eduty truck; ed LVW; Ll cTOX/PTO FS; NOXS ntia/ multip DOR=dire ; E85="85 AR: VI EVAP4 FA	MDV=me EV=low er NAC=NOX SX= contin S= NOX se ort fuel inj ct ozone r %" Ethand EHICLE	edium-du mission vr a dasorpti uous/peri ensor; RD lection; D educing; ol ("15%"; E MOD	ty vehicle ehicle; U on cataly odic trap QS=urea FI=direc prefix 2= gasoline ELS IN	vst; SCR oxidizer a quality t fuel inje parallel; Fuel; NFORI	emissio ra LEV; ; -U/SCR- ; HO2S/ sensor; T ction; T (2) suffiz MATIC INT C(('=N A) inter	N= selec O2S=he: EGR=ex! (C/SC= tr x=series; DN IN-USE DMPLIAN /A or full in E=exh. / er mediate in H	system; S super ULI tive catal; ated/oxyg naust gas rrbo/supe CNG/LN ATE (CE I-use; rap. I-use; rap.	ytic reductic en sensor; recirculatio r charger; C IG= PHASE-IN	ard; C=3- n- n; AC=char	