## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1672 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP CFMXT05.44BC			VEHICLE TYPE (PC=passenger car; LDT=light-du MDV=medium-duty vehicle; LVW vehicle weight; GVW=gross	STANE (LEV=low of transitions	AUST EMISSION DARD CATEGORY emission vehicle; TLEV= al LEV; ULEV=ultra LEV; LEV=super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)  FUEL TYPE (CNG/LNG=compres liquefied natural g LPG=liquefied petro gas)						
201	2				LDT: 6001-8500# GVW; 5 8500# ALVW		USEPA Bin 4 nted as ARB LEV2 ULEV	120K / 150K	Flexible Fuel: Ethanol (E85)/Gasoline (Tier 2 Unleaded)					
No.	EVAPORATIVE FAMILY (EVAF)		No.	SPECIAL FEAT EMISSION CONTROL		(ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC						
1		CFMXR0265NBC 1			2TWC, 2HA	AFS, 2HO2	2S, SFI, OF	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
2					A THE PROPERTY OF									
3	-					*		THE SHIP S	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4						*	TIT ALL	diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.		ECS ENGI No. SIZE		77.0	VEHICLE MAKES & MODELS	STANE	HICLES SUBJECT TO SFTP ANDARDS ARE UNDERLINED							
1		1	5.4		FORD: EXPEDITION FFV 2WD; EXPEDITION FFV 4WD; EXPEDITION EXT FFV 2WD; EXPEDITION EXT FFV 4WD									
1		1	1 5.4		LINCOLN: NAVIGATOR FFV 2WD; NAVIGATOR FFV 4WD; NAVIGATOR EXT FFV 2WD; NAVIGATOR EXT FFV 4WD									
	_			-										

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF= * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
CER	CERT STD		NMOG CERT [g/mi]	NMHC CERT [g/mi]	NMHC STD [g/mi]	mg=millig	ram mi=	mile K=10	000 miles	F=c	degrees	Fahrenhe [mg/mi	it SF	TP=supple PM [g/	emental fed	eral test pr Hwy NO	oceaure	
0.029		0.043				CERT	[g/mi] STD	CERT	x [g/mi] STD		CERT	STE		ERT	STD	CERT	STD	
		@ 50K *		*	*	*	*		*		*	*		*	*	*	*	
		@ UL	0.032 (0.038)	*	0.070 (0.070)	0.9 (1.4)	2.1 (2.1)	0.01	0.04		1 (*)	11 (11		*	0.01 (0.01)	0.005 (0.003)	0.05 (0.05)	
	@ 5	50°F & 4K	-	*	*	*	*				*	*		*	*	*	*	
CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/mi] (composite)			NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
					CERT	STD	CERT	STD	CERT	STI	D C	ERT	STD	CERT	STD	CERT	STD	
CERT	(3.5)		SF	TP @ 4K	*	*	*	*	(0.02)	(0.6		0.6)	* (11.8)	(0.02)	(0.44)	(1.0)	(4.0)	
STD	* (12.5)		SF	TP @ UL	(0.03)	(1.40)	*	*	*	*	(	* 0.8)	* (19.3)	*		(1.2)	(6.4)	
@ UL		VAPORAT	IVE FAM	ILY 1	EVA	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				3	EVAPORATIVE FAMILY 4				
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	F	RL (	ORVR	3-D	2-D	RL	ORVR	
CERT	0.37	0.53	0.001	0.05	*	*	*	*	*	*		*	*	*	*	*	*	
STD	0.90	1.15	0.05	0.20	*	*	*	*	*	*		*	*	1.00	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1672 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, a

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division