FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1706 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD					VEHICLE TYPE (PC=passenger car; LDT=light-du MDV=medium-duty vehicle; LVW vehicle weight; GVW=gross	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles) FUEL TYPE (CNG/LNG=compress liquefied natural ga LPG=liquefied petrologas)						
201	3	DFMX	(T02.02E	С	LDT: <6000# GVW (3751-5750 6001-8500# GVW (3751-5750#		LEV II ULEV			120K / 150K	Gasoline (Tier 2 Unleaded)				
No.		VAPORATIVE AMILY (EVAF)			SPECIAL FEAT EMISSION CONTROL S					TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U/SCR-N= selective catalytic reduction-urea/ammonia;					
1	DFM	DFMXR0145GBB			TWC, AFS,HO	TWC, AFS,HO2S, DFI, TC, CAC, OBD(P)					NH3OC=SCR-U/SCR-N ammonia slip catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; HO2S/O2S=heated/oxygen				
2	DFM	DFMXR0145GBV			Comparison to the property of the second of					sensor; AFS/HAFS=air- fuel ratio sensor / heated AFS; NOXS= NOx sensor; RDQS=reductant quality sensor; EGR=exhaust gas recirculation; EGRC=cooled EGR; AIR=secondary air injection;					
3		*													
4		*									PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger;				
5		*								CAC=charge air cooler; OBD (F)/(P)/(B)= full/partial/both on-boar diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2)					
6		*			1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1						suffix=series;				
EVA No.		ECS No.	ENGINE SIZE (L)		VEHICLE MAKES & MODELS			JECT TO SFTP RE <u>UNDERLINED</u>	ABBREVIATIONS:						
1		1	2.0	*		FORD: (LDT 3751-5750# LVW) <u>EDGE FWD</u>									
2		1 2.0			1000 100 TOPP 100	FORD: (LDT 3751-5750# ALVW) EXPLORER FWD									
*		* *					•								

That the exhaust, the evaporative emission standards, and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *					NMOG or	nitrogen diurnal+h	HCHO=fo ot-soak R	rmaldehyde L [g/mi]=run	PM=part ining loss	ORVR	matter [g/gallo:	RAF=reacti n dispensed	vity adjustn]=on-board	carbon mono nent factor refueling var	2/3 D [g/test or recovery]=2/3 day g=gram	
CERT		STD	NMOG	NMHC	NMHC STD				1000 miles F=degrees I Dx [g/mi] HCHO		[mg/mi]	SFTP=supplemental fe PM [g/mi]		Hwy NOx [g/mi]			
0.040	0	0.043	CERT [g/mi]	CERT [g/mi]	[g/mi]	CERT	STD	CERT		A STATE OF THE PARTY OF THE PAR	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.020	*	0.040	0.9	1.7	0.04	0.08	5	*	8.	*	*	0.01	0.07	
		@ UL	0.022	*	0.055	1.0	2.1	0.05	0.07	7	*	11.	*	0.01	0.03	0.09	
	@ 50	°F & 4K	*	*	*		*	*	*		*	*	*	*	*	*	
CO [d	a/mi]	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/mi] (composite)				NMHC+NOx CO [g/mi] [g/mi] [US06] [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
@ 20°F	& 50K	SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT S1	D CER	RT STD	CERT	STD		
CERT	1.7		SF	TP @ 4K	*	*	*	*	0.03	0.25	2	2.1 10	.5 0.0	6 0.27	0.8	3.5	
STD	12.5		SF	TP @ UL	*	*	*	*	*	*		*	*	*	*	*	
	EVAPORATIVE FAMILY 1				EVA	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3					EVAPORATIVE FAMILY 4			
@ UL	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L OR\	/R 3-D	2-D	RL	ORVR	
CERT	0.22	*	0.000	0.02	0.26	0.19	0.000	0.03	*	*		*	*	*	*	*	
STD	065	0.85	0.05	0.20	0.90	1.15	0.05	0.20	*	*		* *	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV):

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1706 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 20 day of January 2012.

wolf

Annette Hebert, Chief

Mobile Source Operations Division